




2.0A Sintered Glass Passivated Super Fast Rectifier

EGF2A - EGF2K

2.0A Sintered Glass Passivated Super Fast Rectifier

Features

- Sintered glass passivated (SGP) rectifier chip
- Glass passivated cavity-free junction
- Ideal for surface mount automotive applications
- Built-in strain relief
- Easy pick and place
- High temperature soldering guaranteed: 250°C/10 seconds, at terminals
- RoHS Compliance



SMB



Mechanical Data

Case:	JEDEC DO-214AA(SMB) molded plastic over passivated chip
Epoxy:	Plastic package has UL flammability classification 94V-0
Terminals:	Solder plated, solderable per MIL-STD-750, Method 2026
Polarity:	Color band denotes cathode end
Weight:	0.003 ounce, 0.093 gram

Maximum Ratings and Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless noted otherwise)

Symbol	Description	EGF2A	EGF2B	EGF2D	EGF2G	EGF2J	EGF2K	Unit	Conditions
V_{RRM}	Maximum Repetitive Peak Reverse Voltage	50	100	200	400	600	800	V	
V_{RMS}	Maximum RMS Voltage	35	70	140	280	420	560	V	
V_{DC}	Maximum DC Blocking Voltage	50	100	200	400	600	800	V	
I_{F(AV)}	Maximum Average Forward Rectified Current	2.0						A	T _L =110° C
I_{FSM}	Peak Forward Surge Current	65				60		A	8.3ms single half sine-wave superimposed on rated load (JEDEC Method)

2.0A Sintered Glass Passivated Super Fast Rectifier

EGF2A - EGF2K

Symbol	Description	EGF2A	EGF2B	EGF2D	EGF2G	EGF2J	EGF2K	Unit	Conditions
V _F	Maximum Instantaneous Forward Voltage	0.95			1.25	1.7	2.2	V	I _F =2.0 A
I _R	Maximum DC Reverse Current at Rated DC Blocking Voltage	5.0						μA	T _A =25° C
		100							T _A =125° C
T _{rr}	Maximum Reverse Recovery Time	35						nS	I _F =0.5A, I _R =1.0A, I _{rr} =0.25A
C _J	Typical Junction Capacitance	25						pF	V _R =4V, f=1MHz
R _{thJA}	Typical Thermal Resistance	20						°C / W	Note
T _J ,T _{STG}	Operating junction and Storage Temperature Range	-55 to +175						° C	

Note: Thermal resistance from junction to ambient P.C.B mounted on 0.2x0.2" (5.0x5.0mm) copper pad areas.

Typical Characteristics Curves

Fig.1- Forward Current Derating Curve





Fig.2-Max. Non-Repetitive Forward Surge Current



2.0A Sintered Glass Passivated Super Fast Rectifier

EGF2A - EGF2K

Fig.3- Typical Instantaneous Forward Characteristics




Fig.4-Typical Reverse Characteristics






Fig.5- Typical Junction Capacitance



2.0A Sintered Glass Passivated Super Fast Rectifier


EGF2A - EGF2K

Dimensions in inch (mm)



SMB

Mounting Pad Layout in inch (mm)



2.0A Sintered Glass Passivated Super Fast Rectifier

EGF2A - EGF2K

How to contact us:

US HEADQUARTERS

28040 WEST HARRISON PARKWAY, VALENCIA, CA 91355-4162

Tel: (800) TAITRON (800) 824-8766 (661) 257-6060

Fax: (800) TAITFAX (800) 824-8329 (661) 257-6415

Email: taitron@taitroncomponents.com

Http://www.taitroncomponents.com

TAITRON COMPONENTS MEXICO, S.A .DE C.V.

BOULEVARD CENTRAL 5000 INTERIOR 5 PARQUE INDUSTRIAL ATITALAQUIA, HIDALGO C.P.
42970 MEXICO

Tel: +52-55-5560-1519

Fax: +52-55-5560-2190

TAITRON COMPONENTS INCORPORATED E REPRESENTAÇÕES DO BRASIL LTDA

RUA DOMINGOS DE MORAIS, 2777, 2.ANDAR, SALA 24 SAÚDE - SÃO PAULO-SP 04035-001 BRAZIL

Tel: +55-11-5574-7949

Fax: +55-11-5572-0052

TAITRON COMPONENTS INCORPORATED, SHANGHAI REPRESENTATIVE OFFICE

METROBANK PLAZA, 1160 WEST YAN' AN ROAD, SUITE 1503, SHANGHAI, 200052, CHINA

Tel: +86-21-5424-9942

Fax: +86-21-5424-9931