

OUTPUT PENTODE

EL41

Output pentode rated for 9W anode dissipation, primarily intended for use in A.C. mains operated equipment.

HEATER

V_h	6.3	V
I_h	0.7	A

MOUNTING POSITION

Any

CAPACITANCES

C_{out}	7.8	pF
C_{in}	10.2	pF
C_{a-g1}	<1.0	pF
C_{g1-h}	<0.15	pF

CHARACTERISTICS

V_a	250	V
V_{g2}	250	V
I_a	36	mA
I_{g2}	5.2	mA
V_{g1}	-7	V
g_m	10	mA/V
r_a	40	k Ω
μ_{g1-g2}	22	

OPERATING CONDITIONS AS SINGLE VALVE CLASS "A" AMPLIFIER

Pentode connection

V_a	250	V
V_{g2}	250	V
V_{g1}	-7	V
R_k	170	Ω
I_a	36	mA
I_{g2}	5.2	mA
R_a	7	k Ω
V_{in} (r.m.s.) ($P_{out}=50mW$)	0.32	V
P_{out} ($D_{tot}=10\%$)	4.2	W
V_{in} (r.m.s.) ($D_{tot}=10\%$)	3.7	V
P_{out} ($\eta=50\%$)	4.5	W
V_{in} (r.m.s.) ($P_{out}=4.5W$)	4.0	V
D_{tot} ($P_{out}=4.5W$)	11.5	%

OPERATING CONDITIONS AS SINGLE VALVE CLASS "A" AMPLIFIER

Triode connection (g_2 connected to a)

V_a	250	V
R_k	250	Ω
R_a	3.5	k Ω
I_a	33	mA
P_{out}	1.55	W
V_{in} (r.m.s.)	6	V
D_{tot}	8	%



Output pentode rated for 9W anode dissipation, primarily intended for use in A.C. mains operated equipment.

OPERATING CONDITIONS FOR TWO VALVES IN PUSH-PULL

Pentode connection

V_a	250	300	V
V_{g2}	250	300	V
$I_{B(O)}$	2×25	2×30	mA
I_B (max. sig.)	2×30	2×36	mA
$I_{g2(O)}$	2×3.5	2×4	mA
I_{g2} (max. sig.)	2×8	2×9.5	mA
R_k	140	140	Ω
R_{a-a}	9	9	k Ω
P_{out}	9	13	W
$V_{in (g-g)}$ (r.m.s.)	14	17	V
D_{tot}	2.5	2.5	%

OPERATING CONDITIONS FOR TWO VALVES IN PUSH-PULL

Triode connection (g_2 connected to a)

V_a	250	300	V
$I_{B(O)}$	2×27.5	2×33	mA
R_k	150	150	Ω
R_{a-a}	10	10	k Ω
P_{out}	2.5	4	W
$V_{in (g-g)}$ (r.m.s.)	5.4	6.7	V
D_{tot}	1	1	%


LIMITING VALUES

V_a (b) max.	550	V
V_a max.	300	V
p_a max.	9	W
V_{g2} (b) max.	550	V
V_{g2} max.	300	V
p_{g2} (zero sig.) max.	1.4	W
p_{g2} (max. sig.) max.	3.3	W
I_k max.	55	mA
V_{g1} max. ($I_{g1} = +0.3 \mu A$)	-1.3	V
R_{g1-k} max.	1	M Ω
V_{h-k} max.	50	V
R_{h-k} max.	20	k Ω

OUTPUT PENTODE

EL41


Output pentode rated for 9W anode dissipation, primarily intended for use in A.C. mains operated equipment.



EL41

OUTPUT PENTODE

Output pentode rated for 9W anode dissipation, primarily intended for use in A.C. mains operated equipment.



ANODE CURRENT PLOTTED AGAINST ANODE VOLTS