




OUTPUT PENTODE  
PENTHODE DE SORTIE  
ENDPENTODE\*

Heating: indirect by A.C. or D.C.;  
parallel supply  
Chauffage: indirect par C.A. ou C.C.;  $V_f = 6,3 \text{ V}$   
alimentation en parallèle  $I_f = 1,9 \text{ A}$   
Heizung: indirekt durch Wechsel- oder  
Gleichstrom; Parallelspeisung

Dimensions in mm  
Dimensions en mm  
Abmessungen in mm



Base, culot, Sockel: P

Capacitances  
Capacités  
Kapazitäten

$C_{ag1} < 1,5 \text{ pF}$

Typical characteristics  
Caractéristiques types  
Kenndaten

$V_a$	=	500	750	V
$V_{g2}$	=	500	750	V
$V_{g1}$	=	-20	-37,5	V
$I_a$	=	87	60	mA
$I_{g2}$	=	13	10	mA
S	=	11	8	mA/V
$\mu_{g2g1}$	=	16,5	16,5	-
$R_1$	=	33	50	k $\Omega$

Operating characteristics  
 Caractéristiques d'utilisation  
 Betriebsdaten

	class B classe B Klasse B		class AB classe AB Klasse AB		
$V_a$	=	750	500		V
$V_{g2}$	=	750	500		V
$V_{g1}$	=	-40	-		V
$R_k$	=	-	100		$\Omega$
$R_{aa}$	=	6	4,8		k $\Omega$
$R_{g2}$	=	1)	-		-
$V_i$	=	0	28,5	0	19 V <sub>eff.</sub>
$I_a$	=	2x40	2x145	2x87	2x110 mA
$I_{g2}$	=	2x7,5	2x30	2x13	2x23 mA
$W_o$	=	0	140	0	67,5 W
$d_{tot}$	=	-	5	-	5 %

Limiting values  
 Caractéristiques limites  
 Grenzdaten

$V_{ao}$	= max.	1500 V
$V_a$	= max.	750 V
$W_a$	= max.	45 W
$V_{g2o}$	= max.	1500 V
$V_{g2}$	= max.	750 V
$W_{g2} (V_i = 0)$	= max.	7 W
$W_{g2} (W_o = \text{max.})$	= max.	25 W
$I_k$	= max.	200 mA
$V_{g1} (I_{g1} = +0,3 \mu\text{A})$	= max.	-1,3 V
$R_{g1} (A, B)$	= max.	0,35 M $\Omega$
$R_{g1} (AB)$	= max.	0,7 M $\Omega$
$V_{fk}$	= max.	50 V
$R_{fk}$	= max.	20 k $\Omega$

1) Incandescent lamp of 550 V/68 W  
 Lampe à incandescence de 550 V/68 W  
 Glühlampe von 550 V/68 W

**PHILIPS**



*Electronic  
Tube*

**HANDBOOK**

<b>page</b>	<b>EL51 sheet</b>	<b>date</b>
1	1	1953.04.04
2	2	1953.04.04
3	FP	1999.07.04