

# Single P-channel MOSFET

## ELM13401CA-S

### ■ General description

ELM13401CA-S uses advanced trench technology to provide excellent  $R_{ds(on)}$ , low gate charge and low gate resistance.

### ■ Features

- $V_{ds} = -30V$
- $I_d = -4.2A$  ( $V_{gs} = -10V$ )
- $R_{ds(on)} < 50m\Omega$  ( $V_{gs} = -10V$ )
- $R_{ds(on)} < 65m\Omega$  ( $V_{gs} = -4.5V$ )
- $R_{ds(on)} < 120m\Omega$  ( $V_{gs} = -2.5V$ )

### ■ Maximum absolute ratings

$T_a = 25^\circ C$ . Unless otherwise noted.


Parameter	Symbol	Limit	Unit	Note	
Drain-source voltage	$V_{ds}$	-30	V		
Gate-source voltage	$V_{gs}$	$\pm 12$	V		
Continuous drain current	$I_d$	$T_a = 25^\circ C$	-4.2	A	1
		$T_a = 70^\circ C$	-3.5		
Pulsed drain current	$I_{dm}$	-30	A	2	
Power dissipation	$P_d$	$T_c = 25^\circ C$	1.4	W	1
		$T_c = 70^\circ C$	1.0		
Junction and storage temperature range	$T_j, T_{stg}$	-55 to 150	$^\circ C$		

### ■ Thermal characteristics

Parameter	Symbol	Typ.	Max.	Unit	Note
Maximum junction-to-ambient	$R\theta_{ja}$	65	90	$^\circ C/W$	1
Maximum junction-to-ambient		Steady-state	85	125	
Maximum junction-to-lead	$R\theta_{jl}$	43	60	$^\circ C/W$	3


### ■ Pin configuration

SOT-23(TOP VIEW)



Pin No.	Pin name
1	GATE
2	SOURCE
3	DRAIN

### ■ Circuit



# Single P-channel MOSFET

## ELM13401CA-S

### ■ Electrical characteristics

Ta=25°C. Unless otherwise noted.

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
<b>STATIC PARAMETERS</b>						
Drain-source breakdown voltage	BVdss	Id=-250μA, Vgs=0V	-30			V
Zero gate voltage drain current	Idss	Vds=-24V			-1	μA
		Vgs=0V		Ta=55°C	-5	
Gate-body leakage current	Igss	Vds=0V, Vgs=±12V			±100	nA
Gate threshold voltage	Vgs(th)	Vds=Vgs, Id=-250μA	-0.7	-1.0	-1.3	V
On state drain current	Id(on)	Vgs=-4.5V, Vds=-5V	-25			A
Static drain-source on-resistance	Rds(on)	Vgs=-10V		42	50	mΩ
		Id=-4.2A			75	
			Ta=125°C			
		Vgs=-4.5V, Id=-4A		53	65	mΩ
		Vgs=-2.5V, Id=-1A		80	120	mΩ
Forward transconductance	Gfs	Vds=-5V, Id=-5A	7	11		S
Diode forward voltage	Vsd	Is=-1A, Vgs=0V		-0.75	-1.00	V
Max. body-diode continuous current	Is				-2.2	A
<b>DYNAMIC PARAMETERS</b>						
Input capacitance	Ciss			954		pF
Output capacitance	Coss	Vgs=0V, Vds=-15V, f=1MHz		115		pF
Reverse transfer capacitance	Crss			77		pF
Gate resistance	Rg	Vgs=0V, Vds=0V, f=1MHz		6		Ω
<b>SWITCHING PARAMETERS</b>						
Total gate charge	Qg	Vgs=-4.5V, Vds=-15V		9.4		nC
Gate-source charge	Qgs	Id=-4A		2.0		nC
Gate-drain charge	Qgd			3.0		nC
Turn-on delay time	td(on)			6.3		ns
Turn-on rise time	tr	Vgs=-10V, Vds=-15V		3.2		ns
Turn-off delay time	td(off)	RL=3.6Ω, Rgen=6Ω		38.2		ns
Turn-off fall time	tf			12.0		ns
Body diode reverse recovery time	trr	If=-4A, dIf/dt=100A/μs		20.2		ns
Body diode reverse recovery charge	Qrr	If=-4A, dIf/dt=100A/μs		11.2		nC

#### NOTE :

1. The value of Rθja is measured with the device mounted on 1in<sup>2</sup> FR-4 board of 2oz. Copper, in still air environment with Ta=25°C. The value in any given applications depends on the user's specific board design, The current rating is based on the t ≤ 10s thermal resistance rating.
2. Repetitive rating, pulse width limited by junction temperature.
3. The Rθja is the sum of the thermal impedance from junction to lead Rθjl and lead to ambient.
4. The static characteristics in Figures 1 to 6 are obtained using 80μs pulses, duty cycle 0.5%max.
5. These tests are performed with the device mounted on 1in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with Ta=25°C. The SOA curve provides a single pulse rating.

# Single P-channel MOSFET

## ELM13401CA-S

### ■ Typical electrical and thermal characteristics




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

# Single P-channel MOSFET

## ELM13401CA-S




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note 5)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note 5)




Figure 11: Normalized Maximum Transient Thermal Impedance