

Green mode PWM Flyback Controller

General Description

EM8631 is a high performance, low startup current, low cost, current mode PWM controller with green mode power saving. The EM8631 integrates functions of Soft Start(SS), Under Voltage Lockout(UVLO), Leading Edge Blanking(LEB), internal Over Temperature Protection(OTP), internal slope compensation. The EM8631 also features more protection like Over Load Protection(OLP) and Over Voltage Protection(OVP) to prevent circuit damage occurred under abnormal conditions.

The EM8631 provides the users a superior AC/DC power application of high efficiency, excellent EMI performance, low external component counts and lower cost solution.

Features

- Ultra Low Start Up Current (6uA)
- Current Mode Control
- Soft Start Function
- Built-in Slope Compensation
- Internal Leading-edge Blanking
- UVLO
- Over Voltage Protection (OVP) on VDD pin
- Over Load Protection (OLP)
- Cycle-by-cycle Current Limit
- Feedback Open Protection
- Internal Over Temperature Protection (OTP)
- Constant Output Power Limit (Full AC Input Range)
- Excellent EMI performance




Ordering Information

Part Number	Package	Remark
EM8631J	SOT-23-6	
EM8631S	DIP-8	


Applications

- Switching AC/DC Adaptor and charger
- Open-Frame SMPS

Typical Application Circuit




Pin Configuration



Pin Assignment

Pin Name	Pin Number		Pin Function
	SOT236	DIP8	
GND	1	8	Ground.
COMP	2	7	Voltage feedback pin. By connecting a photo-coupler to close the control loop and achieve the regulation.
RT	3	5	Set the switching frequency by connecting a resistor to GND.
CS	4	4	Senses the primary current.
VDD	5	2	IC Power Supply Pin.
GATE	6	1	Gate drive output to drive the external MOSFET.
NC	--	3 & 6	No Internal Connection.

Function Block Diagram



Absolute Maximum Ratings (Note1)

- Supply Input Voltage, VDD ----- 30V
- Gate pin----- 30V
- RT, COMP, CS Pin ----- - 0.3V to 6.5V
- Power Dissipation, PD @ TA = 25°C
 - SOT-23-6 ----- 0.4W
 - DIP-8 ----- 0.714W
- Package Thermal Resistance
 - SOT-23-6 ----- 250°C/W
 - DIP-8 ----- 140°C/W
- Junction Temperature ----- 150°C
- Lead Temperature (Soldering, 10 sec.) ----- 260°C
- Storage Temperature Range ----- -65°C to 150°C
- ESD Susceptibility (Note2)
 - HBM (Human Body Mode) ----- 3KV
 - MM (Machine Mode) ----- 300V
- Gate Output Current----- 300mA

Recommended Operating Conditions (Note3)

- Supply Input Voltage, VDD ----- 11V to 26V
- Operating Frequency ----- 50k to 130kHz
- Junction Temperature Range----- -40°C to 125°C
- Ambient Temperature Range----- -40°C to 85°C

Electrical Characteristics

(V_{DD}=15V, R_{RT}=100K ohm, T_A=25°C, unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Units
VDD Section						
VDD OVP Protect voltage	V _{OVP}		26.5	28	29.6	V
Start up current	I _{START1}	VDD=7V	-	1	2	uA
	I _{START2}	VDD= V _{TH-ON} -0.5V	-	6	12	uA
VDD On Threshold Voltage	V _{TH-ON}		13.5	15	16.5	V
VDD Off Threshold Voltage	V _{TH-OFF}		8.8	9.8	10.8	V
Operating Supply Current 1	I _{DD-OP1}	VDD=15V, V _{COMP} =0V,	-	2	3	mA
Operating Supply Current 2	I _{DD-OP2}	VDD=15V, V _{COMP} =3V, C _{GATE} =1nF	-	2.5	-	mA
Operating Supply Current 3	I _{DD-OP3}	VDD=15V, Protection triggerred	-	0.4	-	mA

Gate Section						
Rising Time	T_R	$C_L = 1nF$	-	150	200	nS
Falling Time	T_F	$C_L = 1nF$	-	30	100	nS
Current-Sense Section						
Maximum Internal Current Setpoint	V_{CSLim}		0.8	0.85	0.9	V
Leading Edge Blanking Time	T_{LEB}		200	300	400	nS
Propagation Delay Time	T_{PD}			100		nS
Soft-Start Period	T_{SS}			2		mS
Internal Oscillator						
Oscillation Frequency	f_{OSC}	$R_{RT}=100K\ ohm$	60	65	70	KHz
Maximum Duty	D_{max}	$V_{COMP}=3V, V_{CS}=0V$		75		%
Green mode minimum frequency				22		KHz
Frequency variation vs. VDD		VDD=11V to 25V			3	%
Frequency variation vs. Temperature		-20°C to 105°C (Note4)			3	%
COMP Section						
COMP short to GND current	I_{COMP}	$V_{COMP}=0V$		1.5	2.2	mA
Open loop COMP voltage	V_{COMP}	COMP pin open		5.2		V
Green mode COMP Threshold Voltage	V_{Green}			2.3		V
Protection Section						
Open loop protection delay time	T_{delay}			56		mS
Open loop protection COMP Trip voltage	V_{OLP}			4.8		V
Internal Temperature Shutdown	T_{SD}			160		°C

Note 1. Stresses listed as the above “Absolute Maximum Ratings” may cause permanent damage to the device. These are for stress ratings. Functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may remain possibility to affect device reliability.

Note 2. Devices are ESD sensitive. Handling precaution is recommended.

Note 3. The device is not guaranteed to function outside its operating conditions.

Note 4. Guaranteed by design.




Fig1. UVLO (on) vs. Temperature




Fig2. UVLO (off) vs. Temperature




Fig3. Frequency vs. Temperature.




Fig4. Green Mode Frequency vs. Temperature.




Fig5. V_{CSLIM} vs. Temperature.




Fig6. Start Up Current vs. Temperature.




Fig7. OVP vs. Temperature.




Fig8. V_{OLP-Trip} vs. Temperature.




Fig9. Comp Open Voltage vs. Temperature.




Fig10. Start Up Current vs. VDD

Functional Description

UVLO

An UVLO comparator is implemented in EM8631 to monitor the VDD pin voltage. As shown in Fig. 11, a hysteresis is built in to prevent the shutdown from the voltage drop during startup. The UVLO (on) and UVLO (off) are setting at 15V and 9.8V, respectively.




Fig. 11

Startup Operation

Fig. 12 shows a typical startup circuit and transformer auxiliary winding for the EM8631 application, it consumes only startup current (typical 6uA) and the current supplied through the startup resistor charges the VDD capacitor (C_{VDD}). When VDD reaches UVLO (on) voltage, EM8631 begins switching and the current consumed increases to 2mA. Then, the power required is supplied from the transformer auxiliary winding. The hysteresis of UVLO (off) provides more holdup time, which allows using a small capacitor for VDD. The ultra low startup current (typical 6uA) allow system using higher resistance value of R_{Start} . It provides a fast startup and low power dissipation solution.




Fig. 12

Switching Frequency

To guarantee accurate frequency, EM8631 is trimmed to 5% tolerance. The internal oscillator also generates slope compensation, 75% maximum duty limit. Connect a resistor from RT pin to GND according to equation below to program the switching frequency:

$$f_{sw} \text{ (KHz)} = 6500 / RT \text{ (K}\Omega\text{)}$$

Leading Edge Blanking (LEB)

Each time the power MOSFET turn on, the MOSFET C_{OSS} , secondary rectifier reverse recovery current and gate driver sourcing current comprise the current spike. To avoid premature termination of the switching pulse, a leading edge blanking time is built in. During the blanking time (300nS), the PWM comparator is off and cannot switch off the gate driver. It is recommended to adopt a smaller R-C filter (as show ad Fig.13) for high power application to avoid the total spike width over 300nS leading edge blanking time.




Fig. 13

Soft Start

The EM8631 has an internal soft-start circuit that increases cycle-by-cycle current limit comparator inverting input voltage slowly after it starts. The typical soft-start time is 2mS. The pulse width to the power MOSFET is progressively increased to establish the correct working conditions for transformers, rectifier diodes and capacitors. The voltage on the output capacitors is progressively increased with the intention of smoothly establishing the required output voltage. It also helps prevent transformer saturation and reduces the stress on the secondary diode during startup.

Slope compensation

In the conventional application, the problem of the stability is a critical issue for current mode controlling, when it operates in high than 50% of the duty cycle. The EM8631 built in saw-tooth slope compensation. So it requires no extra component.

Burst Mode Operation

At no load or light load condition, majority of the power dissipation in switching power supply is from switching loss on the power MOSFET, the core loss of the transformer and the loss on the snubber. The magnitude of power loss is in proportion to the number of switching events within a fixed period of time. Reducing switching events leads reduction on the power loss and

conserves the energy.

The EM8631 adjusts the switching mode according to the load condition, the COMP pin voltage drops below burst mode threshold level. Device enters Burst Mode Control. The Gate drive output remains at off state to minimize the switching loss and reduces the standby power consumption.

Protection

The EM8631 provides many protection functions that intend to protect system from being damaged. All the protection functions are listed as below:

● Cycle-by-cycle current limit

The EM8631 has over-current protection thresholds (0.85V). It is for cycle-by-cycle current limit, which turns off MOSFET for the remainder of the switching cycle when the sensing voltage of MOSFET current reaches the threshold.

● Over-load / Open-loop Protection (OLP)

When feedback loop is open, as shown in Fig. 14, no current flows through the opto-coupler transistor, the EM8631 pulls up the COMP pin voltage to 5.2V.

When the COMP pin voltage is above 4.8V longer than 56mS, OLP is triggered. This protection is also triggered when the SMPS output drops below the normal value longer than 56mS due to the overload condition.




Fig. 14

● **Over Voltage Protection (OVP) on VDD**

The V_{GS} ratings of the HV power MOSFETs are often limited up to max 30V. To prevent the V_{GS} from the fault condition, the EM8631 are implemented a Over-Voltage-Protection (OVP) on VDD. Whenever the VDD voltage is high than the OVP threshold voltage (28V), the output gate drive will be shutdown to stop the switching of the power MOSFET until the next UVLO (on).

The Over-Voltage-Protection on VDD function in EM8631 is an auto-restart type protection. If the OVP condition is not released, the VDD will tripped the OVP level again and re-shutdown the gate output. The VDD is working as a hiccup mode as shown in Fig. 15. On the other hand, if the OVP condition is removed, the VDD level will go back to normal level and the output will automatically return to the normal operation.




Fig. 15


● **Internal Over-Temperature Protection (OTP)**

Internal 130°C / 160°C hysteresis comparator will provide over temperature protection (OTP). OTP will not shutdown system. It stops the system from switching until the temperature is under 130°C. Meanwhile, if VDD is below the UVLO (off) threshold voltage, the system will hiccup.


● **Pin open / short Protection**

There are several open / short protections were integrated in the EM8631 to prevent the power supply or adapter from being damage. Under the conditions list below, the gate output will turn off to protect the system.


- RT pin short to GND
- RT pin open
- CS pin open
- COMP pin short to GND



Device Name: EM8631S for DIP-8




Outline Drawing



Dimension in mm

Dimension	A	A1	B	B1	b	C	D	e	F	G
Min.	0.90	0.00			0.30	0.08				0.30
Typ.	1.15		2.80	1.60			2.90	0.95		0.45
Max.	1.30	0.15			0.50	0.22			1.45	0.60



Dimension in mm

Dimension	A	A1	A2	B	B1	C	D	E	E1	EA	e	L
Min.		0.381	3.17				9.01	6.22	7.36	8.5		2.92
Typ.				1.524	0.457	0.254					2.54	
Max.	5.334		3.429				10.16	6.53	7.87	9.53		3.81