


N-Channel Logic Level Enhancement Mode Field Effect Transistor

Product Summary:

BV_{DSS}	30V
$R_{DS(on)}$ (MAX.)	11.5m Ω
I_D	25A



UIS, Rg 100% Tested

Pb-Free Lead Plating & Halogen Free



ABSOLUTE MAXIMUM RATINGS ($T_C = 25\text{ }^\circ\text{C}$ Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNIT
Gate-Source Voltage		V_{GS}	± 20	V
Continuous Drain Current	$T_C = 25\text{ }^\circ\text{C}$	I_D	25	A
	$T_C = 100\text{ }^\circ\text{C}$		20	
Pulsed Drain Current ¹		I_{DM}	100	
Avalanche Current		I_{AS}	30	
Avalanche Energy	$L = 0.1\text{mH}, I_D = 30\text{A}, R_G = 25\Omega$	E_{AS}	45	mJ
Repetitive Avalanche Energy ²	$L = 0.05\text{mH}$	E_{AR}	22.5	
Power Dissipation	$T_C = 25\text{ }^\circ\text{C}$	P_D	35	W
	$T_C = 100\text{ }^\circ\text{C}$		14	
Operating Junction & Storage Temperature Range		T_{j}, T_{stg}	-55 to 150	$^\circ\text{C}$

100% UIS testing in condition of $V_D = 15\text{V}, L = 0.1\text{mH}, V_G = 10\text{V}, I_L = 15\text{A}, \text{Rated } V_{DS} = 25\text{V N-CH}$

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNIT
Junction-to-Case	$R_{\theta JC}$		3.5	$^\circ\text{C} / \text{W}$
Junction-to-Ambient ³	$R_{\theta JA}$		62	

¹Pulse width limited by maximum junction temperature.

²Duty cycle $\leq 1\%$

³62 $^\circ\text{C} / \text{W}$ when mounted on a 1 in² pad of 2 oz copper.



ELECTRICAL CHARACTERISTICS ($T_c = 25^\circ\text{C}$, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	30			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	1	1.7	3	
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0V, V_{GS} = \pm 20V$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 24V, V_{GS} = 0V$			1	μA
		$V_{DS} = 20V, V_{GS} = 0V, T_J = 125^\circ\text{C}$			25	
On-State Drain Current ¹	$I_{D(ON)}$	$V_{DS} = 5V, V_{GS} = 10V$	25			A
Drain-Source On-State Resistance ¹	$R_{DS(ON)}$	$V_{GS} = 10V, I_D = 15A$		9.7	11.5	$m\Omega$
		$V_{GS} = 4.5V, I_D = 10A$		13	16	
Forward Transconductance ¹	g_{fs}	$V_{DS} = 5V, I_D = 15A$		15		S
DYNAMIC						
Input Capacitance	C_{iss}	$V_{GS} = 0V, V_{DS} = 15V, f = 1\text{MHz}$		1050		pF
Output Capacitance	C_{oss}			141		
Reverse Transfer Capacitance	C_{rss}			87		
Gate Resistance	R_g	$V_{GS} = 15\text{mV}, V_{DS} = 0V, f = 1\text{MHz}$		1.2		Ω
Total Gate Charge ^{1,2}	$Q_g(V_{GS}=10V)$	$V_{DS} = 15V, V_{GS} = 10V, I_D = 15A$		17.6		nC
	$Q_g(V_{GS}=4.5V)$			9.0		
Gate-Source Charge ^{1,2}	Q_{gs}			2.6		
Gate-Drain Charge ^{1,2}	Q_{gd}			4.0		
Turn-On Delay Time ^{1,2}	$t_{d(on)}$		$V_{DS} = 15V, I_D = 1A, V_{GS} = 10V, R_{GS} = 2.7\Omega$		8	
Rise Time ^{1,2}	t_r			8		
Turn-Off Delay Time ^{1,2}	$t_{d(off)}$			15		
Fall Time ^{1,2}	t_f			10		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS ($T_c = 25^\circ\text{C}$)						
Continuous Current	I_S				25	A
Pulsed Current ³	I_{SM}				100	
Forward Voltage ¹	V_{SD}	$I_F = I_S, V_{GS} = 0V$			1.3	V
Reverse Recovery Time	t_{rr}	$I_F = I_S, di_F/dt = 100A / \mu S$		18		nS
Peak Reverse Recovery Current	$I_{RM(REC)}$			100		A
Reverse Recovery Charge	Q_{rr}			10		nC


¹Pulse test : Pulse Width $\leq 300 \mu\text{sec}$, Duty Cycle $\leq 2\%$.

²Independent of operating temperature.

³Pulse width limited by maximum junction temperature.







Ordering & Marking Information:






Device Name: EMB12N03HR for EDFN 5 x 6






TYPICAL CHARACTERISTICS





Outline Drawing



Dimension in mm

Dimension	A	B	C	D	E	F	G	H	I	J	K	L	M
Min.	4.80	5.50	5.90	0.3		0.85	0.15	3.67	0.41	3.00	0.94	0.45	0°
Typ.					1.27								
Max.	5.30	5.90	6.15	0.51		1.20	0.30	4.54	0.85	3.92	1.7	0.71	12°

Recommended minimum pads

