



P-Channel Logic Level Enhancement Mode Field Effect Transistor

Product Summary:

BV_{DSS}	-60V
$R_{DS(on)} (MAX.)$	90m Ω
I_D	-5A



UIS, Rg 100% Tested

Pb-Free Lead Plating & Halogen Free



ABSOLUTE MAXIMUM RATINGS ($T_A = 25\text{ }^{\circ}\text{C}$ Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNIT
Gate-Source Voltage		V_{GS}	± 25	V
Continuous Drain Current	$T_A = 25\text{ }^{\circ}\text{C}$	I_D	-5	A
	$T_A = 100\text{ }^{\circ}\text{C}$		-3.5	
Pulsed Drain Current ¹		I_{DM}	-20	
Avalanche Current		I_{AS}	-5	
Avalanche Energy	$L = 0.1\text{mH}$, $I_D = -5\text{A}$, $R_G = 25\Omega$	E_{AS}	1.25	mJ
Repetitive Avalanche Energy ²	$L = 0.05\text{mH}$	E_{AR}	0.625	
Power Dissipation	$T_A = 25\text{ }^{\circ}\text{C}$	P_D	2.5	W
	$T_A = 100\text{ }^{\circ}\text{C}$		1	
Operating Junction & Storage Temperature Range		$T_{j, T_{stg}}$	-55 to 150	$^{\circ}\text{C}$

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNIT
Junction-to-Case	$R_{\theta JC}$		25	$^{\circ}\text{C} / \text{W}$
Junction-to-Ambient	$R_{\theta JA}$		50	

¹Pulse width limited by maximum junction temperature.

²Duty cycle $\leq 1\%$

ELECTRICAL CHARACTERISTICS ($T_c = 25^\circ\text{C}$, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = -250\mu A$	-60			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = -250\mu A$	-1.0	-1.8	-3.0	
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0V, V_{GS} = \pm 20V$			± 100	nA
		$V_{DS} = 0V, V_{GS} = \pm 25V$			± 500	
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = -48V, V_{GS} = 0V$			-1	μA
		$V_{DS} = -40V, V_{GS} = 0V, T_J = 125\text{ }^{\circ}C$			-25	
On-State Drain Current ¹	$I_{D(ON)}$	$V_{DS} = -5V, V_{GS} = -10V$	-5			A
Drain-Source On-State Resistance ¹	$R_{DS(ON)}$	$V_{GS} = -10V, I_D = -5A$		78	90	m Ω
		$V_{GS} = -4.5V, I_D = -3A$		110	140	
Forward Transconductance ¹	g_{fs}	$V_{DS} = -5V, I_D = -5A$		9		S
DYNAMIC						
Input Capacitance	C_{iss}	$V_{GS} = 0V, V_{DS} = -25V, f = 1MHz$		963		pF
Output Capacitance	C_{oss}			76		
Reverse Transfer Capacitance	C_{rss}			61		
Gate Resistance	R_g	$V_{GS} = 15mV, V_{DS} = 0V, f = 1MHz$		6.8		Ω
Total Gate Charge ^{1,2}	Q_g	$V_{DS} = -30V, V_{GS} = -10V,$ $I_D = -5A$		16.2		nC
Gate-Source Charge ^{1,2}	Q_{gs}			2.0		
Gate-Drain Charge ^{1,2}	Q_{gd}			3.5		
Turn-On Delay Time ^{1,2}	$t_{d(on)}$	$V_{DS} = -10V,$ $I_D = -1A, V_{GS} = -10V, R_{GS} = 6\Omega$		8		nS
Rise Time ^{1,2}	t_r			12		
Turn-Off Delay Time ^{1,2}	$t_{d(off)}$			20		
Fall Time ^{1,2}	t_f			12		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (T _c = 25 °C)						
Continuous Current	I_S				-2.3	A
Pulsed Current ³	I_{SM}				-9.2	
Forward Voltage ¹	V_{SD}	$I_F = I_S, V_{GS} = 0V$			-1.3	V


¹Pulse test : Pulse Width $\leq 300 \mu\text{sec}$, Duty Cycle $\leq 2\%$.

²Independent of operating temperature.


³Pulse width limited by maximum junction temperature.

Ordering & Marking Information:

Device Name: EMB90P06G for SOP-8



Outline Drawing



Dimension in mm

Dimension	A	B	C	D	E	F	G	H	I	J	K
Min.	4.70	3.70	5.80	0.33		1.20	0.08	0.40	0.19	0.25	0°
Typ.					1.27						
Max.	5.10	4.10	6.20	0.51		1.62	0.28	0.83	0.26	0.50	8°



TYPICAL CHARACTERISTICS

