




Token Ring Transceiver Module

EPT7034S





- Supports both UTP and STP Transmission •
- Robust Construction allows for severe soldering processes •
- Complies with or exceeds IEEE 802.5 Requirements •

Electrical Parameters @ 25° C

Primary OCL (μ H Min.)	Interwinding Capacitance (pF Max.)	Leakage Inductance (μ H Max.)	ET Product ($V\mu$ S Min.)	Rise Time (nS Max.)	DCR (Ω Max.)	
					Pri.	Sec.
@ 100 KHz, 0.1 Vrms	@ 100 KHz, 0.1 Vrms	@ 100 KHz, 0.1 Vrms				
75 \pm 30%	14	0.20	2.5	2.0	0.20	0.40

• Isolation : 1500 Vrms •

Schematic



Dimensions

Dim.	(Inches)			(Millimeters)		
	Min.	Max.	Nom.	Min.	Max.	Nom.
A	.440	.460		11.18	11.68	
B	.250	.270		6.35	6.86	
C	.200	.220		5.08	5.59	
D	.350	Typ.		8.89	Typ.	
E	.005	.015		.127	.381	
F	.050	Typ.		1.27	Typ.	
G	.350	.370		8.89	9.40	
H	.016	.022		.406	.559	
I	.008	.012		.203	.305	
J	.050	Typ.		1.27	Typ.	
K	0°	8°		0°	8°	
L	.025	.045		.635	1.14	
M			.030			.762
N			.050			1.27
P			.070			1.78
Q			.400			10.16