

Super-Fast Rectifiers

ES5ACF--ES5DCF

Features

- For surface mounted applications
- Ideal for automated placement
- Low forward voltage drop
- High surge current capability
- RoHS Compliant



Mechanical Data

- Case: SMCF molded plastic
- Molding compound, UL flammability classification rating 94V-0
- Terminals: Solder plated, solderable per MIL-STD-202, Method 208
- Polarity: Color band denotes cathode end

Maximum Ratings (@T_A = 25°C unless otherwise specified)

Characteristic	Symbol	ES5ACF	ES5BCF	ES5CCF	ES5DCF	Units
Peak repetitive reverse voltage	V _{RRM}	50	100	150	200	V
RMS reverse voltage	V _{RMS}	35	70	105	140	V
DC blocking voltage	V _{DC}	50	100	150	200	V
Maximum average forward output current	I _{F(AV)}	5.0				A
Peak forward surge current, 8.3ms single half-sine-wave	I _{FSM}	150				A

Thermal Characteristics

Parameter	Symbol	ES5ACF	ES5BCF	ES5CCF	ES5DCF	Units
Typical thermal resistance (Note 1)	R _{ΘJA}	27				°C/W
	R _{ΘJC}	10				
	R _{ΘJL}	4				
Operating junction temperature range	T _J	- 55 ---- + 150				°C
Storage temperature range	T _{STG}	- 55 ---- + 150				°C

Note:

1. Device mounted on PCB with 10 mm x 20 mm x 0.1mm copper pad areas

Super-Fast Rectifiers**ES5ACF--ES5DCF****Electrical Characteristics** (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test conditions		Typ.	Max.	Units
Maximum instantaneous forward voltage	V_F	$I_F=5.0\text{A}$	@ $T_A=25^\circ\text{C}$	--	0.95	V
Maximum Reverse current	I_R	Rated V_R	@ $T_A=25^\circ\text{C}$	--	5	μA
			@ $T_A=100^\circ\text{C}$	--	100	
Maximum Reverse Recovery Time	t_{rr}	$I_F=0.5\text{A}, I_{RM}=1\text{A}, I_{R(REC)}=0.25\text{A}$		--	35	ns

Super-Fast Rectifiers

ES5ACF--ES5DCF

Ratings and Characteristic Curves ($T_A=25^\circ\text{C}$ unless otherwise noted)

Fig.1-Forward Current Derating Curve




Fig.2- Surge Current Derating Curve




Fig.3- Typical Forward Voltage Characteristic






Fig.4- Typical Reverse Characteristic



Super-Fast Rectifiers


ES5ACF--ES5DCF

Package Outline Dimensions(unit:mm)



SMCF		
Dim	Min	Max
A	6.8	7.2
B	5.8	6.2
D	7.8	8.2
E	0.4	0.6
F1	0.6	1.4
H	1.85	2.15
I	3.1	3.3
All Dimensions in mm		

Mounting Pad Layout(unit:mm)



Ordering Information

Part No.	Marking	Package	Shipping
ES5ACF	ES5ACF	SMCF	3000 / Tape&Reel
ES5BCF	ES5BCF	SMCF	3000 / Tape&Reel
ES5CCF	ES5CCF	SMCF	3000 / Tape&Reel
ES5DCF	ES5DCF	SMCF	3000 / Tape&Reel