


Features

- * Low clamping voltage
- * Low leakage
- * For ESD protection



RoHS
COMPLIANT



SOD-323F				
DIM	INCHES		MM	
	MIN	MAX	MIN	MAX
A	0.091	0.110	2.30	2.80
B	0.045	0.053	1.15	1.35
C	0.063	0.071	1.60	1.80
D	0.010	0.016	0.25	0.40
E	0.031	0.043	0.80	1.10
F	0.004	0.006	0.10	0.15
G	0.016	0.024	0.41	0.61

Maximum Ratings (TA=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Peak Pulse Power (tp = 8/20 µs)	P _{pk}	350	W
Peak Pulse Current (tp = 8/20 µs)	I _{PP}	24	A
ESD Voltage (HRB Waveform per IEC61000-4-2)	V _{PP}	30	KV
Operating Junction Temperature	T _j	- 55 to + 125	°C
Storage Temperature Range	T _{stg}	- 55 to + 150	°C


Electrical Characteristics (TA=25°C unless otherwise noted)

Type	Marking Code	Reverse Stand-off Voltage	Reverse Current	Breakdown Voltage		Clamping Voltage ¹⁾				Capacitance	
		V _{RWM}	I _R at V _{RWM}	V _{BR}	at I _T	V _c	at I _{PP}	V _c	at I _{PP}	C _j	at f
		Max. (V)	Max.(µA)	Min.(V)	mA	Max.(V)	A	Max.(V)	A	Max.(pF)	MHz
ESD3Z5V0	5-	5	10	6	1	9.8	5	14.5	24	350	1
ESD3Z12	12-	12	1	13.3	1	19	5	25	15	150	1


Note: 1) tp = 8/20 µs

Ratings and Characteristic Curves


Non-Repetitive Peak Pulse Power vs. Pulse Time




Power Derating Curve



Pulse Waveform



Clamping Voltage vs. Peak Pulse Current





ESD3Z5V0,ESD3Z12 Transient Voltage Suppressors

Ordering Information

Part No.	Package	Packing Code	Packing
ESD3Z5V0,ESD3Z12	SOD-323F	R30	3000pcs/Reel

Disclaimer

Specifications of the products displayed herein are subject to change without notice. JGD or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in JGD's terms and conditions of sale for such products, JGD assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of JGD products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify JGD for any damages resulting from such improper use or sale.