



**ESD5431XZ**
**1-Line, Bi-directional, Transient Voltage Suppressor**
<http://www.sh-willsemi.com>
**Descriptions**


The ESD5431XZ is a bi-directional TVS (Transient Voltage Suppressor). It is specifically designed to protect sensitive electronic components which are connected to low speed data lines and control lines from over-stress caused by ESD (Electrostatic Discharge), EFT (Electrical Fast Transients) and Lightning.

The ESD5431XZ may be used to provide ESD protection up to  $\pm 30\text{kV}$  (contact discharge) according to IEC61000-4-2, and withstand peak pulse current up to 10A (8/20 $\mu\text{s}$ ) according to IEC61000-4-5.

The ESD5431XZ is available in FBP0603-2L package. Standard products are Pb-free and Halogen-free.


**FBP0603-2L (Bottom View)**

**Circuit diagram**
**Features**

- Stand-off voltage:  $\pm 3.3\text{V}$  Max
- Transient protection for each line according to IEC61000-4-2 (ESD):  $\pm 30\text{kV}$  (contact discharge)  
IEC61000-4-4 (EFT): 40A (5/50ns)  
IEC61000-4-5 (surge): 10A (8/20 $\mu\text{s}$ )
- Capacitance:  $C_J = 17.5\text{pF}$  typ.
- Low leakage current:  $I_R < 1\text{nA}$  typ.
- Low clamping voltage:  $V_{CL} = 8\text{V}$  typ. @  $I_{PP} = 16\text{A}$  (TLP)
- Small package



F = Device code

\* = Month code

**Marking (Top View)**
**Applications**


- Cellular handsets
- Computers and peripherals
- Microprocessors
- Portable Electronics
- Notebooks

**Order information**

Device	Package	Shipping
ESD5431XZ-2/TR	FBP0603-2L	10000/Tape&Reel

**Absolute maximum ratings**

Parameter	Symbol	Rating	Unit
Peak pulse power ( $t_p = 8/20\mu s$ )	$P_{pk}$	100	W
Peak pulse current ( $t_p = 8/20\mu s$ )	$I_{PP}$	10	A
ESD according to IEC61000-4-2 air discharge	$V_{ESD}$	$\pm 30$	kV
ESD according to IEC61000-4-2 contact discharge		$\pm 30$	
Junction temperature	$T_J$	125	$^{\circ}C$
Operating temperature	$T_{OP}$	-40~85	$^{\circ}C$
Lead temperature	$T_L$	260	$^{\circ}C$
Storage temperature	$T_{STG}$	-55~150	$^{\circ}C$







**Electrical characteristics ( $T_A=25^{\circ}C$ , unless otherwise noted)**

**Definitions of electrical characteristics**

**Electrical characteristics (T<sub>A</sub>=25 °C, unless otherwise noted)**


Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Reverse stand-off voltage	V <sub>RWM</sub>				±3.3	V
Reverse leakage current	I <sub>R</sub>	V <sub>RWM</sub> = 3.3V		<1	50	nA
Reverse breakdown voltage	V <sub>BR</sub>	I <sub>BR</sub> = 1mA	3.4		4.2	V
Reverse holding voltage	V <sub>HOLD</sub>	I <sub>HOLD</sub> = 50mA	3.4		4.2	V
Clamping voltage <sup>1)</sup>	V <sub>CL</sub>	I <sub>PP</sub> = 16A, t <sub>p</sub> = 100ns		8		V
Clamping voltage <sup>2)</sup>	V <sub>CL</sub>	V <sub>ESD</sub> = 8kV		8		V
Clamping voltage <sup>3)</sup>	V <sub>CL</sub>	I <sub>PP</sub> = 1A, t <sub>p</sub> = 8/20μs			6	V
		I <sub>PP</sub> = 5A, t <sub>p</sub> = 8/20μs			8	V
		I <sub>PP</sub> = 10A, t <sub>p</sub> = 8/20μs			10	V
Dynamic resistance <sup>1)</sup>	R <sub>DYN</sub>			0.20		Ω
Junction capacitance	C <sub>J</sub>	V <sub>R</sub> = 0V, f = 1MHz		17.5	22	pF
		V <sub>R</sub> = 3.3V, f = 1MHz		12.5	16	pF

**Notes:**


- 1) TLP parameter: Z<sub>0</sub> = 50Ω, t<sub>p</sub> = 100ns, t<sub>r</sub> = 2ns, averaging window from 60ns to 80ns. R<sub>DYN</sub> is calculated from 4A to 16A.
- 2) Contact discharge mode, according to IEC61000-4-2.
- 3) Non-repetitive current pulse, according to IEC61000-4-5.

**Typical characteristics ( $T_A=25^\circ\text{C}$ , unless otherwise noted)**

**8/20 $\mu\text{s}$  waveform per IEC61000-4-5**

**Contact discharge current waveform per IEC61000-4-2**

**Clamping voltage vs. Peak pulse current**

**Capacitance vs. Reverse voltage**

**Non-repetitive peak pulse power vs. Pulse time**

**Power derating vs. Ambient temperature**


Typical characteristics ( $T_A=25^\circ\text{C}$ , unless otherwise noted)






**ESD clamping**  
 (+8kV contact discharge per IEC61000-4-2)




**ESD clamping**  
 (-8kV contact discharge per IEC61000-4-2)






**TLP Measurement**

**PACKAGE OUTLINE DIMENSIONS**
**FBP0603-2L**

**Top View**

**Bottom View**

**Side View**

Symbol	Dimensions in Millimeters		
	Min.	Typ.	Max.
A	0.275	0.307	0.340
D	0.570	0.620	0.670
E	0.270	0.320	0.370
a	0.190REF		
b	0.225	0.260	0.295
c	0.010	0.050	0.090
e	0.365	0.400	0.435
L1	0.125	0.160	0.195
L2	0.030REF		
L3	0.125	0.160	0.195

**Recommend land pattern (Unit: mm)**

**Notes:**

This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met.

**TAPE AND REEL INFORMATION**
**Reel Dimensions**

**Tape Dimensions**

**Quadrant Assignments For PIN1 Orientation In Tape**


RD	Reel Dimension	<input checked="" type="checkbox"/> 7inch	<input type="checkbox"/> 13inch
W	Overall width of the carrier tape	<input checked="" type="checkbox"/> 8mm	<input type="checkbox"/> 12mm
P1	Pitch between successive cavity centers	<input checked="" type="checkbox"/> 2mm	<input type="checkbox"/> 4mm <input type="checkbox"/> 8mm
Pin1	Pin1 Quadrant	<input checked="" type="checkbox"/> Q1	<input checked="" type="checkbox"/> Q2 <input type="checkbox"/> Q3 <input type="checkbox"/> Q4