

Data Sheet

Customer: _____

Product: Aluminum Electrolytic Capacitors – ESG Series _____

Size : 10x16mm ~ 22x41mm _____

Issued Date: 10-Jan.-2017 _____

Edition: Ver. 2 _____

Record of change

Date	Ver.	Description	Page
20-May-2016	1		
10-Jan-2017	2	revise max ripple current	2

HITANO ENTERPRISE CORP.

7F-7, No. 3, Wu Chuan 1st Road, New Taipei Industrial Park,

New Taipei City, TAIWAN, R.O.C.

Tel: +886 2 2299 1331 (Rep.)

Fax: +886 2 2298 2466, 2298 2969


Prepared by	Checked by	Approved by	Accepted by (customer)
20-May-2016	20-May-2016	20-May-2016	
Andy Hsu	Hwa Wu	Hwa Wu	

- ESG series capacitors are suitable for electronic ballast and other long life equipment.
- Load life 105°C, 5000 hours assured.

Characteristics

Voltage Range	160 ~500V							
Temperature Range	-25 ~ + 105℃							
Capacitance Range	4.7 to 330 uF							
Leakage Current	I ≤0.04CV or 10uA, whichever is greater (After 2 minutes)							
Capacitance Tolerance	±20% at 120Hz , 20℃ (10% Tol. is available upon request)							
Dissipation Factor (at 20℃, 120Hz)	WV	160	200	250	350	400	450	500
	tanδ	0.12	0.12	0.12	0.15	0.15	0.17	0.20
Stability at Low Temperature (120Hz)	Rated Voltage (V)	160	200	250	350	400	450	500
	Z-25℃/Z 20℃	3	3	3	6	6	6	6
Load life after application of the rated voltage for 5000 hrs at 105℃	Leakage current		Less than initial specified value					
	Capacitance change		Within ±20% of initial value					
	tanδ		200% or less of initial specified value					
Shelf life (at 105℃)	After storage for 1000 hours at 105℃ with no voltage applied, the capacitor shall meet the specified limit in load life. Pre-treatment for measurement shall be conducted after application of DC working voltage for 30 minutes.							

Diagram of dimensions



Drawing

D ϕ	10	13	16	18	22
p	5.0	5.0	7.5	7.5	10.0
d ϕ	0.6	0.6	0.8	0.8	0.8

Ripple Current Coefficients

Frequency (Hz)	120	1K	10K	100K
Multiplier	0.52	0.79	0.89	1.0

Part Numbering System

ESG	□ □ □	□	□ □	B	□ □
Series	Capacitance	Tolerance	Rated Voltage	Package	Extended Code

Case size & Maximum Ripple Current (mA rms 105°C 100KHz)

Cap. WV	160V		200V		250V		350V	
uF	Size	R.C.	Size	R.C.	Size	R.C.	Size	R.C.
10	10x16	115	10x16 10x20	195 210	10x16 10x20	195 200	10x20	150
22	10x16 10x20	175 195	10x16 10x20	250 255	13x20	300 350	13x20	250
33	10x20 13x20	200 250	10x20 13x20	300 350	13x20 13x25	350 400	13x25	360
47	10x20 13x20	255 300	13x20	490	13x25	500	16x25	430
68	13x20 13x25	350 390	13x25	530	16x25	600	16x31.5	450
100	13x25 16x25	530 560	16x20 16x25	730 810	16x31.5 18x31.5	600 660	18x31.5	700
150	16x25 16x31.5	690	16x31.5	840	18x31.5	690		
220	16x31.5	730	18x31.5	970	22x41	750		
330	18x41	1250						

Cap. WV	400V		450V		500V	
uF	Size	R.C.	Size	R.C.	Size	R.C.
4.7	10x16	115	10x16	115	13x20	82
6.8	10x16	125	10x20	125	13x20	96
10	10x20 13x20	175 200	13x20 13x25	175 185	13x25	130
22	13x25	320	16x25	290	16x25	170
33	16x25	350	16x31.5	390	16x31.5	210
47	16x31.5	450	16x35.5	480	16x35.5	360
68	18x31.5	580	18x41	630	18x35.5	460
100	18x41	790				