

EDISWAN

ESW.501

RADIATION COOLED TRIODEGENERAL

The ESW.501 is a U.H.F. thoriated tungsten filament triode suitable for use in industrial and transmitting equipment.

RATING

Filament Voltage (volts)	V_f	6.0
Filament Current (amps)	I_f	4.0
Maximum Anode Voltage (volts)	$V_a(\max)$	1,500
Average Maximum Filament Emission (amps)	$F_{em(av)}$	1.0
Maximum Anode Dissipation (watts)	$W_a(\max)$	60.0
Mutual Conductance ($\mu A/V$)	g_m	• 1.3
Amplification Factor	μ	• 8.0
Anode Impedance (ohms)	Z_a	• 6,200
Maximum Operating Frequency at full rating		80 Mc/s
Power Output (watts)	P_o	100

• Taken at $V_a = 1,000v$; $I_a = 50$ mA.

|| At higher frequencies the maximum permissible anode voltage and input must be reduced.

INTER-ELECTRODE CAPACITANCES

Anode/Grid (μF)	$c_{a,gl}$	4.0
Anode/Filament (μF)	$c_{a,f}$	1.26
Grid/Filament (μF)	$g_{l,f}$	1.63

DIMENSIONS

Maximum Overall Length (mm)	215
Maximum Diameter (mm)	57.0
Approximate Nett Weight (ozs)	4.0
Approximate Home Packed Weight (lbs)	4.0
Approximate Export Packed Weight (lbs)	6.0

MOUNTING POSITION - Vertical


EDISWAN

ESW.501


RADIATION COOLED TRIODE

TOP CONNEXIONS Anode and Grid - screw terminals.

BASE 4 pin. Standard B.V.A.
Filament - pins 3 & 4.



Viewed from free end of pins.




Anode and Grid terminals on top of valve in alignment with their respective pins on base.

ESW.501

EDISWAN

ESW.501

RADIATION COOLED TRIODE



ESW.501

EDISWAN

ESW.501

RADIATION COOLED TRIODE

