

3 Phase Inverter Automotive Power Module

FAM04V18DT1

Features

- Full Bridge Inverter for Variable Speed Motor Drive
- Temperature Sensing
- R-C Snubber Circuits for each MOSFET
- Electrically Isolated DBC Substrate for Low R_{thjc}
- Compact Design for Low Total Module Resistance
- Module Serialization for Full Traceability
- Lead Free, RoHS and UL94 V-0 Compliant
- Automotive Qualified
- This Device is Pb-Free and is RoHS Compliant

Applications

- 12 V Motor Control
- Brake System, Electrical Steering, Turbo Charger

Benefits

- Enable Design of Small, Efficient and Reliable System for Reduced Vehicle Fuel Consumption and CO₂ Emission
- High Current Application
- Low Thermal Resistance
- Simplified Vehicle Assembly
- High EMI Performance




Figure 1. Pin Configuration



ON Semiconductor®

www.onsemi.com



**APM20CBB / 20LD,
CASE MODFZ**

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

FAM04V18DT1

Table 1. ORDERING INFORMATION

Part Number	Package	Pb-Free and RoHS Compliant	Operating Temperature Range	Packing Method
FAM04V18DT1	APM20-CBB	Yes	-40C ~ 125°C	Tube

Table 2. PIN DESCRIPTION

Pin No.	Pin Name	Pin Descriptions
1	NTC+	NTC Thermistor Terminal 1
2	NTC-	NTC Thermistor Terminal 2
3	U_DN	Gate of Q4
4	U_UP	Gate of Q1
5	U_SENSE	Sense Pin for Source of Q1 and Drain of Q4
6	V_DN	Gate of Q5
7	V_UP	Gate of Q2
8	NC	Not used
9	V_SENSE	Sense Pin for Source of Q2 and Drain of Q5
10	W_DN	Gate for Q6
11	W_UP	Gate for Q3
12	NC	Not used
13	W_SENSE	Sense Pin for Source of Q3 and Drain of Q6
14	V_LINK	Sense Pin for Battery Voltage and Drain of High Side MOSFETs
15	B-_SENSE	B- Sense
16	B-	Battery-
17	B+	Battery+
18	W Phase	W Phase Power lead
19	V Phase	V Phase Power lead
20	U Phase	U Phase Power lead

Block Diagram




Figure 2. Schematic

FAM04V18DT1

Flammability Information

All materials present in the power module meet UL flammability rating class 94 V-0.

Solder

Solder used is a lead free SnAgCu alloy.

Compliance to RoHS directives

The power module is 100% lead free and RoHS compliant 2000/53/C directive.

Table 3. ABSOLUTE MAXIMUM RATINGS ($T_J = 25^\circ\text{C}$, Unless Otherwise Specified)

Symbol	Parameter	Rating	Unit
$V_{DS}(Q1\sim Q6)$	Drain to Source Voltage	40	V
$V_{GS}(Q1\sim Q6)$	Gate to Source Voltage	± 20	V
$E_{AS}(Q1\sim Q6)$	Single Pulse Avalanche Energy (Note 1)	1466	mJ
T_J	Maximum Junction Temperature	175	$^\circ\text{C}$
T_{STG}	Storage Temperature	$-40 \sim +125$	$^\circ\text{C}$

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

Table 4. ELECTRICAL SPECIFICATIONS ($T_J = 25^\circ\text{C}$, Unless Otherwise Specified)

Parameter	Conditions	Min	Typ	Max	Units
B_{VDSS}	Drain-to-Source Breakdown Voltage $I_D = 250 \mu\text{A}$, $V_{GS} = 0 \text{ V}$	40			V
$V_{GS(th)}$	Gate to Source Threshold Voltage $V_{GS} = V_{DS}$, $I_D = 250 \mu\text{A}$	2		4	V
V_{SD}	Source-to-Drain Diode Voltage $I_{SD} = 80 \text{ A}$, $V_{GS} = 0 \text{ V}$			1.1	V
$R_{DS(ON)Q1}$	Q1 Inverter High Side MOSFETs (Note 2) $V_{GS} = 10 \text{ V}$, $I_D = 80 \text{ A}$		0.60	0.85	$\text{m}\Omega$
$R_{DS(ON)Q2}$	Q2 Inverter High Side MOSFETs (Note 2) $V_{GS} = 10 \text{ V}$, $I_D = 80 \text{ A}$		0.53	0.75	$\text{m}\Omega$
$R_{DS(ON)Q3}$	Q3 Inverter High Side MOSFETs (Note 2) $V_{GS} = 10 \text{ V}$, $I_D = 80 \text{ A}$		0.45	0.65	$\text{m}\Omega$
$R_{DS(ON)Q4}$	Q4 Inverter Low Side MOSFETs (Note 2) $V_{GS} = 10 \text{ V}$, $I_D = 80 \text{ A}$		1.03	1.48	$\text{m}\Omega$
$R_{DS(ON)Q5}$	Q5 Inverter Low Side MOSFETs (Note 2) $V_{GS} = 10 \text{ V}$, $I_D = 80 \text{ A}$		0.90	1.28	$\text{m}\Omega$
$R_{DS(ON)Q6}$	Q6 Inverter Low Side MOSFETs (Note 2) $V_{GS} = 10 \text{ V}$, $I_D = 80 \text{ A}$		0.77	1.25	$\text{m}\Omega$
I_{GSS}	Gate-to-Source Leakage Current $V_{GS} = \pm 20 \text{ V}$, $V_{DS} = 0 \text{ V}$	-100		+100	nA
I_{DSS}	Drain-to-Source Leakage Current $V_{DS} = 40 \text{ V}$, $V_{GS} = 0 \text{ V}$			2	μA
Total loop resistance, Total Module $R_{DS(ON)}$: $V_{batt}(+) \rightarrow \text{Phase} \rightarrow \text{GND}(-)$		$V_{GS} = 10 \text{ V}$, $I_D = 80 \text{ A}$		2.36	3.4 $\text{m}\Omega$
Switching Characteristics	T_{don} , Turn-on delay time	$V_{GS} = 10 \text{ V}$, $V_{DD} = 14 \text{ V}$, $I_D = 30 \text{ A}$		500	nS
	T_r , Rise time			400	nS
	T_{doff} , Turn-off delay time			1000	nS
	T_f , Fall time			400	nS

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

- Starting $T_J = 25^\circ\text{C}$, $L = 0.47 \text{ mH}$, $I_{AS} = 79 \text{ A}$, $V_{DD} = 40 \text{ V}$ during inductor charging and $V_{DD} = 0 \text{ V}$ during time in avalanche.
- All MOSFETs (bare die) have same die size and R_{dson} level, The different R_{dson} values listed in the datasheet are due to the different access points available inside the module for R_{dson} measurement.

FAM04V18DT1

Table 5. TEMPERATURE SENSE (NTC THERMISTOR)

Parameter	Test Conditions	Min	Max	Units
Resistance	Current = 1 mA	7.5	13	kΩ

Table 6. MOSFETS RDSON MEASUREMENT PATHS

	+ Force	- Force	+ Sense	- Sense		+ Force	- Force	+ Sense	- Sense
Q1	B+	U phase	Vlink	U sense	Q4	U phase	B-	U sense	B- sense
	Pin 17	Pin 20	Pin 14	Pin 5		Pin 20	Pin 16	Pin 5	Pin 15
Q2	B+	V phase	Vlink	V sense	Q5	V phase	B-	V sense	B- sense
	Pin 17	Pin 19	Pin 14	Pin 9		Pin 19	Pin 16	Pin 9	Pin 15
Q3	B+	W phase	Vlink	W sense	Q6	W phase	B-	W sense	B- sense
	Pin 17	Pin 18	Pin 14	Pin 13		Pin 18	Pin 16	Pin 13	Pin 15




Figure 3.

FAM04V18DT1

Table 7. MODULE RDSON MEASUREMENT PATHS

	+ Force	- Force	+ Sense	- Sense		+ Force	- Force	+ Sense	- Sense
Q1	B+	U phase	B+	U phase	Q4	U phase	B-	U phase	B-
	Pin 17	Pin 20	Pin 17	Pin 20		Pin 20	Pin 16	Pin 20	Pin 16
Q2	B+	V phase	B+	V phase	Q5	V phase	B-	V phase	B-
	Pin 17	Pin 19	Pin 17	Pin 19		Pin 19	Pin 16	Pin 19	Pin 16
Q3	B+	W phase	B+	W phase	Q6	W phase	B-	W phase	B-
	Pin 17	Pin 18	Pin 17	Pin 18		Pin 18	Pin 16	Pin 18	Pin 16




Figure 4.

Table 8. THERMAL RESISTANCE

Parameters		Min	Typ	Max	Unit
Rthjc Thermal Resistance Junction to case, Single Inverter FET	Q1-Q6 Thermal Resistance J-C	-	0.69	0.97	C/W

Table 9. ISOLATION VOLTAGE (Isolation Voltage between DBC Bottom Surface and All Module Pins)

Test	Test Conditions	Min	Max	Unit
Leakage @ Isolation Voltage (Hi-Pot)	VAC = 3 kV Frequency = 50 Hz Test Time = 1 s	-	300	μA

FAM04V18DT1

Table 10. REFERENCE TYPICAL CHARACTERISTICS FOR DISCRETE MOSFET FDBL9401_F085, USED IN HIGH SIDE AND LOW SIDE MOSFETS OF THIS MODULE

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units	
OFF CHARACTERISTICS							
B _V DSS	Drain-to-Source Breakdown Voltage	I _D = 250 μA, V _{GS} = 0 V	40	–	–	V	
I _{DSS}	Drain-to-Source Leakage Current	V _{DS} = 40 V	T _J = 25°C	–	–	1	μA
		V _{GS} = 0 V	T _J = 175°C (Note 3)	–	–	1	mA
I _{GSS}	Gate-to-Source Leakage Current	V _{GS} = ±20 V	–	–	±100	nA	
ON CHARACTERISTICS							
V _{GS(th)}	Gate to Source Threshold Voltage	V _{GS} = V _{DS} , I _D = 250 μA	2.0	3.0	4.0	V	
R _{DS(on)}	Drain to Source On Resistance	I _D = 80 A	T _J = 25°C	–	0.50	0.65	mΩ
		V _{GS} = 10 V	T _J = 175°C (Note 3)	–	0.86	1.10	mΩ
DYNAMIC CHARACTERISTICS							
C _{iss}	Input Capacitance	V _{DS} = 25 V, V _{GS} = 0 V f = 1 MHz	–	15900	–	pF	
C _{oss}	Output Capacitance		–	4025	–	pF	
C _{rss}	Reverse Transfer Capacitance		–	604	–	pF	
R _g	Gate Resistance	f = 1 MHz	–	2.6	–	Ω	
Q _{g(ToT)}	Total Gate Charge at 10 V	V _{GS} = 0 to 10	V _{DD} = 20 V I _D = 80 A	–	220	–	nC
Q _{g(th)}	Threshold Gate Charge	V _{GS} = 0 to 2 V		–	29	–	nC
Q _{gs}	Gate to Source Gate Charge		–	73	–	nC	
Q _{gd}	Gate to Drain “Miller” Charge		–	41	–	nC	
SWITCHING CHARACTERISTICS							
t _{on}	Turn-On Time	V _{DD} = 20 V, I _D = 80 A V _{GS} = 10 V, R _{GEN} = 6 Ω	–	–	221	ns	
t _{d(on)}	Turn-On Delay		–	54	–	ns	
t _r	Rise Time		–	82	–	ns	
t _{d(off)}	Turn-Off Delay		–	106	–	ns	
t _f	Fall Time		–	52	–	ns	
t _{off}	Turn-Off Time		–	–	215	ns	
DRAIN-SOURCE DIODE CHARACTERISTICS							
V _{SD}	Source to Drain Diode Voltage	I _{SD} = 80 A, V _{GS} = 0 V	–	–	1.25	V	
		I _{SD} = 40 A, V _{GS} = 0 V	–	–	1.2	V	
t _{rr}	Reverse Recovery Time	I _F = 80 A, dI _{SD} /dt = 100 A/μs	–	119	133	ns	
Q _{rr}	Reverse Recovery Charge	V _{DD} = 32 V	–	228	274	nC	


3. The maximum value is specified by design at $T_J = 175^\circ C$. Product is not tested to this condition in production.

Table 11. COMPONENTS

	Component				Size	Maker	Remarks
1	MOSFET	PT8 40 V	PT8 40 V, bare die used in FDBL9401	6ea	260 x 145 mil	ON Semiconductor	AEC Q101 qualified by FDBL9401_F085
2	R1, 2, 3, 4, 5, 6	Resistors	1406 10 Ω 200 mV 1%	6ea	2200 x 1100 [μm]	Vishay	AEC Q200 qualified
3	C1, 2, 3, 4, 5, 6	Capacitors	8200 pF 50 V 5%	6ea	2000 x 1250 [μm]	Murata	AEC Q200 qualified
4	C7	Capacitor	1206 100 nF 100 V 10%	1ea	2010 x 1250 [μm]	Murata	AEC Q200 qualified
5	NTC	Thermistor	NCP18XH103F0SRB – 10 k Ω	1ea	1600 x 800 [μm]	Murata	AEC Q200 qualified

FAM04V18DT1

Mechanical Characteristics and Ratings



Warpage Spec. of point 1, 2, 3, 4 : 0~200um





Figure 5.

FAM04V18DT1

PACKAGE DIMENSIONS

APM20CBB / 20LD, PDD STD, R-EPS MODULE CASE MODFZ ISSUE A



NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH AND TIE BAR EXTRUSIONS.
4. DIMENSION b and c APPLY TO THE PLATED LEADS AND ARE MEASURED BETWEEN 1.00 AND 2.00MM FROM THE LEAD TIP.

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	25.00	25.30	25.60
A2	7.00	7.20	7.40
b	1.70	1.80	1.90
b1	5.80	6.00	6.20
b2	0.70	0.80	0.90
b3	1.40	1.50	1.60
c	0.75	0.80	0.90
D	51.50	51.70	51.90
D1	62.40	62.70	63.00
E	34.50	34.70	34.90
E1	20.00	20.20	20.40
E2	19.90	20.10	20.30
e	3.00 BSC		
e1	10.00 BSC		
e2	1.00 BSC		
F	4.80	5.00	5.20
L	4.00	4.20	4.40
L1	3.75	3.95	4.15
q	51.50	51.70	51.90
φA	3.30	3.40	3.50

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Email Requests to: orderlit@onsemi.com

ON Semiconductor Website: www.onsemi.com

TECHNICAL SUPPORT

North American Technical Support:

Voice Mail: 1 800-282-9855 Toll Free USA/Canada

Phone: 011 421 33 790 2910

Europe, Middle East and Africa Technical Support:

Phone: 00421 33 790 2910

For additional information, please contact your local Sales Representative