

KDB3682 (FDB3682)

■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Testconditons	Min	Typ	Max	Unit
Drain to source breakdown voltage	V _{DSS}	I _D =250μA, V _{GS} =0V	100			V
Drain cut-off current	I _{DSS}	V _{DS} =80V, V _{GS} =0			1	μA
		V _{DS} =80V, V _{GS} =0, T _C =150°C			250	μA
Gate leakage current	I _{GSS}	V _{GS} =±20V			±100	nA
Gate threshold voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250μA	2.0		4.0	V
Drain to source on-state resistance	R _{DS(on)}	V _{GS} =10V, I _D =32A		0.032	0.036	Ω
		V _{GS} =16V, I _D =16A		0.040	0.060	
		V _{GS} =10V, I _D =32A, T _C =175°C		0.080	0.090	
Input capacitance	C _{iss}			1250		pF
Output capacitance	C _{oss}	V _{DS} =25V, V _{GS} =0, f=1MHZ		190		pF
Reverse transfer capacitance	C _{rss}			45		pF
Total Gate Charge at 10V	Q _{g(TOT)}	V _{GS} = 0V to 10V		18.5	28	nC
Threshold Gate Charge	Q _{g(TH)}	V _{GS} = 0V to 2V		2.4	3.6	nC
Gate to Source Gate Charge	Q _{gs}			6.5		nC
Gate Charge Threshold to Plateau	Q _{gs2}	V _{DS} = 50 V, I _D = 32A, I _g =1.0mA		4.1		nC
Gate to Drain "Miller" Charge	Q _{gd}			4.6		nC
Turn-On Time	t _{ON}				83	ns
Turn-On Delay Time	t _{d(ON)}			9		ns
Rise Time	t _r	V _{DD} = 50 V, I _D = 32A,		46		ns
Turn-Off Delay Time	t _{d(OFF)}	V _{GS} = 10 V, R _{GS} = 16 Ω		26		ns
Fall Time	t _f			32		ns
Turn-Off Time	t _{OFF}				87	ns
Source to Drain Diode Voltage	V _{SD}	I _{SD} =32A			1.25	V
		I _{SD} =16A			1.0	V
Reverse Recovery Time	t _{rr}	I _{SD} = 32A, di _{SD} /dt = 100A/μs			55	ns
Reverse Recovered Charge	Q _{RR}	I _{SD} = 32A, di _{SD} /dt = 100A/μs			90	nC