


### FEATURES

- High Output Power:  $P_{1dB} = 32.5\text{dBm(Typ.)}$
- High Gain:  $G_{1dB} = 6.0\text{dB(Typ.)}$
- High PAE:  $\eta_{add} = 27\%\text{(Typ.)}$
- Proven Reliability

### DESCRIPTION

The FLK207XV chip is a power GaAs FET that is designed for general purpose applications in the Ku-Band frequency range as it provides superior power, gain, and efficiency.



Fujitsu's stringent Quality Assurance Program assures the highest reliability and consistent performance

### ABSOLUTE MAXIMUM RATING (Ambient Temperature $T_a=25^\circ\text{C}$ )

Item	Symbol	Condition	Rating	Unit
Drain-Source Voltage	$V_{DS}$		15	V
Gate-Source Voltage	$V_{GS}$		-5	V
Total Power Dissipation	$P_{tot}$	$T_c = 25^\circ\text{C}$	12.5	W
Storage Temperature	$T_{stg}$		-65 to +175	$^\circ\text{C}$
Channel Temperature	$T_{ch}$		175	$^\circ\text{C}$

Fujitsu recommends the following conditions for the reliable operation of GaAs FETs:

1. The drain-source operating voltage ( $V_{DS}$ ) should not exceed 10 volts.
2. The forward and reverse gate currents should not exceed 17.8 and -1.0 mA respectively with gate resistance of 250 $\Omega$ .
3. The operating channel temperature ( $T_{ch}$ ) should not exceed 145 $^\circ\text{C}$ .

### ELECTRICAL CHARACTERISTICS (Ambient Temperature $T_a=25^\circ\text{C}$ )

Item	Symbol	Test Conditions	Limit			Unit
			Min.	Typ.	Max.	
Saturated Drain Current	$I_{DSS}$	$V_{DS} = 5\text{V}, V_{GS} = 0\text{V}$	-	800	1200	mA
Transconductance	$g_m$	$V_{DS} = 5\text{V}, I_{DS} = 500\text{mA}$	-	400	-	mS
Pinch-off Voltage	$V_p$	$V_{DS} = 5\text{V}, I_{DS} = 40\text{mA}$	-1.0	-2.0	-3.5	V
Gate Source Breakdown Voltage	$V_{GSO}$	$I_{GS} = -40\mu\text{A}$	-5	-	-	V
Output Power at 1dB Gain Compression Point	$P_{1dB}$	$V_{DS} = 10\text{V}$ $I_{DS} \approx 0.6I_{DSS}$ $f = 14.5\text{GHz}$	31.5	32.5	-	dBm
Power Gain at 1dB Gain Compression Point	$G_{1dB}$		5	6	-	dB
Power-added Efficiency	$\eta_{add}$		-	27	-	%
Thermal Resistance	$R_{th}$	Channel to Case	-	10	12	$^\circ\text{C/W}$


Note: RF parameter sample size 10pcs. criteria (accept/reject)=(2/3)

The chip must be enclosed in a hermetically sealed environment for optimum performance and reliability.


# FLK207XV

## GaAs FET & HEMT Chips


www.DataSheet4U.com **POWER DERATING CURVE**




**DRAIN CURRENT vs. DRAIN-SOURCE VOLTAGE**



**OUTPUT POWER vs. INPUT POWER**



**P1dB & ηadd vs. VDS**



### S-PARAMETERS

$V_{DS} = 10V, I_{DS} = 480mA$


FREQUENCY (MHZ)	S11		S21		S12		S22	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
100	.994	-32.9	16.981	162.0	.008	72.9	.177	-152.4
500	.947	-111.8	9.690	118.1	.023	32.8	.361	-153.8
1000	.932	-142.9	5.469	98.1	.026	17.4	.414	-158.5
1500	.929	-155.1	3.712	87.3	.026	11.5	.442	-158.4
2000	.928	-161.6	2.775	79.5	.026	8.5	.469	-157.3
2500	.928	-165.6	2.195	73.0	.025	7.0	.497	-156.1
3000	.929	-168.4	1.799	67.2	.024	6.3	.526	-155.2
3500	.930	-170.6	1.512	61.9	.024	6.4	.556	-154.7
4000	.932	-172.2	1.293	57.1	.023	7.0	.585	-154.5
4500	.933	-173.6	1.122	52.5	.022	8.2	.613	-154.6
5000	.934	-174.7	.984	48.3	.022	9.8	.639	-154.8
5500	.935	-175.8	.870	44.3	.021	12.0	.664	-155.3
6000	.937	-176.7	.776	40.5	.020	14.6	.688	-155.8
6500	.938	-177.5	.696	37.0	.020	17.5	.709	-156.5
7000	.939	-178.3	.628	33.7	.020	20.8	.729	-157.1
7500	.940	-179.0	.569	30.6	.020	24.3	.748	-157.9
8000	.941	-179.6	.518	27.7	.020	27.8	.764	-158.6
8500	.942	179.7	.474	25.0	.020	31.5	.780	-159.4
9000	.943	179.1	.435	22.4	.020	35.0	.794	-160.1
9500	.944	178.5	.400	20.0	.020	38.4	.806	-160.8
10000	.945	178.0	.369	17.8	.021	41.6	.818	-161.5
10500	.945	177.4	.342	15.7	.022	44.6	.829	-162.2
11000	.946	176.9	.317	13.7	.022	47.4	.838	-162.9
11500	.947	176.4	.295	11.9	.023	49.9	.847	-163.6
12000	.947	175.9	.275	10.2	.024	52.2	.856	-164.2
12500	.948	175.4	.257	8.6	.025	54.2	.863	-164.8
13000	.948	174.9	.241	7.2	.026	56.1	.870	-165.4
13500	.949	174.5	.226	5.9	.027	57.7	.876	-166.0
14000	.949	174.0	.212	4.7	.028	59.2	.882	-166.5
14500	.949	173.5	.199	3.6	.029	60.5	.887	-167.1
15000	.950	173.1	.188	2.6	.030	61.6	.892	-167.6
15500	.950	172.7	.177	1.7	.031	62.7	.897	-168.1
16000	.950	172.2	.167	1.0	.033	63.6	.901	-168.6
16500	.951	171.8	.158	0.3	.034	64.4	.905	-169.0
17000	.951	171.4	.149	-0.2	.035	65.1	.909	-169.5
17500	.951	170.9	.141	-0.6	.036	65.8	.912	-169.9
18000	.951	170.5	.134	-0.9	.037	66.3	.915	-170.4
18500	.952	170.1	.127	-1.1	.039	66.9	.918	-170.8
19000	.952	169.7	.121	-1.2	.040	67.3	.921	-171.2
19500	.952	169.3	.115	-1.1	.041	67.7	.923	-171.6
20000	.952	168.9	.109	-1.0	.042	68.0	.925	-171.9

NOTE:\* The data includes bonding wires.

n: number of wires      Gate    n=8 (0.2mm length, 25µm Dia Au wire)  
    Drain    n=8 (0.2mm length, 25µm Dia Au wire)

# FLK207XV

## GaAs FET & HEMT Chips



**For further information please contact:**

**FUJITSU COMPOUND SEMICONDUCTOR, INC.**  
2355 Zanker Rd.  
San Jose, CA 95131-1138, U.S.A.  
Phone: (408) 232-9500  
FAX: (408) 428-9111  
www.fcsi.fujitsu.com

**FUJITSU MICROELECTRONICS, LTD.**  
Compound Semiconductor Division  
Network House  
Norreys Drive  
Maidenhead, Berkshire SL6 4FJ  
Phone: +44 (0)1628 504800  
FAX: +44 (0)1628 504888

### CAUTION

Fujitsu Compound Semiconductor Products contain **gallium arsenide (GaAs)** which can be hazardous to the human body and the environment. For safety, observe the following procedures:

- Do not put these products into the mouth.
- Do not alter the form of this product into a gas, powder, or liquid through burning, crushing, or chemical processing as these by-products are dangerous to the human body if inhaled, ingested, or swallowed.
- Observe government laws and company regulations when discarding this product. This product must be discarded in accordance with methods specified by applicable hazardous waste procedures.

Fujitsu Limited reserves the right to change products and specifications without notice.  
The information does not convey any license under rights of Fujitsu Limited or others.

© 1998 FUJITSU COMPOUND SEMICONDUCTOR, INC.  
Printed in U.S.A. FCSI0598M200

