

## Schottky Barrier Diodes

40V

V <sub>RM</sub> (V)	Package	Part Number	I <sub>F</sub> (AV) (A)	I <sub>FSM</sub> (A)	T <sub>J</sub> (°C)	T <sub>stg</sub> (°C)	V <sub>F</sub> (V) max	I <sub>F</sub> (A)	I <sub>R</sub> (mA)	I <sub>R</sub> (H) (mA)	R <sub>th</sub> (j-ℓ) R <sub>th</sub> (j-c) (°C/W)	Mass (g)	Fig. No.	Page where characteristic curve is shown
				50Hz Half-cycle Sinewave Single Shot					V <sub>R</sub> = V <sub>RM</sub> max	V <sub>R</sub> = V <sub>RM</sub> max				
40	Surface Mount	SSB-14	0.5	4	-40 to +150	0.58	0.5	0.1	5	100	150	0.009	1	79
		SFPB-54	1.0	30	-40 to +150	0.55	1.0	1	50	100	20	0.072	2	
		SFPB-64	1.5	60	-40 to +150	0.55	2.0	5	50	100	20	0.072		—
		SFPB-74	2.0	60	-40 to +150	0.5	2.0	5	50	100	20	0.072		
		SFPE-64	2.0	40	-40 to +150	0.6	2.0	0.2	20	150 (T <sub>j</sub> )	20	0.072		
		SPB-G34S	3.0	50	-40 to +150	0.55	3.0	3.5	50	100	5	0.29	3	81
		SPB-G54S	5.0	60	-40 to +150	0.55	5.0	5	50	100	5	0.29		
		SPB-64S	6.0	50	-40 to +150	0.55	3.0	3.5	50	100	5	0.29		
	Axial	AK 04	1.0	25	-40 to +150	0.55	1.0	1	50	100 (T <sub>j</sub> )	22	0.13	4	82
		AW 04	1.0	25	-40 to +150	0.58	1.0	5	35	150	22	0.13	—	
		EK 04	1.0	40	-40 to +150	0.55	1.0	5	50	100	20	0.3	5	83
		EK 14	1.5	40	-40 to +150	0.55	2.0	5	50	100	17	0.3	6	
		RK 14	1.7	60	-40 to +150	0.55	2.0	5	50	100	15	0.45	7	84
		RK 34	2.5	50	-40 to +150	0.55	2.5	5	50	100	12	0.6	8	
		RK 44	3.0	80	-40 to +150	0.55	3.0	5	50	100	8	1.2	9	85
	Frame-2Pin	FMB-G14	3.0	60	-40 to +150	0.55	3.0	5	100	100	4	2.1	10	86
		FMB-G14L	5.0	60	-40 to +150	0.55	5.0	5	100	100	4	2.1		
		FMB-G24H	10.0	150	-40 to +150	0.55	10.0	10	65	100	4	2.1		
	Center-tap	MPE-24H	15	100	-40 to +150	0.6	7.5	0.75	50	150 (T <sub>j</sub> )	2.5	1.04	11	82
		FMB-24	4.0	50	-40 to +150	0.55	2.0	5	35	100	4	2.1	12	87
		FMB-24M	6.0	60	-40 to +150	0.55	3.0	5	35	100	4	2.1		88
		FMW-24L	10.0	100	-40 to +150	0.55	5.0	5	175	150	4	2.1		87
		FMB-24L	10	60	-40 to +150	0.55	5.0	5	35	100	4	2.1	13	89
		FME-24L	10	80	-40 to +150	0.6	5.0	0.5	30	100	4	2.1		91
		FMB-34S	12	75	-40 to +150	0.58	6	5	35	100	2	5.5	13	91
		FMW-24H	15	120	-40 to +150	0.55	7.5	7.5	250	150	4	2.1	14	87
		FME-24H	15	100	-40 to +150	0.6	7.5	0.75	50	100	4	2.1		89
		FMB-24H	15	100	-40 to +150	0.55	7.5	7.5	50	100	4	2.1	87	
FMB-34		15	150	-40 to +150	0.55	7.5	10	65	100	2	5.5	15	90	
FMB-2204		20	150	-40 to +150	0.55	10	10	350	150	4	2.1	16	—	
FMB-2304		30	150	-40 to +150	0.55	15	15	500	150	4	2.1	88		
FMB-34M	30	300	-40 to +150	0.55	15.0	20	100	100	2	5.5	17	90		

