

G3R60MT07J

750 V 60 mΩ SiC MOSFET




Silicon Carbide MOSFET
N-Channel Enhancement Mode

V_{DS}	=	750 V
$R_{DS(ON)}(Typ.)$	=	60 mΩ
$I_D(T_C = 100^\circ C)$	=	31 A


Features

- G3R™ Technology with +15 V Gate Drive
- Softer $R_{DS(ON)}$ v/s Temperature Dependency
- LoRing™ - Electromagnetically Optimized Design
- Smaller $R_{G(INT)}$ and Lower Q_G
- Low Device Capacitances (C_{OSS} , C_{RSS})
- Superior Cost-Performance Index
- Robust Body Diode with Low V_F and Low Q_{RR}
- 100% Avalanche (UIL) Tested

Package



T0-263-7



D = Drain
G = Gate
S = Source
KS = Kelvin Source



Advantages

- Compatible with Commercial Gate Drivers
- Low Conduction Losses at all Temperatures
- Reduced Ringing
- Faster and More Efficient Switching
- Lesser Switching Spikes and Lower Losses
- Better Power Density and System Efficiency
- Ease of Paralleling without Thermal Runaway
- Superior Robustness and System Reliability

Applications

- Solar (PV) Inverters
- Server & Telecom Power Supplies
- Uninterruptible Power Supplies (UPS)
- EV / HEV Charging
- DC-DC Converters
- Switched Mode Power Supplies (SMPS)
- Energy Storage and Battery Charging
- Class D Amplifiers

Absolute Maximum Ratings (At $T_C = 25^\circ C$ Unless Otherwise Stated)

Parameter	Symbol	Conditions	Values	Unit	Note
Drain-Source Voltage	$V_{DS(max)}$	$V_{GS} = 0\text{ V}$, $I_D = 100\text{ }\mu\text{A}$	750	V	
Gate-Source Voltage (Dynamic)	$V_{GS(max)}$		-10 / +20	V	
Gate-Source Voltage (Static)	$V_{GS(op)}$	Recommended Operation	-5 / +15	V	
Continuous Forward Current	I_D	$T_C = 25^\circ C$, $V_{GS} = -5 / +15\text{ V}$	44	A	Fig. 15
		$T_C = 100^\circ C$, $V_{GS} = -5 / +15\text{ V}$	31		
		$T_C = 135^\circ C$, $V_{GS} = -5 / +15\text{ V}$	23		
Pulsed Drain Current	$I_{D(pulse)}$	$t_p \leq 3\text{ }\mu\text{s}$, $D \leq 1\%$, $V_{GS} = 15\text{ V}$, Note 1	100	A	Fig. 14
Power Dissipation	P_D	$T_C = 25^\circ C$	182	W	Fig. 16
Non-Repetitive Avalanche Energy	E_{AS}	$L = 7.5\text{ mH}$, $I_{AS} = 7.5\text{ A}$	210	mJ	
Operating and Storage Temperature	T_j , T_{stg}		-55 to 175	$^\circ C$	

Thermal/Package Characteristics

Parameter	Symbol	Conditions	Values			Unit	Note
			Min.	Typ.	Max.		
Thermal Resistance, Junction - Case	R_{thJC}			0.69	0.82	$^\circ C/W$	Fig. 13
Weight	W_T			1.45		g	

Note 1: Pulse Width t_p Limited by $T_{j(max)}$

G3R60MT07J

750 V 60 mΩ SiC MOSFET



Electrical Characteristics (At $T_C = 25^\circ\text{C}$ Unless Otherwise Stated)

Parameter	Symbol	Conditions	Values			Unit	Note
			Min.	Typ.	Max.		
Drain-Source Breakdown Voltage	V _{DSS}	V _{GS} = 0 V, I _D = 100 μA	750			V	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 750 V, V _{GS} = 0 V		1		μA	
Gate Source Leakage Current	I _{GSS}	V _{DS} = 0 V, V _{GS} = 20 V			100	nA	
		V _{DS} = 0 V, V _{GS} = -10 V			-100		
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 8.0 mA	1.8	2.50		V	Fig. 9
		V _{DS} = V _{GS} , I _D = 8.0 mA, T _j = 175°C		2.00			
Transconductance	g _{fs}	V _{DS} = 10 V, I _D = 15 A		7.8		S	Fig. 4
		V _{DS} = 10 V, I _D = 15 A, T _j = 175°C		8.6			
Drain-Source On-State Resistance	R _{DS(on)}	V _{GS} = 15 V, I _D = 15 A		60	78	mΩ	Fig. 5-8
		V _{GS} = 15 V, I _D = 15 A, T _j = 175°C		72			
Input Capacitance	C _{iss}	V _{DS} = 450 V, V _{GS} = 0 V f = 1 MHz, V _{AC} = 25mV		953		pF	Fig. 11
Output Capacitance	C _{oss}			90			
Reverse Transfer Capacitance	C _{rss}			7.9			
C _{oss} Stored Energy	E _{oss}			10		μJ	Fig. 12
C _{oss} Stored Charge	Q _{oss}			59		nC	Note 2
Effective Output Capacitance (Energy Related)	C _{o(er)}			98			
Effective Output Capacitance (Time Related)	C _{o(tr)}			131			
Gate-Source Charge	Q _{gs}	V _{DS} = 450 V, V _{GS} = -5 / +15 V I _D = 15 A Per IEC60747-4		13		nC	Fig. 10
Gate-Drain Charge	Q _{gd}			16			
Total Gate Charge	Q _g			47			
Internal Gate Resistance	R _{G(int)}	f = 1 MHz, V _{AC} = 25 mV		1.0		Ω	
Turn-On Switching Energy (Body Diode)	E _{On}	T _j = 25°C, V _{GS} = -5/+15V, R _{G(ext)} = 3 Ω, L = 60.0 μH, I _D = 15 A, V _{DD} = 450 V		30		μJ	Fig. 22,26
Turn-Off Switching Energy (Body Diode)	E _{Off}			4			
Turn-On Delay Time	t _{d(on)}	V _{DD} = 450 V, V _{GS} = -5/+15V R _{G(ext)} = 3 Ω, L = 60.0 μH, I _D = 15 A Timing relative to V _{DS} , Inductive load		12		ns	Fig. 24
Rise Time	t _r			6			
Turn-Off Delay Time	t _{d(off)}			7			
Fall Time	t _f			4			

*The chip technology was characterized up to 200 V/ns. The measured dV/dt was limited by measurement test setup and package.


Note 2: $C_{o(er)}$, a lumped capacitance that gives same stored energy as C_{oss} while V_{DS} is rising from 0 to 450V.

$C_{o(tr)}$, a lumped capacitance that gives same charging times as C_{oss} while V_{DS} is rising from 0 to 450V.

Reverse Diode Characteristics


Parameter	Symbol	Conditions	Values			Unit	Note
			Min.	Typ.	Max.		
Diode Forward Voltage	V_{SD}	$V_{GS} = -5\text{ V}, I_{SD} = 7\text{ A}$ $V_{GS} = -5\text{ V}, I_{SD} = 7\text{ A}, T_j = 175^\circ\text{C}$		4.4 3.9		V	Fig. 17-18
Continuous Diode Forward Current	I_S	$V_{GS} = -5\text{ V}, T_c = 100^\circ\text{C}$	16			A	
Diode Pulse Current	$I_{S(pulse)}$	$V_{GS} = -5\text{ V}, \text{Note 1}$		64		A	
Reverse Recovery Time	t_{rr}	$V_{GS} = -5\text{ V}, I_{SD} = 15\text{ A}, V_R = 450\text{ V}$ $dif/dt = 800\text{ A}/\mu\text{s}, T_j = 25^\circ\text{C}$		24		ns	
Reverse Recovery Charge	Q_{rr}			102		nC	
Peak Reverse Recovery Current	I_{rrm}			6		A	
Reverse Recovery Time	t_{rr}	$V_{GS} = -5\text{ V}, I_{SD} = 15\text{ A}, V_R = 450\text{ V}$ $dif/dt = 800\text{ A}/\mu\text{s}, T_j = 175^\circ\text{C}$		26		ns	
Reverse Recovery Charge	Q_{rr}			155		nC	
Peak Reverse Recovery Current	I_{rrm}			9		A	

Figure 1: Output Characteristics ($T_j = 25^\circ\text{C}$)




$$I_D = f(V_{DS}, V_{GS}); t_P = 250\text{ }\mu\text{s}$$

Figure 2: Output Characteristics ($T_j = 175^\circ\text{C}$)




$$I_D = f(V_{DS}, V_{GS}); t_P = 250\text{ }\mu\text{s}$$

Figure 3: Output Characteristics ($V_{GS} = 15\text{ V}$)




$$I_D = f(V_{DS}, T_j); t_P = 250\text{ }\mu\text{s}$$

Figure 4: Transfer Characteristics ($V_{DS} = 10\text{ V}$)




$$I_D = f(V_{GS}, T_j); t_P = 100\text{ }\mu\text{s}$$

Figure 5: On-State Resistance v/s Temperature




$$R_{DS(ON)} = f(T_j, V_{GS}); t_P = 250 \mu s; I_D = 15 A$$

Figure 6: On-State Resistance v/s Drain Current




$$R_{DS(ON)} = f(T_j, I_D); t_P = 250 \mu s; V_{GS} = 15 V$$

Figure 7: Normalized On-State Resistance v/s Temperature




$$R_{DS(ON)} = f(T_j); t_P = 250 \mu s; I_D = 15 A; V_{GS} = 15 V$$

Figure 8: On-State Resistance v/s Gate Voltage




$$R_{DS(ON)} = f(T_j, V_{GS}); t_P = 250 \mu s; I_D = 15 A$$

Figure 9: Threshold Voltage Characteristics




$$V_{GS(th)} = f(T_j); V_{DS} = V_{GS}; I_D = 8.0 \text{ mA}$$

Figure 10: Gate Charge Characteristics




$$I_D = 15 \text{ A}; V_{DS} = 450 \text{ V}; T_c = 25^\circ\text{C}$$

Figure 11: Capacitance v/s Drain-Source Voltage




$$f = 1 \text{ MHz}; V_{AC} = 25 \text{ mV}$$

Figure 12: Output Capacitor Stored Energy




$$E_{oss} = f(V_{DS})$$

Figure 13: Transient Thermal Impedance




$$Z_{th,jc} = f(t_p, D); D = t_p / T$$

Figure 14: Safe Operating Area ($T_c = 25^\circ\text{C}$)




$$I_D = f(V_{DS}, t_p); T_j \leq 175^\circ\text{C}; D = 0$$

Figure 15: Current De-rating Curve




$$I_D = f(T_C); T_j \leq 175^\circ\text{C}$$

Figure 16: Power De-rating Curve




$$P_D = f(T_C); T_j \leq 175^\circ\text{C}$$

Figure 17: Body Diode Characteristics ($T_j = 25^\circ\text{C}$)




$$I_D = f(V_{DS}, V_{GS}); t_P = 250 \mu\text{s}$$

Figure 18: Body Diode Characteristics ($T_j = 175^\circ\text{C}$)




$$I_D = f(V_{DS}, V_{GS}); t_P = 250 \mu\text{s}$$

Figure 19: Third Quadrant Characteristics ($T_j = 25^\circ\text{C}$)




$$I_D = f(V_{DS}, V_{GS}); t_P = 250 \mu\text{s}$$

Figure 20: Third Quadrant Characteristics ($T_j = 175^\circ\text{C}$)




$$I_D = f(V_{DS}, V_{GS}); t_P = 250 \mu\text{s}$$

Figure 21: Inductive Switching Energy v/s Drain Current
 ($V_{DD} = 350V$)




$T_j = 25^\circ C$; $V_{GS} = -5/+15V$; $R_{G(ext)} = 3 \Omega$; $L = 60.0\mu H$

Figure 22: Inductive Switching Energy v/s Drain Current
 ($V_{DD} = 450V$)




$T_j = 25^\circ C$; $V_{GS} = -5/+15V$; $R_{G(ext)} = 3 \Omega$; $L = 60.0\mu H$

Figure 23: Inductive Switching Energy v/s $R_{G(ext)}$
 ($V_{DD} = 450V$)




$T_j = 25^\circ C$; $V_{GS} = -5/+15V$; $I_{DS} = 15 A$; $L = 60.0\mu H$

Figure 24: Switching Time v/s $R_{G(ext)}$
 ($V_{DD} = 450V$)




$T_j = 25^\circ C$; $V_{GS} = -5/+15V$; $I_{DS} = 15 A$; $L = 60.0\mu H$

Figure 25: Inductive Switching Energy v/s Temperature
 ($V_{DD} = 450V$)




$T_j = 25^\circ C$; $V_{GS} = -5/+15V$; $R_{G(ext)} = 3 \Omega$; $I_{DS} = 15 A$; $L = 60.0 \mu H$

Figure 26: dV/dt v/s $R_{G(ext)}$
 ($V_{DD} = 450V$)




$T_j = 25^\circ C$; $V_{GS} = -5/+15V$; $I_{DS} = 15 A$; $L = 60.0 \mu H$


Gate Charge Circuit




Gate Charge Waveform




Switching Time Circuit




Switching Time Waveform




Switching Energy Circuit




Switching Energy Waveform




Reverse Recovery Circuit



Reverse Recovery Waveform



TO-263-7 Package Outline



Compliance

RoHS Compliance

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS 2), as adopted by EU member states on January 2, 2013 and amended on March 31, 2015 by EU Directive 2015/863. RoHS Declarations for this product can be obtained from your GeneSiC representative.

REACH Compliance

REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact a GeneSiC representative to insure you get the most up-to-date REACH SVHC Declaration. REACH banned substance information (REACH Article 67) is also available upon request.

Disclaimer

GeneSiC Semiconductor, Inc. reserves right to make changes to the product specifications and data in this document without notice. GeneSiC disclaims all and any warranty and liability arising out of use or application of any product. No license, express or implied to any intellectual property rights is granted by this document.

Unless otherwise expressly indicated, GeneSiC products are not designed, tested or authorized for use in life-saving, medical, aircraft navigation, communication, air traffic control and weapons systems, nor in applications where their failure may result in death, personal injury and/or property damage.

Related Links

- SPICE Models: https://www.genesicsemi.com/sic-mosfet/G3R60MT07J/G3R60MT07J_SPICE.zip
- PLECS Models: https://www.genesicsemi.com/sic-mosfet/G3R60MT07J/G3R60MT07J_PLECS.zip
- CAD Models: https://www.genesicsemi.com/sic-mosfet/G3R60MT07J/G3R60MT07J_3D.zip
- Gate Driver Reference: <https://www.genesicsemi.com/technical-support>
- Evaluation Boards: <https://www.genesicsemi.com/technical-support>
- Reliability: <https://www.genesicsemi.com/reliability>
- Compliance: <https://www.genesicsemi.com/compliance>
- Quality Manual: <https://www.genesicsemi.com/quality>

Revision History

- Rev 21/May: Initial Release



www.genesicsemi.com/sic-mosfet/