

1A Single Cell Li-Ion Battery Linear Charger

Features

- No External Power MOSFET, Sense Resistor or Blocking Diode Required
- 1% Regulation Voltage Accuracy
- Programmable Constant Charge Current Limit up to 1A
- Automatic Recharge
- Complete Pre-Charge, Constant Current, Constant Voltage and Charge Termination Charge Procedure
- Support for 5V Power Supply Voltage
- Internal Thermal Protection Circuit
- SOT-23-5 & SOP-8 (FD) Package

General Description

The G5803 is a standalone linear Li-Ion battery charger with a complete pre-charge, constant-current and constant-voltage charge loop.

No external power MOSFET, sense resistor and blocking diode is required due to internal power MOSFET architecture. The charge voltage is regulated at 4.2V, and the charge current is programmable by an external resistor. After the final regulation voltage is reached and the charge current drops to 1/10th the programmed charge current, the open drain NMOS $\overline{\text{CHRG}}$ pin would be turn off automatically without terminating the charge loop.

Other features include under voltage lockout, automatic recharge, over temperature protection and a charge status indication pin.

Ordering Information


ORDER NUMBER	MARKING	TEMP. RANGE	PACKAGE (Green)
G5803T11U	5803x	-40°C ~ +85°C	SOT-23-5
G5803F11U	G5803	-40°C ~ +85°C	SOP-8 (FD)

Note: T1: SOT-23-5 F1: SOP-8 (FD)

1: Bonding Code

U: Tape & Reel


Pin Configuration



Note: Recommend connecting the Thermal Pad to the Ground for excellent power dissipation.

Typical Application Circuit

500mA Single Cell Li-Ion Charger



*1.5Ω resistor in series with a ceramic capacitor will minimize the start-up voltage overshoot transients