



# 1A Low Dropout Regulator with Enable

## Features

- Adjustable Output from 1.2V to 4.8V Using External Resistors
- 1.5V, 1.8V and 2.5V Options by Setting ADJ Pin Below 0.2V
- Over current and over temperature protection
- 400mV dropout @1A
- Enable pin
- 10µA quiescent current in shutdown
- SOT-89-5 Package

## Applications

- Battery powered systems
- Motherboards
- Peripheral cards
- Network cards
- Set Top Boxes
- Medical Equipment
- Notebook Computers

## General Description

The G961 is a high performance positive voltage regulator designed for use in applications requiring very low dropout voltage at up to 1 Amps. Since it has superior dropout characteristics compared to regular LDOs, it can be used to supply 2.5V on motherboards or 1.5V, 1.8V on peripheral cards from the 3.3V supply thus allowing the elimination of costly heatsinks. An enable pin further reduces power dissipation while shut down. The G961 provides excellent regulation over variations in line, load and temperature.

The SOT-89-5 is available with 1.5V, 1.8V and 2.5V internally preset outputs that are also adjustable using external resistors.

## Ordering Information


ORDER NUMBER	ORDER NUMBER (Pb free)	MARKING	TEMP. RANGE	PACKAGE
G961-15ADJTEU	G961-15ADJTEUf	961-15	-40°C ~ +85°C	SOT-89-5
G961-18ADJTEU	G961-18ADJTEUf	961-18	-40°C ~ +85°C	SOT-89-5
G961-25ADJTEU	G961-25ADJTEUf	961-25	-40°C ~ +85°C	SOT-89-5

Note: TE: SOT-89-5


U : Tape & Reel

e.g. 18 denotes the 1.8V output voltage.

## Pin Configuration



## Typical Application Circuit



$$V_O = \frac{1.2 (R_1 + R_2)}{R_2} \text{ Volts}$$

R2=12kΩ is recommended

R3 should be connected for current  $I_{ENH}$  restriction as  $V_{EN} > V_{IN} + 0.3V$



<b>Absolute Maximum Ratings</b>	(Note 1)
Input Voltage.....	7V
V <sub>EN</sub> Voltage.....	V <sub>IN</sub> +0.3V
Power Dissipation Internally Limited	(Note 2)
Maximum Junction Temperature.....	150°C
Storage Temperature Range.....	-65°C ≤ T <sub>J</sub> ≤ +150°C
Reflow Temperature (soldering, 10sec).....	260°C
Thermal Resistance Junction to Ambient, (θ <sub>JA</sub> )	
SOT-89-5.....	128°C/W
Thermal Resistance Junction to Case, (θ <sub>JC</sub> )	
SOT-89-5.....	19°C/W
ESD Rating (Human Body Model).....	2kV

<b>Operation Conditions</b>	(Note 1)
Input Voltage.....	2.2V ~5.5V
Temperature Range.....	-40°C ≤ T <sub>A</sub> ≤ +85°C

## Electrical Characteristics

V<sub>EN</sub>=V<sub>IN</sub>, V<sub>IN</sub>=5V, I<sub>O</sub>=0.5A, C<sub>IN</sub>=4.7μF, C<sub>OUT</sub>=10μF, T<sub>A</sub>=T<sub>J</sub>=25°C unless otherwise specified (Note 3)

PARAMETER	SYMBOL	CONDITION	MIN	TYP	MAX	UNIT
Supply Voltage	V <sub>IN</sub>		2.2	---	5.5	V
Output Voltage	V <sub>O</sub>	V <sub>IN</sub> =V <sub>O</sub> +0.7V, I <sub>O</sub> =10mA	-2	V <sub>O</sub>	2	%
Line Regulation		V <sub>O</sub> +0.7V ≤ V <sub>IN</sub> ≤ 5.5V, I <sub>O</sub> =10mA	---	0.2	2	%
Load Regulation		10mA ≤ I <sub>O</sub> ≤ 1A	---	0.8	2	%
Quiescent Current	I <sub>Q</sub>	V <sub>IN</sub> =3.3V, V <sub>EN</sub> =V <sub>IN</sub>	---	1.7	2.5	mA
		V <sub>IN</sub> =3.3V, V <sub>EN</sub> =0V	---	16	35	μA
Ripple Rejection		fi=120Hz, 1V <sub>P-P</sub> , I <sub>O</sub> =100mA	---	55	---	dB
Dropout Voltage	V <sub>D</sub>	I <sub>O</sub> =1A	---	0.4	0.6	V
Short Circuit Current			---	0.8	---	A
Over Temperature			---	150	---	°C
V <sub>EN</sub> Voltage High	V <sub>ENH</sub>	Output Active	1.6	---	---	V
V <sub>EN</sub> Voltage Low	V <sub>ENL</sub>	Output Disabled	---	---	0.4	V
V <sub>EN</sub> Bias Current Low	I <sub>ENL</sub>	V <sub>EN</sub> =0.4V	---	---	20	μA
ADJ Reference Voltage	V <sub>REF</sub>	V <sub>IN</sub> =2.2V, V <sub>ADJ</sub> =V <sub>OUT</sub> , I <sub>O</sub> =10mA	1.188	1.2	1.212	V
ADJ Pin Threshold			---	0.2	---	V

**Note 1:** Absolute Maximum Ratings are limits beyond which damage to the device may occur. Operating Conditions are conditions under which the device functions but the specifications might not be guaranteed. For guaranteed specifications and test conditions see the Electrical Characteristics.

**Note2:** The maximum power dissipation is a function of the maximum junction temperature, T<sub>Jmax</sub>; total thermal resistance, θ<sub>JA</sub>, and ambient temperature T<sub>A</sub>. The maximum allowable power dissipation at any ambient temperature is (T<sub>Jmax</sub>-T<sub>A</sub>) / θ<sub>JA</sub>. If this dissipation is exceeded, the die temperature will rise above 150°C and IC will go into thermal shutdown.

**Note3:** Low duty pulse techniques are used during test to maintain junction temperature as close to ambient as possible.

**Note4:** The type of output capacitor should be tantalum or aluminum.

## Definitions

### Dropout Voltage

The input/output Voltage differential at which the regulator output no longer maintains regulation against further reductions in input voltage. Measured when the output drops 2% below its nominal value, dropout voltage is affected by junction temperature, load current and minimum input supply requirements.

### Line Regulation

The change in output voltage for a change in input voltage. The measurement is made under conditions of low dissipation or by using pulse techniques such that average chip temperature is not significantly affected.

### Load Regulation

The change in output voltage for a change in load current at constant chip temperature. The measurement is made under conditions of low dissipation or by using pulse techniques such that average chip temperature is not significantly affected.

### Maximum Power Dissipation

The maximum total device dissipation for which the regulator will operate within specifications.


### Quiescent Bias Current

Current which is used to operate the regulator chip and is not delivered to the load.


**Typical Performance Characteristics**

$V_{EN}=V_{IN}$ ,  $V_{IN}=5V$ ,  $I_O=0.5A$ ,  $C_{IN}=4.7\mu F$ ,  $C_{OUT}=10\mu F$ ,  $T_A=T_J=25^\circ C$   
 ( $V_{OUT}=1.8V$ )


**Line Transient Response**




**Load Transient Response**




**Short Circuit Current**




**Ripple Rejection**



**Overcurrent Protection Characteristics**









**Start-up**







Typical Performance Characteristics (Continued)



**Recommended Minimum Footprint**




**Package Information**



**SOT-89-5 Package**

SYMBOL	DIMENSION IN MM		DIMENSION IN INCH	
	MIN	MAX	MIN	MAX
A	4.40	4.60	0.173	0.181
B	4.05	4.25	0.159	0.167
C	1.50	1.70	0.059	0.067
D	1.30	1.50	0.051	0.059
E	2.40	2.60	0.094	0.102
F	0.80	----	0.031	----
G	3.00 REF		0.118 REF	
H	1.50 REF		0.059 REF	
I	0.40	0.52	0.016	0.020
J	1.40	1.60	0.055	0.063
K	0.35	0.41	0.014	0.016
L	5° TYP		5° TYP	

**Taping Specification**



PACKAGE	Q'TY/REEL
SOT-89-5	1,000 ea

GMT Inc. does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and GMT Inc. reserves the right at any time without notice to change said circuitry and specifications.