


## GLASS PASSIVATED BRIDGE RECTIFIERS

REVERSE VOLTAGE - 600 Volts FORWARD CURRENT - 8.0 Amperes

## **FEATURES**

- ●Surge overload rating -200 amperes peak
- Ideal for printed circuit board
- Reliable low cost construction utilizing molded plastic technique
- Plastic material has U/L
   the flammability classification 94V-0
- Mounting postition: Any



## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 ℃ ambient temperature unless otherwise specified.

Single phase, half wave ,60Hz, resistive or inductive load.


For capacitive load, derate current by 20%


CHARACTERISTICS	SYMBOL	GBU806L	UNIT
Maximum Recurrent Peak Reverse Voltage	Vrrm	600	V
Maximum RMS Voltage	VRMS	420	V
Maximum DC Blocking Voltage	VDC	600	V
Maximum Average Forward (with heatsink Note 2) Rectified Current @ Tc=100℃ (without heatsink)	I(AV)	8.0 2.9	А
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Super Imposed on Rated Load (JEDEC Method)	IFSM	200	А
Maximum Forward Voltage at 4.0A DC	VF	0.92	V
Maximum DC Reverse Current @ TJ=25℃ at Rated DC Blocking Voltage @ TJ=125℃	lr	10.0 500	μА
I <sup>2</sup> t Rating for Fusing (t<8.3ms)	l <sup>2</sup> t	127	A <sup>2</sup> s
Typical Junction Capacitance Per Element (Note1)	Cı	60	pF
Typical Thermal Resistance	Rejc	2.2	°C/W
Operating Temperature Range	TJ	-55 to +150	$^{\circ}$
Storage Temperature Range	Тѕтс	-55 to +150	$^{\circ}$


NOTES: 1.Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

- 2.Device mounted on 75mm\*75mm\*1.6mm Cu plate heatsink.
- 3.The typical data above is for reference only( 典型值仅供参考).



















The cruve graph is for reference only, can't be the basis for judgment(曲线图仅供参考)!