


GE13007

NPN SILICON TRIPLE DIFFUSED MESA TYPE TRANSISTOR


Description

The GE13007 is designed for electronic transformers and power switching circuit applications.

Package Dimensions



Marking :



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	4.40	4.80	c1	1.25	1.45
b	0.76	1.00	b1	1.17	1.47
c	0.36	0.50	L	13.25	14.25
D	8.60	9.00	e	2.54 REF.	
E	9.80	10.4	L1	2.60	2.89
L4	14.7	15.3	Ø	3.71	3.96
L5	6.20	6.60	A1	2.60	2.80

Absolute Maximum Ratings at Ta = 25°C


Parameter	Symbol	Ratings	Unit
Junction Temperature	Tj	+150	°C
Storage Temperature	Tstg	-55 ~ +150	°C
Collector to Base Voltage	VCBO	700	V
Collector to Emitter Voltage	VCEO	400	V
Emitter to Base Voltage	VEBO	9	V
Collector Current	IC	8	A
Total Power Dissipation at Tc=25°C	PD	80	W


Electrical Characteristics(Tc = 25°C Unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Collector-Emitter Sustaining Voltage	VCE(sus)	400	-	-	V	IC=10mA, IB=0
Collector-Base Breakdown Voltage	BVCBO	700	-	-	V	IC=1mA, IE=0
Emitter-Base Breakdown Voltage	BVEBO	9	-	-	V	IE=1mA, IC=0
Collector Cutoff Current	ICBO	-	-	100	µA	VCB=700V
Collector-Emitter Cutoff Current	ICEO	-	-	50	µA	VCE=400V
Emitter-Base Cutoff Current	IEBO	-	-	10	µA	VEB=7V
Collector-Emitter Saturation Voltage	*VCE(sat)1	-	-	1.2	V	IC=2A, IB=400mA
	*VCE(sat)2	-	-	3.0	V	IC=8A, IB=2A
Base-Emitter Saturation Voltage	*VBE(sat)	-	-	1.2	V	IC=2A, IB=400mA
DC Current Gain	*HFE1	8	-	50		VCE=5V, IC=2A
	*HFE2	5	-	-		VCE=5V, IC=5A
Frequency characteristics	fT	4	-	-	MHz	VCE=10V, IC=500mA, f=1MHz
Turn-On Time	ton	-	-	1.6	µs	VCC=125V, IC=5A, IB1=IB2=0.4A
Storage Time	tstg	-	-	3		
Fall Time	tf	-	-	0.7		

*Pulse Test: Pulse Width=300µs, Duty Cycle ≤ 2%

Characteristics Curve





Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:

- **Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165