

GJ1060

NPN EPITAXIAL PLANAR TRANSISTOR



Description

The GJ1060 is designed for relay drivers, high-speed inverters, converters and other general large-current switching.

Features

- Low Collector-Emitter Saturation Voltage : $V_{CE(sat)} = 0.4V$ (Max.) @ $I_C = 3A$, $I_B = 0.3A$,

Package Dimensions



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	6.40	6.80	G	0.50	0.70
B	5.20	5.50	H	2.20	2.40
C	6.80	7.20	J	0.45	0.55
D	2.40	3.00	K	0	0.15
E	2.30 REF.		L	0.90	1.50
F	0.70	0.90	M	5.40	5.80
S	0.60	0.90	R	0.80	1.20

Absolute Maximum Ratings ($T_A = 25^\circ C$)

Parameter	Symbol	Ratings	Unit
Collector to Base Voltage	V_{CB0}	60	V
Collector to Emitter Voltage	V_{CE0}	50	V
Emitter to Base Voltage	V_{EB0}	6	V
Collector Current	I_C	5	A
Collector Current (Pulse)	I_{CP}	9	A
Total Device Dissipation ($T_C = 25^\circ C$)	P_D	20	W
Junction Temperature	T_J	150	$^\circ C$
Storage Temperature	T_{stg}	-55 ~ +150	$^\circ C$

Electrical Characteristics ($T_A = 25^\circ C$ unless otherwise noted)


Symbol	Min.	Typ.	Max.	Unit	Test Conditions
V_{CB0}	60	-	-	V	$I_C = 1mA$, $I_E = 0$
V_{CE0}	50	-	-	V	$I_C = 1mA$, $I_B = 0$
V_{EB0}	6	-	-	V	$I_E = 1mA$, $I_C = 0$
I_{CBO}	-	-	100	μA	$V_{CB} = 40V$, $I_E = 0$
I_{EBO}	-	-	100	μA	$V_{EB} = 4V$, $I_C = 0$
* $V_{CE(sat)}$	-	-	0.4	V	$I_C = 3A$, $I_B = 0.3A$
* h_{FE1}	70	-	280		$V_{CE} = 2V$, $I_C = 1A$
* h_{FE2}	30	-	-		$V_{CE} = 2V$, $I_C = 3A$
f_T	-	30	-	MHz	$V_{CE} = 5V$, $I_C = 1A$
C_{ob}	-	100	-	pF	$V_{CB} = 10V$, $I_E = 0$, $f = 1MHz$
t_{on} (Turn-on Time)	-	0.1	-	μS	See specified test circuit
t_{stg} (Storage Time)	-	1.4	-		
t_f (Fall Time)	-	0.2	-		

*Pulse Test: Pulse Width $\leq 380\mu s$, Duty Cycle $\leq 2\%$

Classification Of hFE1





Rank	Q	R	S
Range	70 - 140	100 - 200	140 - 280




Switching Time Test Circuit



$$I_C = 10I_{B1} = -10I_{B2} = 2A$$

Characteristics Curve





Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:

- **Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
- TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
- TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165