

■ Features


1. Built-in Schmidt trigger circuit
2. Low threshold input current
(I_{FLH} : MAX. 8mA)
3. Low level supply current
(I_{CCL} : MAX. 5mA)
4. Operating supply voltage V_{cc} : 4.5~17V
5. TTL and CMOS compatible output
6. Wide gap between LED and detector
(5mm)

■ Applications

1. Copiers, printers, facsimiles
2. Optoelectronic switches, optoelectronic counters

■ Outline Dimensions

(Unit : mm)



* OPIC is a registered trademark of Sharp and stands for Optical IC. It has a light detecting element and signal processing circuitry integrated onto a single chip.

■ Absolute Maximum Ratings

 $(T_a = 25^\circ C)$

Parameter	Symbol	Rating	Unit
Input	Forward current	I_F	mA
	*1 Peak forward current	I_{FM}	A
	Reverse voltage	V_R	V
	Power dissipation	P	mW
Output	Supply voltage	V_{cc}	V
	Low level output current	I_{OL}	mA
	Power dissipation	P_o	mW
	Operating temperature	T_{opr}	${}^\circ C$
Storage temperature		T_{stg}	${}^\circ C$
*2 Soldering temperature		T_{sol}	${}^\circ C$

*1 Pulse width $\leq 100\mu s$, Duty ratio = 0.01

*2 For 5 seconds

■ Electro-optical Characteristics

Parameter		Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Input	Forward voltage	V _F	I _F =8mA	—	1.14	1.4	V
	Reverse current	I _R	V _R =3V	—	—	10	μA
Output	Operating supply voltage	V _{CC}		4.5	—	17	V
	Low level output voltage	V _{OL}	I _{OL} =16mA, V _{CC} =5V, I _F =0	—	0.15	0.4	V
	High level output voltage	V _{OH}	V _{CC} =5V, I _F =8mA	4.9	—	—	V
	Low level supply current	I _{CCL}	V _{CC} =5V, I _F =0	—	2.5	5.0	mA
Transfer characteristics	High level supply current	I _{CHH}	V _{CC} =5V, I _F =8mA	—	1.0	3.0	mA
	*3 "Low→High" threshold input current	I _{FLH}	V _{CC} =5V	—	1.5	8.0	mA
	*4 Hysteresis	I _{FLH} /I _{FLL}		0.55	0.75	0.95	—
	"Low→High" propagation time	t _{PLH}	V _{CC} =5V	—	3	9	μs
Response time	"High→Low" propagation time	t _{PHL}	I _F =8mA	—	5	15	
	Rise time	t _r	R _L =280Ω	—	0.1	0.5	
	Fall time	t _f		—	0.05	0.5	

*3 I_{FLH} represents forward current when output goes from low to high.

*4 I_{FLL} represents forward current when output goes from high to low.

Hysteresis stands for I_{FLH}/I_{FLL}.

In order to stabilize power supply line, connect a by-pass capacitor of more than 0.01μF between V_{CC} and GND near the device.

■ Recommended Operating Conditions

Parameter	Symbol	Operating temperature	MIN.	MAX.	Unit
Low level output current	I _{OL}	Ta=0~+70°C	—	16.0	mA
Forward current	I _F		10.0	20.0	mA

Fig. 1 Forward Current vs. Ambient Temperature




Fig. 2 Output Power Dissipation vs. Ambient Temperature




Fig. 3 Low Level Output Current vs. Ambient Temperature




Fig. 5 Relative Threshold Input Current vs. Supply Voltage




Fig. 7 Low Level Output Voltage vs. Low Level Output Current




Fig. 4 Forward Current vs. Forward Voltage




Fig. 6 Relative Threshold Input Current vs. Ambient Temperature




Fig. 8 Low Level Output Voltage vs. Ambient Temperature




Fig. 9 Supply Current vs. Supply Voltage




Fig. 10 Propagation Time vs. Forward Current





Fig. 11 Rise Time, Fall Time vs. Load Resistance



Test Circuit for Response Time

