

MARCH 2003

GPS ANTENNA WITH LOW NOISE AMPLIFIER

GPA-017S

SPECIFICATION

PRELIMINARY

www.DataSheet4U.com

**BY FURUNO ELECTRIC CO., LTD.
SYSTEM PRODUCTS DEVELOPMENT &
MARKETING DIVISION**

No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, for any purpose without the express written permission of the publisher, FURUNO ELECTRIC CO., LTD.

© **2003 FURUNO ELECTRIC CO., LTD.** All rights reserved.

The Global Positioning System (GPS) is operated by the U. S. DoD and is subject to U. S. Government Selective Availability (SA) policy, thus FURUNO is not liable for the degradation by SA. Users are expected to be familiar with the System and make full use of it with their own responsibility.

FURUNO ELECTRIC CO., LTD. reserves the right to make changes to it's products and specifications without notice.

CONTENTS

1. Scope.....	1
2. Model name.....	1
3. performance	
3.1. Ratings	1
3.2. Electrical characteristics	1
3.2.1. Antenna characteristics	1
3.2.2. LNA	1

1. Scope

This paper describes outer shape, mechanism and characteristics of GPS antenna.

2. Model name

GPS antenna GPA-017S

3. Performance

3.1. Ratings

Item	Rating
Operating temperature	-25°C to +65°C
Storage temperature	-35°C to +75°C
Operating relative humidity	<95% RH (without condensation)
Power voltage	5.0VDC

3.2. Electrical characteristics

3.2.1 Antenna

Item	Remarks
Frequency range	1,575.42MHz \pm 1.023MHz
Polarization	R. H. C. P. (Right Hand Circular Polarization)
Gain	> 2.0dBi (at 90° elev. angle) > -4.0dBi (at 10° elev. angle)
Axial ratio	< 4.0dBi (at 90° elev. angle)

3.2.2. LNA (not including cable, at 25 \pm 5°C, 65 \pm 20% humidity)

Item	Ratings	Criteria for environmental tests
Frequency range	1,575.42MHz \pm 1.023MHz	1,575.42MHz \pm 1.023MHz
Gain	27.5 \pm 5.5dB	26.5 \pm 5.5dB
Noise figure	<1.6 dB	<1.8dB
Out band attenuation	fo \pm 20MHz (>7dB) fo \pm 50MHz (>20dB) fo \pm 100MHz(>30dB) (fo=1575.42MHz)	fo \pm 20MHz (>6dB) fo \pm 50MHz (>19dB) fo \pm 100MHz(>28dB) (fo=1575.42MHz)
Output VSWR	<2.0	<2.0
Supply voltage	4.75 \pm 0.75VDC (See Note *1)	
Power consumption	<25mA	

*1 Supply voltage: Reversed Bias-T may cause damage.