



Fast Recovery Surface Mount Rectifiers
 Reverse Voltage 50 to 1000 Volts Forward Current 1.5 Amperes

Features



- ◆ Fast switching for high efficiency
- ◆ For surface mounted applications
- ◆ Glass passivated chip
- ◆ Low reverse leakage current
- ◆ Low forward voltage drop
- ◆ High current capability
- ◆ Plastic material has UL flammability classification 94V-0



DO-214AC (SMA)

Mechanical Data

- ◆ Case : Molded plastic
- ◆ Polarity : Indicated by cathode band
- ◆ Weight : 0.002 ounce, 0.064 gram



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.
 Single phase, half wave, 60Hz, resistive or inductive load.
 For capacitive load, derate current by 20%

Parameter	Symbols	GROAA	GROBA	GRODA	GROGA	GROJA	GROKA	GROMA	Units	
Maximum repetitive peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts	
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	Volts	
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	Volts	
Maximum average forward rectified current @ $T_J=90^\circ\text{C}$	I_{AV}	1.5								Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	50.0								Amps
Maximum forward voltage at 1.5A DC	V_F	1.3								Volts
Maximum DC reverse current @ $T_J=25^\circ\text{C}$ at rated DC blocking voltage @ $T_J=125^\circ\text{C}$	I_R	5.0 200								μA
Maximum reverse recovery time (Note 1)	t_{tr}	150				250	500		nS	
Typical junction capacitance (Note 2)	C_J	30								pF
Typical thermal resistance (Note 3)	$R_{\theta JL}$	20								$^\circ\text{C/W}$
Operating temperature range	T_J	-55 to +150								$^\circ\text{C}$
Storage temperature range	T_{STG}	-55 to +150								$^\circ\text{C}$

- Notes:**
1. Reverse Recovery Test Conditions: $I_F=0.5\text{A}$, $I_R=1.0\text{A}$, $I_{RR}=0.25\text{A}$
 2. Measured at 1.0MHz and applied reverse voltage of 4.0V D.C.
 3. Thermal Resistance Junction to Lead

RATINGS AND CHARACTERISTIC CURVES

FIG.1 - FORWARD CURRENT DERATING CURVE




FIG.2 - MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3 - TYPICAL FORWARD CHARACTERISTICS




FIG.4 - TYPICAL REVERSE CHARACTERISTICS

