

GS324

Low Power Quad Operational Amplifiers

Product Description

The GS324 consists of four independent, high gain, internally frequency compensated operational amplifiers which were designed specifically to operate from a single power supply over a wide range of voltages.

Operation from split power supplies is also possible and the low power supply current drains in independent of the magnitude of the power supply voltage.


Application areas include transducer amplifiers, DC gain blocks and all the conventional op amp circuits, which now can be more easily implemented in single power supply systems.

For example, the GS324 can be directly operated off of the standard +5V power supply voltage which is used in digital systems and will easily provide the required interface electronics without requiring the additional $\pm 15V$ power supplies.


Features

- Wide range of supply voltages 3V to 32V
- Low supply current drain independent of Supply
- Supply Current 0.7mA TYP.
- Low input biasing current
- Low input offset voltage and offset current
- Input common-mode voltage range includes ground
- Differential input voltage range equal to the power supply voltage
- DC voltage gain: 100V/mV TYP.
- Internally frequency compensation
- RoHS Compliant, 100%Pb & Halogen Free
- ESD Protection(2KV) between V+/V- and GND


Block Diagram



Pin Assignments




Ordering Information



| Device | Package | Quantity Reel |
|---------|---------|---------------|
| GS324SF | SOP-14 | 4000 PCS |

Marking Information



Absolute Maximum Ratings

| Symbol | Parameter | Value | Unit | |
|-----------------------------------|----------------------------------------|-------------|------|------|
| V _{CC} | Single Supply | 32 | V | |
| V _{CC} , V _{EE} | Split Supply | ±16 | V | |
| V _{IDR} | Input Differential Voltage Range | ±32 | V | |
| I _{OS} | Output Short-circuit to GND | Continuous | | |
| T _J | Junction Temperature | 150 | °C | |
| T _{STG} | Storage Temperature Range | -65 to +150 | °C | |
| T _A | Operating Ambient Temperature Range | -40 to 85 | °C | |
| θ _{JA} | Junction to Ambient Thermal Resistance | SOP-14 | 150 | °C/W |
| θ _{JC} | Junction to Case Thermal Resistance | SOP-14 | 23 | °C/W |
| ESD | ESD Rating (HBM) | 2K | V | |

Electrical Characteristics

at specified free-air temperature, V_{CC}=5V (Unless Otherwise Noted)

| Symbol | Parameter | Test Conditions* | Min | Typ | Max | Unit | |
|------------------|---------------------------------------------------------|-----------------------------------------------------------------------------------------------|------------|---------------------------|-----|-------|----|
| V _{IO} | Input offset voltage | V _{CC} =5V to Max. V _{IC} =V _{ICR} min, V _O =1.4V | 25°C | | 2 | 3 | mV |
| | | | Full range | | | 5 | |
| αV _{IO} | Average temperature coefficient of input offset voltage | | Full range | 7 | | μV/°C | |
| I _{IO} | Input offset current | V _O =1.4V | 25°C | 2 | 50 | nA | |
| | | | Full range | | 150 | | |
| αI _{IO} | Average temperature coefficient of input offset current | | Full range | 10 | | pA/°C | |
| I _{IB} | Input bias current | V _O =1.4V | 25°C | 20 | 250 | nA | |
| | | | Full range | | 500 | | |
| V _{ICR} | Common-mode input voltage range | V _{CC} =5V to MAX | 25°C | 0 to V _{CC} -1.5 | | V | |
| | | | Full range | 0 to V _{CC} -2 | | | |
| V _{OH} | High-level output voltage | R _L ≥2kΩ | 25°C | V _{CC} -1.5 | | V | |
| | | V _{CC} =MAX, R _L =2kΩ | Full range | 26 | | | |
| | | V _{CC} =MAX, R _L ≥10kΩ | Full range | 27 | 28 | | |
| V _{OL} | Low-level output voltage | R _L ≥10kΩ | Full range | 5 | 20 | mV | |

| Symbol | Parameter | Test Conditions* | | Min | Typ | Max | Unit |
|------------------------------------------------|----------------------------------------------------------------------|--------------------------------------------------------------------------|------------|-----|-----|-----|------|
| A _{VD} | Large-signal differential voltage amplification | V _{CC} =15V V _O =1V to 11V R _L ≥2kΩ | 25°C | 25 | 100 | | V/mV |
| | | | Full range | 15 | | | |
| CMRR | Common-mode rejection ratio | V _{CC} =5V to MAX V _{IC} =V _{ICR} min | 25°C | 65 | 80 | | dB |
| K _{SVR} | Supply voltage rejection ratio (ΔV _{CC} /ΔV _{IO}) | V _{CC} =5V to MAX | 25°C | 65 | 100 | | dB |
| V _{O1} /V _{O2} | Crosstalk attenuation | f=1kHz to 20kHz | 25°C | | 120 | | dB |
| I _O | Output current | V _{CC} =15V, V _{ID} =1V, V _O =0V | 25°C | -20 | -30 | | mA |
| | | | Full range | -10 | | | |
| | | V _{CC} =15V V _{ID} =-1V, V _O =15V | 25°C | 10 | 20 | | mA |
| | | | Full range | 5 | | | |
| V _{ID} =-1V, V _O =200mV | 25°C | 12 | 30 | | μA | | |


Electrical Characteristics (Continue)

| Symbol | Parameter | Test Conditions* | | Min | Typ | Max | Unit |
|-----------------|---------------------------------|-----------------------------------------------------------------------|------------|-----|-----|-----|------|
| I _{OS} | Short-circuit output current | V _{CC} at 5V, GND at -5V, V _O =0V | 25°C | | ±40 | ±60 | mA |
| I _{CC} | Supply current (two amplifiers) | V _O =2.5V, No load | Full range | | 1.5 | 3 | mA |
| | | V _{CC} =MAX, V _O =0.5V _{CC} , No load | Full range | | 0.7 | 1.2 | |


*All characteristics are measured under open-loop conditions with zero common-mode input voltage unless otherwise specified. "MAX" V_{CC} for testing Purposes is 30V. Full range is -40 °C to 85 °C.

Typical Performance Characteristics


Input Voltage Range




Input Current




Supply Current




Voltage Gain



Open Loop Frequency Response




Common Mode Rejection Ratio




Typical Performance Characteristics (Continue)


Voltage Follower Pulse Response




Voltage Follower Pulse Response (Small Signal)




Large Signal Frequency Response




Output Characteristics Current Sourcing



Output Characteristics Current Sinking




Current Limiting



Package Dimension

SOP-14 PLASTIC PACKAGE









| Dimensions | | | | |
|-------------------------|-------------|------|------------|------|
| SYMBOL | Millimeters | | Inches | |
| | MIN | MAX | MIN | MAX |
| A | 1.35 | 1.75 | .053 | .069 |
| A2 | 1.25 | 1.65 | .049 | .065 |
| b | 0.31 | 0.51 | .012 | .020 |
| b1 | 0.28 | 0.48 | .011 | .019 |
| c | 0.17 | 0.25 | .007 | .010 |
| A1 | 0.1(MAX) | | 0.004(MAX) | |
| D | 8.65 (TYP) | | .341 (TYP) | |
| E | 6.00 (TYP) | | .236 (TYP) | |
| E1 | 3.90 (TYP) | | .154 (TYP) | |
| e | 1.27 (TYP) | | .050 (TYP) | |
| L | 0.40 | 1.27 | .016 | .050 |
| L1 | 1.04 (TYP) | | .041 (TYP) | |
| L2 | 0.25 (TYP) | | .010 (TYP) | |
| R | 0.07 | - | .003 | - |
| R1 | 0.07 | - | .003 | - |
| h | 0.25 | 0.50 | .010 | .020 |
| θ | 0° | 8° | 0° | 8° |
| θ1 | 5° | 15° | 5° | 15° |
| θ2 | 0° | - | 0° | - |
| Lead Coplanarity | - | 0.1 | - | .004 |

NOTICE

Information furnished is believed to be accurate and reliable. However Globaltech Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Globaltech Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of Globaltech Semiconductor.

CONTACT US

| GS Headquarter | |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
|  | 4F.,No.43-1,Lane11,Sec.6,Minquan E.Rd Neihu District Taipei City 114, Taiwan (R.O.C) |
|  | 886-2-2657-9980 |
|  | 886-2-2657-3630 |
|  | sales_twn@gs-power.com |

| RD Division | |
|-------------------------------------------------------------------------------------|--------------------------------------|
|  | 824 Bolton Drive Milpitas. CA. 95035 |
|  | 1-408-457-0587 |