

# GS358

## Dual Operational Amplifiers

JAN. 2010

### Product Description

The GS358 consists of two independent, high gain, internally frequency compensated operational amplifiers which were designed specifically to operate from a single power supply over a wide range of voltages.


Operation from split power supplies is also possible and the low power supply current drains in independent of the magnitude of the power supply voltage.

Application areas include transducer amplifiers, dc gain blocks and all the conventional op amp circuits, which now can be more easily implemented in single power supply systems. For example, the GS358 can be directly operated off of the standard +5V power supply voltage which is used in digital systems and will easily provide the required interface electronics without requiring the additional  $\pm 15V$  power supplies.


### Features

- Wide range of supply voltages 3V to 30V
- Low supply current drain independent of supply voltage 0.7mA (TYP.)
- Low input biasing current
- Low input offset voltage and offset current
- Input common-mode voltage range includes ground
- Differential input voltage range equal to the power supply voltage
- DC voltage gain: 100V/mV TYP.
- Internally frequency compensation
- RoHS Compliant, 100%Pb & Halogen Free


### Block Diagram



## Pin Assignments




## Ordering Information



Device	Package
GS358PF	DIP-8
GS358SF	SOP-8

## Marking Information



## Absolute Maximum Ratings

Symbol	Parameter	Value		Unit
V <sub>CC</sub>	Single Supply	32		V
V <sub>CC</sub> , V <sub>EE</sub>	Split Supply	±16		V
V <sub>IDR</sub>	Input Differential Voltage Range	±32		V
I <sub>OS</sub>	Output Short-circuit to GND	Continuous		
T <sub>J</sub>	Junction Temperature	150		°C
T <sub>STG</sub>	Storage Temperature Range	-65 to +150		°C
T <sub>A</sub>	Operating Ambient Temperature Range	0 to 70		°C
θ <sub>JA</sub>	Thermal Resistance ( Junction to Ambient )	DIP-8	125	°C/W
		SOP-8	160	
θ <sub>JC</sub>	Thermal Resistance ( Junction to Case )	DIP-8	42	°C/W
		SOP-8	22	
ESD	ESD Rating (HBM)	2		KV

## Electrical Characteristics


at specified free-air temperature,  $V_{CC}=5V$  (Unless Otherwise Noted)

Symbol	Parameter	Test Conditions*	Min	Typ	Max	Unit	
$V_{IO}$	Input offset voltage	$V_{CC}=5V$ to Max. $V_{IC}=V_{ICR}$ min, $V_o = 1.4V$	25°C		3	7	mV
			Full range			9	
$\alpha V_{IO}$	Average temperature coefficient of input offset voltage		Full range		7		$\mu V/^\circ C$
$I_{IO}$	Input offset current	$V_o = 1.4V$	25°C		2	50	nA
			Full range			150	
$\alpha I_{IO}$	Average temperature coefficient of input offset current		Full range		10		$\mu A/^\circ C$
$I_{IB}$	Input bias current	$V_o = 1.4V$	25°C		-20	-250	nA
			Full range			-500	
$V_{ICR}$	Common-mode input voltage ange	$V_{CC} = 5V$ to MAX	25°C	0 to $V_{CC}-1.5$			V
			Full range	0 to $V_{CC}-2$			
$V_{OH}$	High-level output voltage	$R_L = 2k\Omega$	25°C	$V_{CC}-1.5$			V
		$V_{CC} = MAX,$ $R_L = 2k\Omega$	Full range	26			
		$V_{CC} = MAX,$ $R_L = 10k\Omega$	Full range	27	28		
$V_{OL}$	Low-level output voltage	$R_L = 10k\Omega$	Full range		5	20	mV
$A_{VD}$	Large-signal differential voltage amplification	$V_{CC} = 15V$ $V_o=1V$ to 11V $R_L=2k\Omega$	25°C	25	100		V/mV
			Full range	15			
CMRR	Common-mode rejection ratio	$V_{CC} = 5V$ to MAX $V_{IC} = V_{ICR}$ min	25°C	65	80		dB
$K_{SVR}$	Supply voltage rejection ratio ( $\Delta V_{CC}/\Delta V_{IO}$ )	$V_{CC} = 5V$ to MAX	25°C	65	100		dB
$V_{O1}/V_{O2}$	Crosstalk attenuation	$f = 1k$ to 20k (Hz)	25°C		120		dB
$I_o$	Output current	$V_{CC} = 15V,$ $V_{ID} = 1V,$ $V_o = 0V$	25°C	-20	-30		mA
			Full range	-10			
		$V_{CC} = 15V$ $V_{ID} = -1V,$ $V_o = 15V$	25°C	10	20		
			Full range	5			
$V_{ID} = -1V,$ $V_o = 200mV$	25°C	12	30		$\mu A$		
$I_{OS}$	Short-circuit output current	$V_{CC}$ at 5V, GND at -5V, $V_o = 0V$	25°C		$\pm 40$	$\pm 60$	mA
$I_{CC}$	Supply current (two amplifiers)	$V_o = 2.5V,$ No load	Full range		0.7	1.2	mA
		$V_{CC} = MAX,$ $V_o = 0.5V_{CC},$ No load	Full range		1	2	


\*All characteristics are measured under open-loop conditions with zero common-mode input voltage unless otherwise specified. "MAX"  $V_{CC}$  for testing Purposes is 30V. Full range is 0°C to 70°C

## Typical Performance Characteristics


### Input Voltage Range




### Input Current




### Supply Current




### Voltage Gain



### Open Loop Frequency Response




### Common Mode Rejection Ratio




## Typical Performance Characteristics (Continue)


### Voltage Follower Pulse Response




### Voltage Follower Pulse Response (Small Signal)




### Large Signal Frequency Response




### Output Characteristics Current Sourcing



### Output Characteristics Current Sinking




### Current Limiting




## Package Dimension

# SOP-8 PLASTIC PACKAGE



Dimensions				
SYMBOL	Millimeters		Inches	
	MIN	MAX	MIN	MAX
A	1.35	1.75	.053	.069
A1	0.10	0.25	.004	.010
A2	1.25	1.65	.049	.065
b	0.31	0.51	.012	.020
b1	0.28	0.48	.011	.019
c	0.17	0.25	.007	.010
D	4.90 (TYP)		.193 (TYP)	
E	6.00 (TYP)		.236 (TYP)	
E1	3.90 (TYP)		.154 (TYP)	
e	1.27 (TYP)		.050 (TYP)	
L	0.40	1.27	.016	.050
L1	1.04 (TYP)		.041 (TYP)	
L2	0.25 (TYP)		.010 (TYP)	
R	0.07	-	.003	-
R1	0.07	-	.003	-
h	0.25	0.50	.010	.020
$\theta$	0°	8°	0°	8°
$\theta_1$	5°	15°	5°	15°
$\theta_2$	0°	-	0°	-

# DIP-8 PLASTIC PACKAGE



## Dimensions





SYMBOL	Millimeters		Inches	
	MIN	MAX	MIN	MAX
A	-	5.33	-	.210
A1	0.38	-	.015	-
A2	2.92	4.95	.115	.195
b	0.36	0.56	.014	.022
b2	1.14	1.78	.045	.070
b3	0.76	1.14	.030	.045
c	0.20	0.36	.008	.014
D	9.02	10.16	.355	.400
D1	0.13	-	.005	-
E	7.62	8.26	.300	.325
E1	6.10	7.11	.240	.280
e	2.54 (TYP)		.100 (TYP)	
eA	7.62 (TYP)		.300 (TYP)	
eB	-	10.92	-	.430
eC	0.00	1.52	.000	.060
L	2.92	3.81	.115	.150
G	0.38 (TYP)		.015 (TYP)	







## NOTICE

Information furnished is believed to be accurate and reliable. However Globaltech Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Globaltech Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of Globaltech Semiconductor.



## CONTACT US

GS Headquarter	
	4F.,No.43-1,Lane11,Sec.6,Minquan E.Rd Neihu District Taipei City 114, Taiwan (R.O.C)
	886-2-2657-9980
	886-2-2657-3630
	sales_twn@gs-power.com

Wu-Xi Branch	
	No.21 Changjiang Rd., WND, Wuxi, Jiangsu, China (INFO. & TECH. Science Park Building A 210 Room)
	86-510-85217051
	86-510-85211238
	sales_cn@gs-power.com

RD Division	
	824 Bolton Drive Milpitas. CA. 95035
	1-408-457-0587