

GSM2319Y

20V P-Channel MOSFETs

Product Description

These P-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode.

These devices are well suited for high efficiency fast switching applications.


Features


- -20V, -400mA, $R_{DS(ON)}=600m\Omega@V_{GS}=-4.5V$
- Improved dv/dt capability
- Fast switching
- Suit for -1.5V Gate Drive Applications
- Green Device Available
- SOT-523 package design

Applications


- Notebook
- Load Switch
- Hand-Held Instruments
- Battery Protection

Packages & Pin Assignments


GSM2319YX7F (SOT-523)	
 Top Views	
Pin	Description
1	Gate
2	Source
3	Drain



Ordering Information



Marking Information



Part Number	Package	Part Marking	Quantity
GSM2319YX7F	SOT-523	FYM	3000pcs

Absolute Maximum Ratings

$T_C=25^{\circ}\text{C}$ Unless otherwise noted

Symbol	Parameter	Typical	Unit
V_{DS}	Drain-Source Voltage	-20	V
V_{GS}	Gate-Source Voltage	± 8	V
I_D	Continuous Drain Current	$T_C=25^{\circ}\text{C}$	mA
		$T_C=100^{\circ}\text{C}$	
I_{DM}	Pulsed Drain Current	-1.6	A
P_D	Power Dissipation ($T_C=25^{\circ}\text{C}$)	312	mW
	Power Dissipation (Derate above 25°C)	2.5	mW/ $^{\circ}\text{C}$
T_J	Operating Junction Temperature Range	-55 to +150	$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range	-55 to +150	$^{\circ}\text{C}$
$R_{\theta JA}$	Thermal Resistance-Junction to Ambient	400	$^{\circ}\text{C}/\text{W}$

Electrical Characteristics

T_J=25°C Unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static						
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =-250μA	-20			V
ΔBV _{DSS} /ΔT _J	BV _{DSS} Temperature Coefficient	Reference to 25°C, I _D =-1mA		-0.01		V/°C
V _{GS(th)}	Gate Threshold Voltage	V _{GS} =V _{DS} , I _D =-250μA	-0.3	-0.6	-1.0	V
ΔV _{GS(th)}	V _{GS(th)} Temperature Coefficient			3		mV/°C
I _{GSS}	Gate-Source Leakage Current	V _{DS} =0V, V _{GS} =±8V			±20	μA
I _{DSS}	Drain-Source Leakage Current	V _{DS} =-20V, V _{GS} =0V			-1	μA
		V _{DS} =-16V, V _{GS} =0V, T _J =125°C			-10	
I _S	Continuous Source Current	V _G =V _D =0V, Force Current			-0.4	A
I _{SM}	Pulsed Source Current				-0.8	
R _{DS(on)}	Static Drain-Source On-Resistance	V _{GS} =-4.5V, I _D =-0.3A		440	600	mΩ
		V _{GS} =-2.5V, I _D =-0.2A		610	850	
		V _{GS} =-1.8V, I _D =-0.1A		810	1200	
		V _{GS} =-1.5V, I _D =-0.1A		1020	1600	
		V _{GS} =-1.2V, I _D =-0.1A		1800	3000	
V _{SD}	Diode Forward Voltage	V _{GS} =0V, I _S =-0.2A			-1	V
Dynamic						
Q _g	Total Gate Charge	V _{DS} =-10V, V _{GS} =-4.5V, I _D =-0.2A		1	2	nC
Q _{gs}	Gate-Source Charge			0.28	0.5	
Q _{gd}	Gate-Drain Charge			0.18	0.4	
C _{iss}	Input Capacitance	V _{DS} =-10V, V _{GS} =0V, F=1MHz		40	78	pF
C _{oss}	Output Capacitance			15	30	
C _{rss}	Reverse Transfer Capacitance			6.5	13	
t _{d(on)}	Turn-On Delay Time	V _{DD} =-10V, I _D =-0.2A, V _{GS} =-4.5V, R _G =10Ω		8	16	ns
t _r	Rise Time			5.2	10	
t _{d(off)}	Turn-Off Delay Time			30	60	
t _f	Fall Time			18	36	

Typical Performance Characteristics




Fig.1 Continuous Drain Current vs. T_C




Fig.2 Normalized $R_{DS(on)}$ vs. T_J




Fig.3 Normalized V_{th} vs. T_J




Fig.4 Gate Charge Waveform




Fig.5 Normalized Transient Response








Fig.6 Maximum Safe Operation Area

Typical Performance Characteristics (Continue)



Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms




Diode Recovery Test Circuit & Waveforms



Package Dimension

SOT-523



Dimensions				
Symbol	Millimeters		Inches	
	Min	Max	Min	Max
A	0.700	0.900	0.028	0.035
A1	0.000	0.100	0.000	0.004
A2	0.700	0.800	0.028	0.031
b	0.250	0.350	0.010	0.014
b1	0.150	0.250	0.006	0.010
c	0.100	0.200	0.004	0.008
D	1.500	1.750	0.059	0.069
E	0.700	0.900	0.028	0.035
E1	1.400	1.750	0.055	0.069
e	0.5TYP		0.02TYP	
e1	0.900	1.100	0.035	0.043
L	0.300	0.460	0.012	0.018
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8

NOTICE

Information furnished is believed to be accurate and reliable. However Globaltech Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Globaltech Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of Globaltech Semiconductor.

CONTACT US

GS Headquarter	
	4F.,No.43-1,Lane11,Sec.6,Minquan E.Rd NeiHu District Taipei City 114, Taiwan (R.O.C)
	886-2-2657-9980
	886-2-2657-3630
	sales_twn@gs-power.com

Shenzhen Branch(China)	
	1113 B Building, Happiness Washington, Baoan Nan Road, Luohu District, Shenzhen City, China
	0755-22208941
	sales_cn@gs-power.com

RD Division	
	824 Bolton Drive Milpitas. CA. 95035
	1-408-457-0587