

GSMDL6912

60V N-Channel MOSFETs

Product Description

These N-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode.

These devices are well suited for high efficiency fast switching applications.


Features


- 60V, 5A, $R_{DS(ON)}=90m\Omega@V_{GS}=10V$
- Improved dv/dt capability
- Fast switching
- 100% EAS guaranteed
- Green Device Available
- SOT-223 package design

Applications


- Motor Drive
- Power Tools
- LED Lighting

Packages & Pin Assignments


GSMDL6912XF (SOT-223)	
TAB 	
Pin	Description
1	Gate
2	Drain
3	Source



Ordering Information



Marking Information



Part Number	Package	Quantity
GSMDL6912XF	SOT-223	2500pcs

Absolute Maximum Ratings

T_A=25°C Unless otherwise noted

A 25 °C unless otherwise noted				
Symbol	Parameter		Typical	Unit
V _{DS}	Drain-Source Voltage		60	V
V _{GS}	Gate –Source Voltage		±20	V
I _D	Continuous Drain Current	T _A =25°C	5	A
		T _A =100°C	3.2	
I _{DM}	Pulsed Drain Current		20	A
EAS	Single Pulse Avalanche Energy		25	mJ
IAS	Single Pulse Avalanche Current		7	A
P _D	Power Dissipation (T _A =25°C)		1.79	W
	Power Dissipation (Derate above 25°C)		0.014	W/°C
T _J	Operating Junction Temperature Range		-50 to +150	°C
T _{STG}	Storage Temperature Range		-50 to +150	°C
R _{θJA}	Thermal Resistance-Junction to Ambient		70	°C/W
R _{θJC}	Thermal Resistance-Junction to Case		30	°C/W

Electrical Characteristics

T_A=25°C Unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static						
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V,I _D =250uA	60			V
△BV _{DSS} /△T _J	BV _{DSS} Temperature Coefficient	Reference to 25℃, I _D =1mA		0.05		V/℃
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} ,I _D =250uA	1.2	1.8	2.5	V
△V _{GS(th)}	V _{GS(th)} Temperature Coefficient			-5		mV/℃
I _{GSS}	Gate Leakage Current	V _{DS} =0V,V _{GS} =±20V			±100	nA
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =60V,V _{GS} =0V			1	uA
		V _{DS} =48V,V _{GS} =0V, T _J =125℃			10	
I _S	Continuous Source Current	V _G =V _D =0V, Force Current			5	A
I _{SM}	Pulsed Source Current				20	
R _{DS(on)}	Drain-Source On-Resistance	V _{GS} =10V,I _D =5A		76	90	mΩ
		V _{GS} =4.5V,I _D =3A		87	100	
g _{FS}	Forward Transconductance	V _{DS} =10V,I _D =3A		7		S
V _{SD}	Diode Forward Voltage	V _{GS} =0V,I _S =1A			1	V
t _{rr}	Reverse Recovery Time	V _{GS} =30V,I _S =1A, di/dt=100A/us		23.2		ns
Q _{rr}	Reverse Recovery Charge			14.3		nC
Dynamic						
Q _g	Total Gate Charge	V _{DS} =48V,V _{GS} =10V, I _D =5A		9.3	14	nC
Q _{gs}	Gate-Source Charge			2.1	4	
Q _{gd}	Gate-Drain Charge			1.8	4	
C _{iSS}	Input Capacitance	V _{DS} =15V,V _{GS} =0V, f=1MHz		500	725	pF
C _{oSS}	Output Capacitance			45	65	
C _{rSS}	Reverse Transfer Capacitance			16	30	
t _{d(on)}	Turn-On Time	V _{DD} =30V,I _D =1A, V _{GS} =10V,R _G =3.3Ω		2.9	6	ns
t _r				9.5	18	
t _{d(off)}	Turn-Off Time			18.4	35	
t _f				5.3	10	
R _g	Gate Resistance	V _{DS} =0V,V _{GS} =0V, f=1MHz		2	4	Ω

Typical Performance Characteristics




Fig.1 Output Characteristics




Fig.2 Continuous Drain Current vs. T_C




Fig.3 Normalized $R_{DS(on)}$ vs. T_J




Fig.4 Normalized V_{th} vs. T_J




Fig.5 Gate Charge Waveform






Fig.6 Capacitance Characteristics

Typical Performance Characteristics (Continue)


Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms




Unclamped Inductive Switching Test Circuit & Waveforms



Package Dimension

SOT-223



Dimensions				
Symbol	Millimeters		Inches	
	Min	Max	Min	Max
A	1.520	1.800	0.060	0.071
A1	0.000	0.100	0.000	0.004
A2	1.500	1.700	0.059	0.067
b	0.660	0.820	0.026	0.032
c	0.250	0.350	0.010	0.014
D	6.200	6.400	0.244	0.252
D1	2.900	3.100	0.114	0.122
E	3.300	3.700	0.130	0.146
E1	6.830	7.070	0.269	0.278
e	2.300 (BSC)		0.091 (BSC)	
e1	4.500	4.700	0.177	0.185
L	0.900	1.150	0.035	0.045
θ	0°	10°	0°	10°

NOTICE

Information furnished is believed to be accurate and reliable. However Globaltech Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Globaltech Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of Globaltech Semiconductor.

CONTACT US

GS Headquarter	
	4F.,No.43-1,Lane11,Sec.6,Minquan E.Rd NeiHu District Taipei City 114, Taiwan (R.O.C)
	886-2-2657-9980
	886-2-2657-3630
	sales_twn@gs-power.com

Shenzhen Branch(China)	
	1113 B Building, Happiness Washington, Baoan Nan Road, Luohu District, Shenzhen City, China
	0755-22208941
	sales_cn@gs-power.com

RD Division	
	824 Bolton Drive Milpitas. CA. 95035
	1-408-457-0587