


Features

- High Breakdown Voltage
- Low Saturation Voltage
- RoHS Compliant

1. Emitter
2. Base
3. Collector



SOT-23

Applications

- High Voltage Control Circuits

Absolute Maximum Ratings

(T_A=25°C unless otherwise specified)

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V _{CBO}	500	V
Collector to Emitter Voltage	V _{CEO}	400	V
Emitter to Base Voltage	V _{EBO}	6.0	V
Collector Current	I _C	300	mA
Collector Power Dissipation	P _C	350	mW
Collector Power Dissipation	P _{C(TC=25°C)}	1.5	W
Junction Temperature	T _J	-55 to +150	°C
Storage Temperature Range	T _{STG}	-55 to +150	°C

Thermal Characteristics







Parameter	Symbol	Typ.	Max.	Unit
Thermal Resistance Junction to Ambient	R _{θJA}	---	357	°C/W

Electrical Characteristics


($T_A=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Emitter Breakdown Voltage	V_{CEO}	$I_C=100\mu\text{A}$ $I_E=0$	500	--	--	V
Collector to Base Breakdown Voltage	V_{CBO}	$I_C=1.0\text{mA}$ $I_B=0$	400	--	--	V
Emitter to Base Breakdown Voltage	V_{EBO}	$I_E=10\mu\text{A}$ $I_C=0$	6.0	--	--	V
Collector Cut-Off Current	I_{CBO}	$V_{CB}=400\text{V}$ $I_E=0$	--	--	0.1	μA
Collector Cut-Off Current	I_{CEO}	$V_{CE}=400\text{V}$ $V_{BE}=0$	--	--	0.5	μA
Emitter Cut-Off Current	I_{EBO}	$V_{CE}=4.0\text{V}$ $I_C=0$	--	--	0.1	μA
Forward Current Transfer Ratio(1)	$h_{FE(1)}$	$V_{CE}=10\text{V}$ $I_C=10\text{mA}$	50	--	200	
Forward Current Transfer Ratio(2)	$h_{FE(2)}$	$V_{CE}=10\text{V}$ $I_C=100\text{mA}$	40	--	--	
Forward Current Transfer Ratio(3)	$h_{FE(3)}$	$V_{CE}=10\text{V}$ $I_C=50\text{mA}$	45	--	--	
Forward Current Transfer Ratio(4)	$h_{FE(4)}$	$V_{CE}=10\text{V}$ $I_C=1.0\text{mA}$	40	--	--	
Collector-Emitter Saturation Voltage(1)	$V_{CE(sat)(1)}$	$I_C=1.0\text{mA}$ $I_B=0.1\text{mA}$	--	--	0.4	V
Collector-Emitter Saturation Voltage(2)	$V_{CE(sat)(2)}$	$I_C=10\text{mA}$ $I_B=1.0\text{mA}$	--	--	0.5	V
Collector-Emitter Saturation Voltage(3)	$V_{CE(sat)(3)}$	$I_C=50\text{mA}$ $I_B=5.0\text{mA}$	--	--	0.75	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C=10\text{mA}$ $I_B=1.0\text{mA}$	--	--	0.75	V
Output Capacitance	C_{ob}	$V_{CB}=20\text{V}$ $I_E=0$ $f=1.0\text{MHz}$	--	--	7.0	pF

Typical Characteristic Curves



Package Outline Dimensions



Symbol	Dimensions In Millimeters		Symbol	Dimensions In Millimeters	
	Min	Max		Min	Max
L	2.2	2.7	C	1.30	Max
L1	0.45	0.65	C1	0.90	1.20
A	1.15	1.50	c	0.05	0.20
B	2.70	3.10	K	0	0.10
E	1.70	2.10	M	0.20	MIN
E1	0.85	1.05	P	7	
b	0.35	0.55			