

SPECIFICATION FOR LCD MODULE

**Model No. GVLCM240320G-13705A (TFT)
(2.4" TFT)**

Approved	Checked	Department

CONTENTS

	Page
1.General Specifications -----	3
2.Outline Drawing -----	4
3.Absolute Maximum Ratings -----	5
4.Electrical Characteristics -----	5
5.Module Function Description -----	5
5-1.InterFace Signal -----	6
5-2.Interface Timing Chart -----	6
5-3.Instruction Code -----	8
6.Electro-Optical Characteristics -----	11
7.Lightguide Specification -----	14
8. Reliability -----	15
8-1.MTBF-----	15
8-2.Content Of Reliability Test -----	15
9.Inspection Criteria -----	15

1. General Specifications:

1.1. FEATURES

Display Mode	Transmissive and Negative type
	TFT
Display Format	Graphic 240 (RGB)* 320 Dot-matrix (262K Color)
Viewing Direction	12:00 O'clock
Multiplexing Ratio	1/320 Duty
Screen size(inch)	2.4(Diagonal)
Controller	UC8230S
Data Transfer	16 BITS 8080 PARALLEL INTERFACE
VDD	2.8~3.3V



1-2. MECHANICAL SPECIFICATION

Item	Specifcation	Unit
Viewing Area	37.72(W)x54.4(H)	mm
Active Area	36.72(W)x50.06(H)	mm
Dots pitch	0.153(H)X0. 153 (W)	mm
Outline Dimensional	40.7(W)x57.1(H)x2.75(D) Refer to outline drawing on next page	mm
Blacklight type	White LED*4	—
VLED	3.0V(typ.)	V

*Exclude FPC outline

2. Outline Drawing

APPROVED BY:



NO.	ITEM	NO.	ITEM
1	NC	19	DB9
2	NC	20	DB8
3	NC	21	DB7
4	IM3	22	DB6
5	NC	23	DB5
6	RESET	24	DB4
7	VSYNC	25	DB3
8	HSYNC	26	DB2
9	DOTCLK	27	DB1
10	DEN	28	DB0
11	DB17	29	RD
12	DB16	30	WR
13	DB15	31	DC
14	DB14	32	CS
15	DB13	33	GND
16	DB12	34	VCC
17	DB11	35	LED_K
18	DB10	36	LED_A

LCD TYPE	TFP	BACKLIGHT COLOR	WHITE
POLARIZER TYPE	TRANSMISSIVE	FRAME TYPE	
DISPLAY TYPE	NEGATIVE	DATA TRANSFER	16bit 8080
LCD COLOR		CONNECTOR TYPE	FPC
VIEWING ANGLE	12:00	TECHNOLOGY	COG
OPERATING TEMP	-20°C ~ +70°C	DC-DC IC	Without
STORAGE TEMP	-30°C ~ +80°C	LCD DUTY	1/320
BACKLIGHT TYPE	Pdga LED	LCD BIAS	
CONTROLLER IC	UC8230S	ROHS	

GOLDEN VIEW

PRODUCT NO.	GVLCM240320G-13705A		
DRAWN BY	ZCS	SCALE	1:1
CHECKED BY	lzy	PAGE	1/1
DATE	2009-03-16	UNTT	mm

Ver	Date	Modify Contents

3. Absolute Maximum Ratings ($T_a=25^{\circ}\text{C}$)

Item	Symbol	Min	Max	Unit	Note
Supply voltage	Vdd	-0.3	4.6	V	1,2
Supply voltage (Logic)	VDDI	-0.3	4.6	V	
Supply voltage (Digital)	VCC	-0.3	2.4	V	
Driver supply Voltage	VGH- VGL	-0.3	33	V	
Input Voltage	Vin	-0.3	VddI+0.3	V	
Logic Output voltage range	VO	-0.3	VddI+0.3	V	
Operating temperature	Topr	-20	70	$^{\circ}\text{C}$	
Storage temperature	Tstr	-30	80	$^{\circ}\text{C}$	
Humidity	-	-	90	%RH	

Note:

1. If the module is above these absolute maximum ratings. It may become permanently damaged.
Using the module within the following electrical characteristic conditions are also exceeded,
the module will malfunction and cause poor reliability.
2. VDD > VSS must be maintained.

4. Electrical Characteristics ($T_a=25^{\circ}\text{C}$)

Item		Symbol	Min	Typ	Max	Unit	Note
Input Voltage (VDD=2.8V)	'H'	Vih	0.8Vdd	-	Vdd	V	
	'L'	Vil	Vss	-	0.2Vdd		
Output Voltage (VDD=2.8V)	'H'	Vih	0.8Vdd	-	Vdd	V	
	'L'	Vil	Vss	-	0.2Vdd		
Current Consumption		Normal Mode	-	25.5	-	mA	1,3
		Partial Mode	-	TBD	TBD	uA	2

Note:

- 1: Display full white. Backlight on state.
- 2: IC on standby mode.
- 3: the default voltage is 2.8V, for N lights in series, the power is that the current multiply N.

5. Module Function Description


5-1. Interface Signal

Pin No.	Symbol	Level	Description
1-3,5	NC	—	No connection
4	IM3	I	NC (Connected to GND interal)
6	RESET	I	Reset input pin
7	VSYNC	I	Frame synchronization signal
8	HSYNC		Line synchronization signal
9	DOTCLK		DOT clock
10	DEN		Enable signal in RGB mode
11-28	D17-D0		Data bus
29	RD	I	Read/write control pin
30	WR	I	Read/write execution control pin
31	DC	I	Register selection input pin
32	/CS	I	Chip select input pins
33	VSS	0V	Ground
34	VDD	3.3V	Power supply voltage for logic
35	LED_K	—	Back light-
36	LED_A	—	Back light+

5-2. Interface Timing Chart

Inter 80 system CPU interfac

GOLDEN-VIEW



(1.65V ≤ V_{DD} < 2.5V, T_a = -30 to +85°C)

Symbol	Signal	Description	Condition	Min.	Max.	Units
t _{CYCW}	WR	Bus cycle time Write		200	-	nS
t _{CYCR}	RD	Bus cycle time Read		400	-	nS
PW _{LW}	WR	Write low-level pulse width		90	-	nS
PW _{LR}	RD	Read low-level pulse width		350	-	nS
PW _{HW}	WR	Write high-level pulse width		90	-	nS
PW _{HR}	RD	Read high-level pulse width		400	-	nS
t _{WRr} , t _{WRf}	WR, RD	Write/Read rise/fall time			25	nS
t _{AS}	RS to CS, WR, RD	Set up time		10	-	nS
t _{AH}	RS to CS, WR, RD	Address hold time		5	-	nS
t _{DSW}	WR	Write data set up time		5	-	nS
t _{HWR}	RD	Write data hold time		60	-	nS
t _{DDR}	WR	Read data delay time		-	200	nS
t _{DHR}	RD	Read data hold time		5	-	nS

5-3. Instruction Code

GOLDEN-VIEW

Command	Reg.	R/W	RS	D15	D14	D13	D12	D11	D10	D9	D8	D7	D6	D5	D4	D3	D2	D1	D0	Default	
1. Index	IR	W	0	0	0	0	0	0	0	0	0	ID[7:0]									
2. Status	SR	R	0	0	0	0	0	0	0	0	0	0	TE	MTPS	0	0	0	0	0		
3. Set Display Enable	R00H	W	1	0	0	0	0	0	0	0	0	0	0	0	0	0	AOF	MAN	OS		
4. Device Code Read		R	1	1	0	0	0	0	0	1	0	0	0	1	1	0	0	0	0		
5. Drive Output Control	R01H	W	1	0	0	0	0	0	0	SM	SS	0	0	0	0	0	0	0	0	0000H	
6. LCD Drive Waveform Control	R02H	W	1	0	0	0	0	0	1	BC0	EOR	0	0	0	0	0	0	0	0	0400H	
7. Entry Mode	R03H	W	1	TRI	DFM	0	BGR	0	0	0	0	ORG	0	ID1	ID0	AM	0	0	0	0030H	
8. Resize Control	R04H	W	1	0	0	0	0	0	0	0	RCV[1:0]	0	0	RCH[1:0]		0	0	RSZ[1:0]	0	0000H	
9. Display Control (1)	R07H	W	1	0	0	PTDE[1:0]		0	0	0	BASE E	0	VON	GON	DTE	COL	0	D1	D0		
10. Display Control (2)	R08H	W	1	0	0	0	0	FP[3:0]			0	0	0	0	BP[3:0]				0808H		
11. Display Control (3)	R09H	W	1	0	0	0	0	0	0	PTS[1:0]	0	0	PTG[1:0]		ISC[3:0]				0000H		
12. Display Control (4)	R0AH	W	1	0	0	0	0	0	0	0	0	0	0	0	0	FMAR KOE	FMI[2:0]				
13. Ext. Display Interface Ctl 1	R0CH	W	1	0	ENC[2:0]			0	0	0	0	0	0	0	DM[1:0]	0	0	0	RIM[1:0]	0000H	
14. Frame Marker Control	R0DH	W	1	0	0	0	0	0	0	0	0	FMP[8:0]								0000H	
15. Ext. Display Interface Ctl 2	R0FH	W	1	0	0	0	0	0	0	0	0	0	0	VSPL	HSP	0	EPL	DPL	0000H		
Power Control (1)	R10H	W	1	0	0	0	SAP	BT[2:0]			APE	0	AP[1:0]	0	DSTB	SLP	0	0	0000H		
Power Control (2)	R11H	W	1	0	0	0	0	0	0	DC1[1:0]	0	0	0	DC0[1:0]	0	VC[2:0]			0000H		
Power Control (3)	R12H	W	1	PSV MD	0	0	0	0	PDC4	PDC2	PDC	1	PON 4	PON2	PON1	VRH[3:0]			00F0H		
Power Control (4)	R13H	W	1	0	0	VDV[5:0]					0	0	VCM[5:0]								
17. Setting Disable	R17H	W	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	PSE		
18. RAM Address Set - Horizontal	R20H	W	1	0	0	0	0	0	0	0	0	AD[7:0]									
19. RAM Address Set - Vertical	R21H	W	1	0	0	0	0	0	0	0	0	AD[16:8]									
20. RAM Data Write / Read	R22H	W R	1	WR17-0 RD17-0																	
y- Control (1)	R30H	W	1	0	0	0	0	0	PKP1[2:0]			0	0	0	0	0	PKP0[2:0]			00H	
y- Control (2)	R31H	W	1	0	0	0	0	0	PKP3[2:0]			0	0	0	0	0	PKP2[2:0]			00H	
y- Control (3)	R32H	W	1	0	0	0	0	0	PKP5[2:0]			0	0	0	0	0	PKP4[2:0]			00H	
y- Control (4)	R33H	W	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	00H		
y- Control (5)	R34H	W	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	00H		
y- Control (6)	R35H	W	1	0	0	0	0	0	PRP1[2:0]			0	0	0	0	PRP0[2:0]			00H		
y- Control (7)	R36H	W	1	0	0	0	0	VRP1[4:0]				0	0	VRP0[4:0]				00H			
y- Control (8)	R37H	W	1	0	0	0	0	0	PKN1[2:0]			0	0	0	0	PKN0[2:0]			00H		
y- Control (9)	R38H	W	1	0	0	0	0	0	PKN3[2:0]			0	0	0	0	PKN2[2:0]			00H		
y- Control (10)	R39H	W	1	0	0	0	0	0	PKN5[2:0]			0	0	0	0	PKN4[2:0]			00H		
y- Control (11)	R3AH	W	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	00H		
y- Control (12)	R3BH	W	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	00H		
y- Control (13)	R3CH	W	1	0	0	0	0	0	PRN1[2:0]			0	0	0	0	PRN0[2:0]			00H		
y- Control (14)	R3DH	W	1	0	0	0	0	VRN1[4:0]				0	0	VRN0[4:0]				00H			
22. Checksum Control	R41H	W	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	DAE	IRE	0000H	
23. IR Checksum	R42H	W	1	0	0	0	0	0	0	0	0	IRCK[7:0]								0000H	
24. DT Checksum	R43H	W	1	DACK[15:0]																	0000H
25. Windows Horizontal Start Addr.	R50H	W	1	0	0	0	0	0	0	0	0	HSA[7:0]									
26. Windows Horizontal End Addr.	R51H	W	1	0	0	0	0	0	0	0	0	HEA[7:0]									
27. Windows Vertical Start Addr.	R52H	W	1	0	0	0	0	0	0	0	0	VSA[8:0]									
28. Windows Vertical End Addr.	R53H	W	1	0	0	0	0	0	0	0	0	VEA[8:0]									
29. Driver Output Control	R60H	W	1	GS	0	NL[5:0]					0	0	SCN[5:0]								
30. Base Image Display Control	R61H	W	1	0	0	0	0	0	0	0	0	0	0	0	0	NDL	VLE	REV			
31. Vertical Scroll Control	R6AH	W	1	0	0	0	0	0	0	0	0	VL[8:0]									
32. Partial Image 1 Display Position	R80H	W	1	0	0	0	0	0	0	0	0	PTDP0[8:0]									
33. Partial Image 1 Start RAM Addr.	R81H	W	1	0	0	0	0	0	0	0	0	PTSA0[8:0]									
34. Partial Image 1 End RAM Addr.	R82H	W	1	0	0	0	0	0	0	0	0	PTEA0[8:0]									
35. Partial Image 2 Display Position	R83H	W	1	0	0	0	0	0	0	0	0	PTDP1[8:0]									
36. Partial Image 2 Start RAM Addr.	R84H	W	1	0	0	0	0	0	0	0	0	PTSA1[8:0]									
37. Partial Image 2 End RAM Addr.	R85H	W	1	0	0	0	0	0	0	0	0	PTEA1[8:0]									
Panel Interface Control 1	R90H	W	1	0	0	0	0	0	0	DIV[1:0]	0	0	0	RTNI[4:0]							
Panel Interface Control 2	R92H	W	1	0	0	0	0	0	NOWI[2:0]			0	0	0	0	0	0	0			
Panel Interface Control 3	R93H	W	1	0	0	0	0	0	0	0	0	0	0	0	MCPJ[2:0]						
Panel Interface Control 4	R95H	W	1	0	0	0	0	0	0	DIVE[1:0]	0	0	RTNE[5:0]								
Panel Interface Control 5	R97H	W	1	0	0	0	0	NOWE[3:0]			0	0	0	0	0	0	0	0			
Panel Interface Control 6	R98H	W	1	0	0	0	0	0	0	0	0	0	0	0	0	MCPE[2:0]					
39. Calibration Control	RA4H	W	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	CALB		

Command	Reg.	R/W	RS	D15	D14	D13	D12	D11	D10	D9	D8	D7	D6	D5	D4	D3	D2	D1	D0	Default		
40. MTP Register	R46H	W	1	--	--	--	--	--	--	--	MAT CH	--	--	MP1	MP0	--	--	MTPig n	MTP_ EN			
41. MTP Timer	RC9H	W	1	WRTIMER											RDTIMER							
42. MTP Cell	RCAH	W	1	MTPID [1:0]	MVDV[5:0]						--	--	--	MVCM[5:0]								

6. Electro-Optical Characteristics

Item	Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Brightness	Bp	$\theta=0^\circ$	-	200	-	Cd/m ²	1
Uniformity	ΔBp	$\Phi=0^\circ$	80%	-	-		1,2
Viewing Angle	θ_1 ($\Phi=90^\circ$ or 270°)	Cr \geq 10	-27~+60			Deg	3
	θ_2 ($\Phi=0^\circ$ or 180 $^\circ$)						
Contrast Ratio	Cr	$\theta=0^\circ$ $\Phi=0^\circ$		301.5		-	4
Response Time	t _{on}		-	15	30	ms	5
	t _{off}	-	35	50	ms		
Color of CIE Coordinate	W	x	-	-	-	-	1,6
		y	-	-	-	-	
	R	x	-	-	-	-	
		y	-	-	-	-	
	G	x	-	-	-	-	
		y	-	-	-	-	
	B	x	-	-	-	-	
		y	-	-	-	-	
NTSC Ratio	S	60.5%	-				


Note: The parameter is slightly changed by temperature, driving voltage and materiel.

Note 1: The data are measured after LEDs are turned on for 5 minutes. LCM displays full white.

The brightness is the average value of 9 measured spots. Measurement equipment PR-705 ($\Phi 8\text{mm}$)

Measuring condition:

- Measuring surroundings: Dark room.
 - Measuring temperature: $T_a=25^{\circ}\text{C}$.
 - Adjust operating voltage to get optimum contrast at the center of the display.
- Measured value at the center point of LCD panel after more than 5 minutes while backlight turning on.




Note 2: The luminance uniformity is calculated by using following formula.

$$\Delta B_p = B_p (\text{Min.}) / B_p (\text{Max.}) \times 100 (\%)$$

$B_p (\text{Max.})$ = Maximum brightness in 9 measured spots


$B_p (\text{Min.})$ = Minimum brightness in 9 measured spots.



Measurement equipment PR-705 ($\Phi 8\text{mm}$)

Note 3: The definition of viewing angle:

Refer to the graph below marked by θ and Φ



Note 4: The definition of contrast ratio (Test LCM using PR-705):

Luminance When LCD is at “White” state

Contrast Ratio(CR)=

Luminance When LCD is at “Black” state


(Contrast Ratio is measured in optimum common electrode voltage)

Note 5: Definition of Response time. (Test LCD using DMS501):

The output signals of photo detector are measured when the input signals are changed


from “black” to “white”(falling time) and from “white” to “black”(rising time), respectively. The

response time is defined as the time interval between the 10% and 90% of amplitudes. Refer to figure as below.



The definition of response time


Note 6: Definition of Color of CIE Coordinate and NTSC Ratio.



Color gamut:

$$S = \frac{\text{area of RGB triangle}}{\text{area of NTSC triangle}} \times 100\%$$

7. Lightguide specification



Item	Symbol	Min	Typ	Max	Unit	Condition
Forward voltage	Vf	-	3.3	3.4	V	If=60mA
Forward Current	If	-	60	-	mA	
Luminance	Master Screen	Lv	2000	2500	-	Cd/m ² If=30mA

Colour coordinate	X	0.260		0.315	If=30mA
	Y	0.260		0.315	

Note:

1. Average Luminous Intensity of P1 ~ P9
2. Luminous Uniformity = (MIN / MAX) * 100%
3. Luminous Uniformity required $\geq 80\%$

8. Reliability

8-1.MTBF

The LCD module shall be designed to meet a minimum MTTF value of 50000 hours with normal. (25°C in the room without sunlight)

8-2. Content of Reliability Test

NO.	Test Item	Content of Test	Condition
1	High Temperature Storage	Endurance test applying the high temperature for a long time	+80°C, 96H
2	Low Temperature Storage	Endurance test applying the low temperature for a long time	-30°C, 96H
3	High Temperature/Humidity Storage	Endurance test applying the high temperature and high humidity for a long time	60°C, 90% RH, 96H
4	Heat Shock	Endurance test applying The low and high temperature cycles -20°C ↔ 25°C ↔ +70°C (30min) ↔ (5min) ↔ (30min) 1 Cycle	-20°C / +70°C 5 cycle

Note: Test after 2 hours in room temperature.

9. Inspection Criteria

9-1. Environmental conditions

The environmental conditions for inspection shall be as follows

Room temperature: 20±3°C

Humidity: 65±20%RH

9-2.The external visual inspection

With a single 20-watt fluorescent lamp as the light source, the inspection was in the distance of 30cm or more from the LCD to the inspector's eyes.