

Schottky Barrier Rectifiers

GVS23-V--GVS24-V

Features

- Metal silicon junction, majority carrier conduction
- High surge capability
- High temperature soldering guaranteed:
260°C/10 seconds
- High current capability, low forward voltage drop
- Guarding for over voltage protection
- RoHS Compliant



Mechanical Data

- Case: SMB molded plastic
- Molding compound, UL flammability classification rating 94V-0
- Terminals: Matte tin plated leads, solderable per J-STD-002 and JESD22-B102
- Polarity: Color band denotes cathode end

Maximum Ratings (@T_A = 25°C unless otherwise specified)

Characteristic	Symbol	GVS23-V	GVS24-V	Units
Peak repetitive reverse voltage	V _{RRM}	30	40	V
RMS reverse voltage	V _{RMS}	21	28	V
DC blocking voltage	V _{DC}	30	40	V
Maximum average forward output current	I _{F(AV)}	2.0		A
Peak forward surge current, 8.3ms single half-sine-wave	I _{FSM}	40		A

Thermal Characteristics

Parameter	Symbol	GVS23-V	GVS24-V	Units
Typical thermal resistance (Note 1)	R _{ΘJA}	60		°C /W
	R _{ΘJC}	23		
	R _{ΘJL}	25		
Operating junction temperature range	T _J	- 55 ---- + 125		°C
Storage temperature range	T _{STG}	- 55 ---- + 150		°C

Note:

1. Device mounted on PCB with 10 mm x 20 mm x 0.1mm copper pad areas

Schottky Barrier Rectifiers**GVS23-V--GVS24-V****Electrical Characteristics**(@T_A = 25°C unless otherwise specified)

Parameter	Symbol	Testconditions		Typ.	Max.	Units
Maximum instantaneous forward voltage(Note 1)	V _F	I _F =2.0A	@T _A =25°C	--	0.40	V
Maximum Reversecurrent (Note2)	I _R	Rated V _R ,	@T _J =25°C	--	500	μ A
			@T _J =100°C	--	40	m A

Note:

1.Pulse test: 300us pulse width, 1 % duty cycle

2.Pulse test: Pulse width40ms

Schottky Barrier Rectifiers

GVS23-V--GVS24-V

Ratings and Characteristic Curves ($T_A=25^\circ\text{C}$ unless otherwise noted)

Fig.1-Forward Current Derating Curve




Fig.2- Surge Current Derating Curve




Fig.3- Typical Forward Voltage Characteristic






Fig.4- Typical Reverse Characteristic




Schottky Barrier Rectifiers

GVS23-V--GVS24-V

Package Outline Dimensions(unit:mm)



Mounting Pad Layout(unit:mm)



Ordering Information

Part No.	Marking	Package	Shipping
GVS23-V	VS23	SMB	3000/Tape&Reel
GVS24-V	VS24	SMB	3000/Tape&Reel