

Schottky Barrier Rectifiers

GVS34B-V--GVS345B-V

Features

- Metal silicon junction, majority carrier conduction
- High surge capability
- High temperature soldering guaranteed:
260°C/10 seconds
- High current capability, low forward voltage drop
- Guarding for over voltage protection
- RoHS Compliant



Mechanical Data

- Case: SMB molded plastic
- Molding compound, UL flammability classification rating 94V-0
- Terminals: Matte tin plated leads, solderable per J-STD-002 and JESD22-B102
- Polarity: Color band denotes cathode end

Maximum Ratings (@T_A = 25°C unless otherwise specified)

Characteristic	Symbol	GVS34B-V	GVS345B-V	Units
Peak repetitive reverse voltage	V _{RRM}	40	45	V
RMS reverse voltage	V _{RMS}	28	31.5	V
DC blocking voltage	V _{DC}	40	45	V
Maximum average forward output current	I _{F(AV)}	3.0		A
Peak forward surge current, 8.3ms single half-sine-wave	I _{FSM}	80		A

Thermal Characteristics

Parameter	Symbol	GVS34B-V	GVS345B-V	Units
Typical thermal resistance (Note 1)	R _{ΘJA}	60		°C /W
	R _{ΘJC}	23		
	R _{ΘJL}	25		
Operating junction temperature range	T _J	- 55 ---- + 150		°C
Storage temperature range	T _{STG}	- 55 ---- + 150		°C

Note:

1. Device mounted on PCB with 10 mm x 20 mm x 0.1mm copper pad areas

Schottky Barrier Rectifiers**GVS34B-V--GVS345B-V****Electrical Characteristics** (@ $T_A = 25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test conditions		Typ.	Max.	Units
Maximum instantaneous forward voltage(Note 1)	V_F	$I_F=3.0\text{A}$	@ $T_A=25^{\circ}\text{C}$	--	0.40	V
Maximum Reverse current (Note 2)	I_R	Rated V_R ,	@ $T_J=25^{\circ}\text{C}$	--	500	μA
			@ $T_J=100^{\circ}\text{C}$	--	40	m A

Note:


1.Pulse test: 300us pulse width, 1 % duty cycle

2.Pulse test: Pulse width 40ms


Schottky Barrier Rectifiers

GVS34B-V--GVS345B-V

Package Outline Dimensions(unit:mm)



Mounting Pad Layout(unit:mm)



Ordering Information

Part No.	Marking	Package	Shipping
GVS34B-V	VS34B	SMB	3000/Tape&Reel
GVS345B-V	VS345B	SMB	3000/Tape&Reel