




PIN	CONNECTION	PIN
1	Not connected	1
7	Ground	4
8	Output	5
14	Supply	8

Scale 1:1

Features

- Low voltage 3.3V operation
- Express manufacturing service
- Custom frequencies easily available
- Tight tolerance options
- Low cost for volume applications
- Industrial temperature range option

Specifications

GXO-U102F: Full size (14 pin DIL)

GXO-U102H: Half size (8 pin DIL)

Parameters	Variant		Option Codes
	F	H	
Package style: 14 pin DIL (full size) 8 pin DIL (half size)	■	■	
Frequency range: 125kHz ~ 200MHz	■	■	
Frequency stability: ±100ppm ±50ppm ±25ppm Other	■ □ □ □	■ □ □ □	B A specify
Operating temperature range: 0 to +70°C -40 to +85°C	■ □	■ □	I
Storage temperature range: -55 to +125°C	■	■	
Supply voltage (V_{DD}): +3.3V (±5%)	■	■	
Supply current (max): 10mA (125kHz ~ 0.99MHz) 15mA (1.0 ~ 5.0MHz) 20mA (>5.0 ~ 24.0MHz) 25mA (>24.0 ~ 70.0MHz) 35mA (>70.0 ~ 90.0MHz) 45mA (>90 ~ 200MHz)	■ ■ ■ ■ ■ ■	■ ■ ■ ■ ■ ■	
Driving ability: 30pF HCMOS / 5 LSTTL	■	■	
Output voltage: '0' level = 0.4V max '1' level = 90% V _{DD} min	■ ■	■ ■	
Start up time: 10ms max	■	■	
Rise / fall times: 6ns max (<80.0MHz) 5ns max (>80.0MHz)	■ ■	■ ■	
Waveform symmetry @ 50% V_{DD}: 45:55 max (<50.0MHz) 40:60 max (>50.0MHz)	■ ■	■ ■	

■ Standard. □ Optional - Please specify required code(s) when ordering

Ordering Information

Product name + variant + option codes (if any) + frequency

e.g: **GXO-U102F 40.0MHz** ±100ppm 0 to +70°C (standard)

GXO-U102F/BI 40.0MHz ±50ppm -40 to +85°C

Option code X (eg GXO-U102F/X) denotes a custom spec.

♦ Gull wing version available for SM. Refer to our website for details.