



## Features

- ▶ Ceramic package with metal lid
- ▶ High drive capability - up to 50pF
- ▶ Enable / disable tristate function
- ▶ 3.3V option with power saving function

## Enable / Disable Function

Input (pad 1)	Output (pad 3)
Open	Enabled
'1' level	Enabled
'0' level	High Impedance

## Specifications

**GXO-U115S:** 5.0V supply, E/D, low supply current

**GXO-U115H:** 5.0V supply, E/D high drive

**GXO-U115L:** 3.3V supply, E/D with power saving

Parameters	Variant			Option Codes
	S	H	L	
<b>Frequency range:</b> 1.8 ~ 50.0MHz 1.8 ~ 156MHz	■	■	■	
<b>Frequency stability:</b> ±100ppm ±50ppm ±25ppm	■ □ □	■ □ □	■ □ □	B A
<b>Operating temperature range:</b> -10 to +70°C -40 to +85°C	■ □	■ □	■ □	I
<b>Storage temperature range:</b> -55 to +125°C	■	■	■	
<b>Supply voltage (V<sub>DD</sub>):</b> +5.0V (±10%) +3.3V (±10%)	■	■	■	
<b>Supply current (mA max):</b> 1.8 ~ 50.0MHz >50.0 ~ 67.0MHz >67.0 ~ 125.0MHz >125 ~ 156MHz	35	45	18 18 40 50	
<b>Logic levels:</b> '0' level = 10%V <sub>DD</sub> max '1' level = 90%V <sub>DD</sub> min	■ ■	■ ■	■ ■	
<b>Start up time:</b> 10ms max	■	■	■	
<b>Waveform symmetry:</b> 40:60 max @ 50%V <sub>DD</sub>	■	■	■	
<b>Driving ability:</b> 10 LSTTL 15pF HCMOS 10 TTL 50pF HCMOS	■ ■	■ ■	■ ■	
<b>Rise / fall time:</b> 10ns max 7ns max	■	■	■	
<b>Enable / disable function:</b> Tristate (control via pad 1) 100ns / 100ns max 10ms / 150ns max	■ ■	■ ■	■ ■	
<b>Stand-by current (power-saving):</b> 10µA			■	

■ Standard. □ Optional - Please specify required code(s) when ordering

## Ordering Information

Product name + variant + option codes (if any) + frequency

eg: **GXO-U115H 40.0MHz** 5V, ±100ppm -10+70°C

**GXO-U115L/BI 40.0MHz** 3.3V, ±50ppm -40+85°C

Option code X (eg GXO-U115H/X) denotes a custom spec.

- ◆ Available on T&R - 2k pcs per reel.
- ◆ Refer to our website for T&R and soldering details.