


TRIPLE DIFFUSED SILICON NPN TRANSISTOR

... designed for low frequency power amplifier

MAXIMUM RATINGS

Characteristic	Symbol	Value	Unit
Collector Base Voltage	V_{CBO}	100	V
Collector Emitter Voltage	V _{CEO}	80	V
Emitter Base Voltage	V_{EBO}	5	V
Collector Current (DC)	I_C	4	Α
Collector Current (Peak)	I_C	8	Α
Collector power Dissipation	Pc	40	W
Junction Temperature	T_J	150	°C
Storage Temperature	T_{stg}	-55~150	°C



ELECTRICAL CHARACTERISTICS


Characteristic	Symbol	Test Condition	Min.	Тур.	Max.	Unit
Collector Cut Off Current	I_{CBO}	$V_{CB} = 80V$, $I_E = 0A$	ı	-	100	μΑ
Collector – Emitter Breakdown Voltage	V _{(BR)CEO}	$I_C = 50 \text{mA}, I_B = 0 \text{A}$	80	-	-	V
DC Current Gain	h_{FE}	$V_{CE} = 4V$, $I_{C} = 1A$	60	-	200	-
		$V_{CE} = 4V$, $I_{C} = 0.1A$	35	-	-	-
Collector Emitter Saturation Voltage	V _{CE(sat)}	$I_C = 2A$, $I_B = 0.2A$	-	-	1	V
Base Emitter Voltage	V_{BE}	$V_{CE} = 4V$, $I_{C} = 1A$	-	-	1.5	V
Transition Frequency	f_T	$V_{CE} = 5V$, $I_{C} = 0.5A$	-	10	1	MHz
Collector Out put Capacitance	C_{ob}	$V_{CB} = 20V$, $I_E = 0A$, $f=1MHz$	-	40	-	Pf

HIGH POWER DISSIPATION

MEDIUM SPEED POWER SWITCHING

Classification of hFE

Rank	В	С		
Range	60 to 120	100-200		



TO - 220AB

PMC reserves the right to make changes without further notice to any products herein. PMC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does PMC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential damages. The examples of applied circuits are provided as reference to the reader therefore we shall not undertake any responsibility for the exercise of rights by third parties.

© PMC Components Pte Ltd., Singapore, 2000

www.DataSheet4U.com