


Dual NPN Digital Transistors

HBC123ES6R


Features

- Built-in bias resistors enable the configuration of an inverter circuit without connecting external input resistors (see equivalent circuit).
- The bias resistors consist of thin-film resistors with complete isolation to allow negative biasing of the input. They also have the advantage of almost completely eliminating parasitic effects.
- Only the on/off conditions need to be set for operation, making device design easy.
- Two DTC123E chips in a SOT-363 package.
- Mounting by SOT-323 automatic mounting machines is possible.
- Mounting cost and area can be cut in half.
- Transistor elements are independent, eliminating interference.
- Complements the HBA123ES6R.
- Pb-free lead plating and halogen-free package.

Equivalent Circuit




Outline





Ordering Information

Table with 3 columns: Device, Package, Shipping. Row 1: HBC123ES6R-0-T1-G, SOT-363 (Pb-free lead plating and halogen-free package), 3000 pcs / Tape & Reel



Absolute Maximum Ratings (Each Transistor, Ta=25°C)

Table with 4 columns: Parameter, Symbol, Limits, Unit. Rows include Collector-Base Voltage, Collector-Emitter Voltage, Emitter-Base Voltage, Input Voltage, Output Current, Power Dissipation, Junction Temperature, Storage Temperature.

Note:*1.Device mounted on a FR-4 PCB, single sided copper, tin plated and standard footprint.


Characteristics (Each Transistor, Ta=25°C)

Table with 7 columns: Parameter, Symbol, Min., Typ., Max., Unit, Test Conditions. Rows include Collector-Base Cutoff Current, Collector-Emitter Cutoff Current, Emitter-Base Cutoff Current, DC Current Gain, Collector-Emitter Saturation Voltage, Input Voltage, Input Resistance, Resistance Ratio, Transition Frequency.


* Transition frequency of the device

Typical Characteristics


Current Gain vs Collector Current




Collector-Emitter Saturation Voltage vs Collector Current




Input Voltage vs Collector Current (ON characteristics)




Input Voltage vs Collector Current (OFF characteristics)




Power Derating Curve



Reel Dimension




Carrier Tape Dimension



Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds


Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T _{smax} to T _p)	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(T _{s min})	100°C	150°C
-Temperature Max(T _{s max})	150°C	200°C
-Time(t _{s min} to t _{s max})	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (T _L)	183°C	217°C
- Time (t _L)	60-150 seconds	60-150 seconds
Peak Temperature(T _p)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

SOT-363 Dimension



DIM	Millimeters		Inches		DIM	Millimeters		Inches	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.900	1.100	0.035	0.043	E1	2.150	2.450	0.085	0.096
A1	0.000	0.100	0.000	0.004	e	0.650	TYP	0.026	TYP
A2	0.900	1.000	0.035	0.039	e1	1.200	1.400	0.047	0.055
b	0.150	0.350	0.006	0.014	L	0.525	REF	0.021	REF
c	0.080	0.150	0.003	0.006	L1	0.260	0.460	0.010	0.018
D	2.000	2.200	0.079	0.087	θ	0°	8°	0°	8°
E	1.150	1.350	0.045	0.053					

Notes : 1.Controlling dimension : millimeters.
 2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.
 3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material :

- Lead : Pure tin plated.
- Mold Compound : Epoxy resin family, flammability solid burning class:UL94V-0.

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.