



NOTE:

1. DISPLAY TYPE: STN-Y/G-POSITIVE
2. DISPLAY MODE: TRANSPARENT
3. DRIVE METHOD: 1/8 DUTY, 1/4 BIAS, 4.6V Vop, 5V VDD
4. VIEWING DIR.: 6:00
5. OP₂ TEMP.: -20°C~70°C
6. ST TEMP.: -30°C~80°C
7. BACKLIGHT: COLOR-Y/G, 5.0±0.2V, 130mA, MIN.80 CD/m²
8. DRIVER IC:S6A0069

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
SYMBOL	VSS	VDD	VD	RS	R/W	E	DD	D1	D2	D3	D4	D5	D6	D7	LED+	LED-

TOLERANCE	HTD DISPLAY CO., LTD.		DESIGN	ZOJYS	06.04.01	STANDARD	REV. : A	SCALE : -
>0~6 ±0.10			CHECKED			TECHNOLOGY	PROJECTION:	UNIT : mm
>6~80 ±0.20			APPROVED			Q.A		SHEET : 1/1
>80~240 ±0.30								
>240~400 ±0.50								
// 1.0 ±0.10								

REV.	CHANGE CONTENT	BY	DATE