



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
	VSS	VDD	VO	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	LED+	LED-

NOTE:

- 1.STN-YELLOW-GREEN-TRANSFLECTIVE-POSITIVE
2. 1/16 DUTY, 1/5 BIAS
- 3.Vop=4.6V VDD=5.0V
- 4.OP.TEMP.: -20°C~70°C
- 5.ST.TEMP.: -30°C~80°C
- 6.VIEWING DIR.: 6:00
- 7.DRIVER IC: S6A0069
- 8.LED BACKLIGHT: Y/G 4.72V,40mA

TOLERANCE		HTD DISPLAY CO., LTD.		DRAWING No. : HC160211C-YF62L-VA	
>0~6	±0.10	DESIGN	ZOUYS	06.08.16	STANDARD
>6~80	±0.20	CHECKED			TECHNOLOGY
>80~240	±0.30	APPROVED			Q.A
>240~400	±0.50				
// L @ ±0.10					
		REV. : A	SCALE : -		
		PROJECTION:	UNIT : mm		
			SHEET : 1/1		

REV.	CHANGE CONTENT	BY	DATE