



REV.	CHANGE CONTENT	BY	DATE

PINS ASSIGNMENTS

PIN	SYMBOL
1	LED-A
2	LED-K
3	VSS
4	VDD
5	REST
6	RS
7	R/W
8	E
9	DB0
10	DB1
11	DB2
12	DB3
13	DB4
14	DB5
15	DB6
16	DB7

- NOTES:
1. DISPLAY TYPE:FSTN,POSITIVE,TRANSFLECTIVE
 2. VIEWING DIRECION: 6 O'CLOCK
 3. POWER SUPPLY FOR LOGIC : 3.0 V
 4. OPERATING TEMP: -20°C TO 70°C
 5. STORAGE TEMP: -30°C TO 80°C
 6. DRIVER IC: S6A0074(COB)
 7. DRIVER METHOD: 1/33 DUTY 1/6.7 BAIS
 8. LCD DRIVING VOLTAGE : 6.5V
 9. BACK LIGHT: LED,Y/G,4 Dices,Vf=2.0V,If=50mA

TOLERANCE				DRAWING No. : HC160402C-FF62L-VA			
>0~6	±0.10			DRAWING TITLE: LCM DRAWING			
>6~80	±0.20			FILE NO.: 8			
>80~240	±0.30			DESIGN	JHG	20061110	STANDARD
>240~400	±0.50			CHECKED			TECHNOLOGY
// L @	±0.10	APPROVED			Q.A		

REV. : A SCALE : -

www.DataSheet4U.com

SHEET : 1/1