



- NOTE:
1. DISPLAY TYPE: STN-Y/G-POSITIVE
 2. DISPLAY MODE: TRANSMISSIVE
 3. DRIVE METHOD: 1/16 DUTY, 1/5 BIAS, 4.6V Vop
 4. VIEWING DIR.: 6:00
 5. OP. TEMP.: 0°C~50°C
 6. ST. TEMP.: -20°C~60°C
 7. CONTROLLER: S6A0069X01-C0CX
 8. BACKLIGHT: LED Y/G 5.0V

PIN NO.	1	2	3	4	5	6	7~14	15	16
SYMBOL	Vss	Vdd	Vo	RS	R/W	E	DB0~DB7	LED+	LED-

TOLERANCE				HTDISPLAY CO., LTD.		DRAWING No. : HC200402C-YT60L-VA	
>0~6	±0.10					DRAWING TITLE: LCM DRAWING	
>6~80	±0.20	DESTGN		LI JINTANG	06.07.29	STANDARD	FILE NO: 8
>80~240	±0.30	CHECKED				TECHNOLOGY	REV. : A
>240~400	±0.50	APPROVED				Q. A	PROJECTION:
// 1.0 ±0.10							SCALE : 1:1
							UNIT : mm
							SHEET : 1/2

REV.	CHANGE CONTENT	BY	DATE