




ISSUE 1; January 2016

Description

- IQD understand that HC49S has become an industry standard abbreviation for the strip crystal version of the HC49 crystal. IQD do offer this crystal type in various package types, please see below for full details of IQD model names. Then please search for the IQD model name on our website to find the full specification or contact our Application Support team for assistance.
- HC49/4H Standard leaded package type
- HC49/3.5H 3.5mm height leaded package type
- HC49/3H 3mm height leaded package type
- HC49/2.5H 2.5mm height leaded package type
- HC49/4H AUTO Automotive version of the standard leaded package type
- HC49/4H SMX Standard SMD package type
- HC49/3.5HSMX 3.5mm height SMD package type
- HC49/3HSMX 3mm height SMD package type
- HC49/2.5HSMX 2.5mm height SMD package type
- HC49/4HSMX AUTO Automotive version of the SMD package type



Outline (mm) HC49/4H



Frequency Parameters

- Frequency 3.01MHz to 100.0MHz
- See specific IQD model data sheet for full details.

Electrical Parameters

- See specific IQD model data sheet for full details.

Operating Temperature Ranges

- 0 to 50°C
- -10 to 60°C
- -20 to 70°C
- -30 to 80°C
- -40 to 85°C
- -55 to 105°C
- -40 to 125°C


Environmental Parameters

- See specific IQD model data sheet for full details.



Compliance

- RoHS Status (2011/65/EU) Compliant
- REACh Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable


Outline (mm) = HC49-4HSMX



- * Package Height Options
- HC49/4HSMX 4.3mm max
 - HC49/3.5HSMX 3.7mm max
 - HC49/3HSMX 3.1mm max
 - HC49/2.5HSMX 2.85mm max



Solder Pad Layout



Sales Office Contact Details:

UK: +44 (0)1460 270200
Germany: 0800 1808 443

France: 0800 901 383
USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com