


# HDM40216H-4

## Dimensional Drawing

液晶之友 电话: 020-33819057  
Http://www.lcdfriends.com

40 Character x 2 Lines



Dimension tolerance: +/- 0.3mm


## Features

Character Format .....5x7 Dots with Cursor  
Backlight.....EL Optional  
Options....TN/Gray STN/Yellow STN, 12 o'Clock/6 o'Clock View  
Normal/Extended Temperature  
Normal/Negative Displays

## Physical Data

Module Size.....182.0W x 33.5H x 10.0T mm  
Viewing Area Size.....154.5W x 15.8H mm  
Weight.....70g

## Block Diagram



## Absolute Maximum Ratings

| PARAMETER              | SYMBOL          | MIN      | MAX      | UNIT |
|------------------------|-----------------|----------|----------|------|
| SUPPLY VOLTAGE         | $V_{DD}-V_{SS}$ | 0        | 7.0      | V    |
| SUPPLY VOLTAGE FOR LCD | $V_{DD}-V_O$    | 0        | 13.5     | V    |
| INPUT VOLTAGE          | $V_{IN}$        | $V_{SS}$ | $V_{DD}$ | V    |
| OPERATING TEMPERATURE  | $T_{OP}$        | 0        | 50       | °C   |
| STORAGE TEMPERATURE    | $T_{STG}$       | -20      | 70       | °C   |

## Electrical Characteristics (VDD=5.0±0.25V 25°C)

| PARAMETER            | SYM          | CONDITION         | MIN | TYP | MAX | UNIT |
|----------------------|--------------|-------------------|-----|-----|-----|------|
| INPUT HIGH VOLTAGE   | $V_{IH}$     | -                 | 2.2 | -   | -   | V    |
| INPUT LOW VOLTAGE    | $V_{IL}$     | -                 | -   | -   | .6  | V    |
| OUTPUT HIGH VOLTAGE  | $V_{OH}$     | $I_{OH}=0.2mA$    | 2.4 | -   | -   | V    |
| OUTPUT LOW VOLTAGE   | $V_{OL}$     | $I_{OL}=1.2mA$    | -   | -   | 0.4 | V    |
| POWER SUPPLY CURRENT | $I_{DD}$     | $V_{DD}=5.0V$     | -   | 1.0 | 2.2 | mA   |
| POWER SUPPLY FOR LCD | $V_{DD}-V_L$ | $T_A=25^{\circ}C$ | 4.3 | -   | 4.7 | V    |
| DRIVE METHOD         | 1/16 Duty    |                   |     |     |     |      |

## Pin Connections

| PIN NO. | SYMBOL   | LEVEL | FUNCTION                                   |
|---------|----------|-------|--------------------------------------------|
| 1       | $V_{SS}$ | -     | 0V                                         |
| 2       | $V_{DD}$ | -     | 5V                                         |
| 3       | $V_L$    | -     | -                                          |
| 4       | RS       | H/L   | H: Data input<br>L: Instruction data input |
| 5       | R/W      | H/L   | H: Data read<br>L: Data write              |
| 6       | E        | H/L   | Enable signal                              |
| 7       | D0       | H/L   | Data bus                                   |
| 8       | D1       | H/L   |                                            |
| 9       | D2       | H/L   |                                            |
| 10      | D3       | H/L   |                                            |
| 11      | D4       | H/L   |                                            |
| 12      | D5       | H/L   |                                            |
| 13      | D6       | H/L   |                                            |
| 14      | D7       | H/L   |                                            |
| 15      | A        |       | Anode for LED back light                   |
| 16      | K        |       | Cathode for LED back light                 |