



**NOTE:**

1. DISPLAY TYPE: STN-Y/G-POSITIVE-TRANSFLECTIVE
2. DRIVE METHOD: 1/32 DUTY, 1/5 BIAS, 7.5V Vop(typ.), 5V VDD
3. VIEWING DIR.: 6:00
4. OP. TEMP.:  $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$
5. ST. TEMP.:  $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$
7. BACKLIGHT: LED(Orange), Vf=5.0V, If<150mA 500cd/m<sup>2</sup>
8. DRIVER IC: NUU6450(OR EQUAL)
9. 提供和FCO配套使用的下接触的一个 18PIN插座一个

Wavelength 625±5nm

**TOLERANCE**

>0~6	±0.10
>6~80	±0.20
>80~240	±0.30
>240~400	±0.50
// L ⊙	±0.10

**HTDISPLAY CO., LTD.**

DESIGN LI JINTANG 06.06.23 STANDARD  
 CHECKED TECHNOLOGY  
 APPROVED Q.A

DRAWING No. : HG1223206C-YF62L-VA  
 DRAWING TITLE: LCD MODULE  
 FILE NO.: 8

REV. : A  
 SCALE : -  
 PROJECTION: UNIT : MM  
 SHEET : 1/2

REV.	CHANGE CONTENT	BY	DATE
B	增加泡棉、更改电极焊位置及接口	LJT	05.08.18