



NOTE:

1. DISPLAY TYPE: STN-Y/G-POSITIVE-TRANSFLECTIVE
2. DRIVE METHOD: 1/32 DUTY, 1/5 BIAS, 7.5V Vop(typ.), 5V VDD
3. VIEWING DIR.: 6:00
4. OP. TEMP.: $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$
5. ST. TEMP.: $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$
7. BACKLIGHT: LED(Y/G), $V_f = 5.0\text{V}$, $I_f < 150\text{mA}$ $500\text{CD}/\text{m}^2$
Wavelength $570 \pm 2.5\text{nm}$
8. DRIVER IC: NUU6450(OR EQUAL)
9. 提供和FCO配套使用的下接触的18PIN插座一个

TOLERANCE	
>0~6	± 0.10
>6~80	± 0.20
>80~240	± 0.30
>240~400	± 0.50
// L ϕ	± 0.10

HTDISPLAY CO., LTD.

HTDISPLAY

DRAWING No. : HG1233206C-YF62L-VB
 DRAWING TITLE: LCD MODULE
 FILE NO. : 8

DESIGN	LI JINTANG	06.06.23	STANDARD
CHECKED			TECHNOLOGY
APPROVED			Q.A
REV. : A			SCALE : -
PROJECTION:			UNIT : MM
			SHEET : 1/2

REV.	CHANGE CONTENT	BY	DATE
B	增加泡棉、更改电极焊位置及接口	LJT	05.08.18