



NOTE:

1. DISPLAY TYPE: STN-Y/G-POSITIVE-TRANSFLECTIVE
2. DRIVE METHOD: 1/32 DUTY, 1/5 BIAS, 6.0V Vop(typ.), 3.3V VDD
3. VIEWING DIR.: 6:00
4. OP. TEMP.: $-20^{\circ}C \sim 70^{\circ}C$
5. ST. TEMP.: $-40^{\circ}C \sim 80^{\circ}C$
7. BACKLIGHT: LED(Y/G), $V_f = 5.0V$, $I_f < 150mA$ 500CD/m²
Wavelength 570±2.5nm
8. DRIVER IC: NUU6450(OR EQUAL)
9. 提供和FC0配套使用的下接触的18PIN插座一个

HTDISPLAY

HTDISPLAY CO., LTD.

DRAWING No. : HG1233206C-YF62L-VC
DRAWING TITLE: LCD MODULE
FILE NO.: 8

TOLERANCE	>0~6 ±0.10	>6~80 ±0.20	>80~240 ±0.30	>240~400 ±0.50	// L ⊙ ±0.10
DESIGN	LI JINTANG	06.06.23	STANDARD	CHECKED	APPROVED
TECHNOLOGY	Q.A				
REV. : A	SCALE : -				
PROJECTION:	UNIT : MM				
	SHEET : 1/2				

REV.	CHANGE CONTENT	BY	DATE
B	增加泡棉、更改电极焊位置及接口	LJT	05.08.18