



DETAIL A

- Note:
1. Display Mode: STN, Y/G, POSITIVE, Transflective
 2. View Direction: 6 O'Clock
 3. Driver Method: 1/32 Duty, 1/6Bias
 4. LCD Operating Voltage: 5.0V
 5. Operating Temperature: -20° C-70° C
 6. Storage Temperature: -40° C- 85° C
 7. Controller: SED1520D0A OR EQUAL.
 8. LED: COLOR: Y/G 5.0V 40mA

PIN No	1	2	3	4	5	6	7	8	9	10-17	18	19	20
Symbol	VSS	VDD	V0	A0	NC	E2	NC	E1	R/W	DB0-DB7	RST	LEDA	LEDK

TOLERANCE		HTDISPLAY		HTDISPLAY CO., LTD.		DRAWING No.: HG122321TC-YF62L-VA	
>0~6	±0.10	DESIGN	LJT	06.10.11	STANDARD	REV. : A	SCALE : -
>6~80	±0.20	CHECKED			TECHNOLOGY	PROJECTION:	UNIT : MM
>80~240	±0.30	APPROVED			Q. A	FILE NO. : 8	SHEET : 1/1
>240~400	±0.50						
// 1.0	±0.10						

REV.	CHANGE CONTENT	BY	DATE