



Pins Description

Pin No	Symbol	Description
1	A	LED+
2	K	LED-
3	V0	LCD Operation Voltage
4	VDD	Power Supply Pin :+5.0V
5	VSS	Ground
6	E	Enable signal
7	C/D	L:Data; H:Instruction
8	R/W	Write and read signal
9	CS	Chip select signal, H:left, L:right
10	/RST	Reset: L: Enable; H: Disable
11-18	DD-D7	Data Bus

- NOTE:
1. DISPLAY TYPE: STN-POSITIVE-TRANSPARENT-REFLECTIVE-Y/G
  2. VIEWING DIR.: 6:00
  3. DRIVE METHOD: 1/32DUTY, 1/6BIAS, Vop=8.0V,VDD=5.0V
  4. OP. TEMP.: -20°C~70°C
  5. ST. TEMP.: -30°C~80°C
  6. CONTROLLER: S6B0108,S6B0107
  - 7.BACKLIGHTLED COLDR-Y/G,Vf=4.1±0.2V,If=350mA,

www.

REV.	CHANGE CONTENT	BY	DATE

TOLERANCE		HTDISPLAY CO., LTD.		DRAWING No. : HG1283203C-YF62L-VA	
>0~6	±0.10	DESIGN	ZOUYS	REV. : A	SCALE : -
>6~80	±0.20	CHECKED		PROJECTION:	UNIT : mm
>80~240	±0.30	APPROVED		Φ	SHEET : 1/1
>240~400	±0.50				
L ⊕ ±0.10					