

HL6503MG

Visible High Power Laser Diode for DVD-RAM

HITACHI

ADE-208-670D (Z)
5th Edition
Dec. 2000

Description

The HL6503MG is a 0.66 μm band AlGaInP laser diode (LD) with a multi-quantum well (MQW) structure. It is suitable as a light source for large capacity optical disc memories, such as DVD-RAM, and various other types of optical equipment.

Hermetic sealing of the small package (ϕ 5.6 mm) assures high reliability.

Application

- Optical disc memories
- Optical equipment

Features


- High output power : 50 mW (CW)
- Visible light output : $\lambda_p = 664 \text{ nm Typ}$
- Small package : ϕ 5.6 mm
- Low astigmatism : 5 $\mu\text{m Typ}$ ($P_o = 5 \text{ mW}$)

Internal Circuit

Package Type
• HL6503MG: MG



Internal Circuit



Absolute Maximum Ratings (T_C = 25°C)

Item	Symbol	Value	Unit
Optical output power	P _O	50	mW
Pulse optical output power	P _{O(pulse)}	70 *	mW
Laser diode reverse voltage	V _{R(LD)}	2	V
Operating temperature	Topr	−10 to +60	°C
Storage temperature	Tstg	−40 to +85	°C





Note: Pulse condition : Pulse width = 100 ns, duty = 50%

Optical and Electrical Characteristics (T_C = 25°C)

Item	Symbol	Min	Typ	Max	Unit	Test Conditions
Optical output power	P _O	50	—	—	mW	Kink free *
Pulse optical output power	P _{O(pulse)}	70	—	—	mW	Kink free *
Threshold current	I _{th}	30	45	60	mA	—
Operating current	I _{op}	—	115	135	mA	P _O = 50 mW
Operating voltage	V _{OP}	2.1	2.6	3.0	V	P _O = 50 mW
Beam divergence parallel to the junction	θ//	7	8.5	11	deg.	P _O = 50 mW
Beam divergence parpendicular to the junction	θ⊥	18	21	26	deg.	P _O = 50 mW
Asitgmatism	A _s	—	5	—	μm	P _O = 5 mW, NA = 0.55
Lasing wavelength	λ _p	655	664	667	nm	P _O = 50 mW


Note: Kink free is confirmed at the temperature of 25°C.

Typical Characteristic Curves




Typical Characteristic Curves (cont)


Lasing Spectrum




Wavelength vs. Case Temperature




Far Field Pattern



Astigmatism vs. Optical Output Power




Typical Characteristic Curves (cont)



Package Dimensions

Unit: mm



Hitachi Code	LD/MG
JEDEC	—
EIAJ	—
Mass (reference value)	0.3 g

Cautions

1. Hitachi neither warrants nor grants licenses of any rights of Hitachi's or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document. Hitachi bears no responsibility for problems that may arise with third party's rights, including intellectual property rights, in connection with use of the information contained in this document.
2. Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.
3. Hitachi makes every attempt to ensure that its products are of high quality and reliability. However, contact Hitachi's sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic, safety equipment or medical equipment for life support.
4. Design your application so that the product is used within the ranges guaranteed by Hitachi particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. Hitachi bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating Hitachi product does not cause bodily injury, fire or other consequential damage due to operation of the Hitachi product.
5. This product is not designed to be radiation resistant.
6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from Hitachi.
7. Contact Hitachi's sales office for any questions regarding this document or Hitachi semiconductor products.

1. The laser light is harmful to human body especially to eye no matter what directly or indirectly. The laser beam shall be observed or adjusted through infrared camera or equivalent.

HITACHI

Hitachi, Ltd.

Semiconductor & Integrated Circuits.
Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan
Tel: Tokyo (03) 3270-2111 Fax: (03) 3270-5109

URL NorthAmerica : <http://semiconductor.hitachi.com/>
 Europe : <http://www.hitachi-eu.com/hel/ecg>
 Asia : <http://sicapac.hitachi-asia.com>
 Japan : <http://www.hitachi.co.jp/Sicd/indx.htm>

For further information write to:

Hitachi Semiconductor (America) Inc. 179 East Tasman Drive, San Jose, CA 95134 Tel: <1> (408) 433-1990 Fax: <1> (408) 433-0223	Hitachi Europe GmbH Electronic Components Group Dornacher StraÙe 3 D-85622 Feldkirchen, Munich Germany Tel: <49> (89) 9 9180-0 Fax: <49> (89) 9 29 30 00	Hitachi Asia Ltd. Hitachi Tower 16 Collyer Quay #20-00, Singapore 049318 Tel : <65>-538-6533/538-8577 Fax : <65>-538-6933/538-3877 URL : http://www.hitachi.com.sg	Hitachi Asia (Hong Kong) Ltd. Group III (Electronic Components) 7/F., North Tower, World Finance Centre, Harbour City, Canton Road Tsim Sha Tsui, Kowloon, Hong Kong Tel : <852>-(2)-735-9218 Fax : <852>-(2)-730-0281 URL : http://www.hitachi.com.hk
	Hitachi Europe Ltd. Electronic Components Group. Whitebrook Park Lower Cookham Road Maidenhead Berkshire SL6 8YA, United Kingdom Tel: <44> (1628) 585000 Fax: <44> (1628) 585160	Hitachi Asia Ltd. (Taipei Branch Office) 4/F, No. 167, Tun Hwa North Road, Hung-Kuo Building, Taipei (105), Taiwan Tel : <886>-(2)-2718-3666 Fax : <886>-(2)-2718-8180 Telex : 23222 HAS-TP URL : http://www.hitachi.com.tw	

Copyright © Hitachi, Ltd., 2000. All rights reserved. Printed in Japan.
Colophon 2.0